








EROSION AND SILTATION CONTROL  
EROSION CONTROL BLANKET INSTALLATION



NOTE:  
If a Single Net Blanket is used the side with the netting should be on the top once the blanket is installed.




PIPE INLETS  
INSTALLATION AT PIPE ENDS









BLANKET LAYOUT  
CHANNEL OR SLOPE INSTALLATION

3.8 staples per square yard  
using 8-inch 11 gauge wire  
"u" staples.



NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-03-13	
REVISIONS	
DATE	CHANGE
06-26-14	Changed standard drawing number from D-708-5 to D-255-2.
07-27-15	Changed installation details such as trench depth and overlap dimensions.

This document was originally issued and sealed by  
Roger Weigel  
Registration Number  
PE-2930,  
on 07/27/15 and the original document is stored at the North Dakota Department of Transportation



NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-03-13	
REVISIONS	
DATE	CHANGE
06-26-14	Changed standard drawing number from D-708-2 to D-256-1. Deleted silt fence details.
10-17-17	Updated to active voice.

This document was originally issued and sealed by Roger Weigel Registration Number PE-2930, on 10-17-2017 and the original document is stored at the North Dakota Department of Transportation

# STANDARD SLOPE PROTECTION UNDER BRIDGES

D-258-1

## NOTES:

The toe wall shall be placed before concrete is placed on the slope.

All inside panels shall be 5'-6" square. All outside panels shall be adjustable from 5'-0" minimum to 8'-0" maximum.

All transverse joints shall be 1/2" deep grooved joints sealed with concrete joint sealer. All longitudinal joints shall be construction joints with 1/2" deep grooves sealed with concrete joint sealer. All cracks that may have developed before the project has been accepted shall also be sealed with concrete joint sealer. An elastomeric joint sealant which meets ASTM C-920, CI 25, can be used in lieu of the sealants allowed in 826.02 of the ND Standard Specifications.


Wherever parts of a structure, such as piers, etc. are contacted by the slope protection, preformed expansion joint filler shall be installed between the contact areas as shown.

Shear keys shall be placed in every panel on the slope, as shown.


The welded wire fabric (WWF) shall be supplied in sheets. When it is necessary to make the WWF continuous, a lap splice at least 8" long shall be used.

Several shorter bars may be substituted for the continuous Bar 2 x 3/8. If the substitution is made, the space from the end of the bar to the first hole shall not be more than 6 inches.


The bolts to hold the neoprene gland in place shall be installed into the abutment by a mechanical or chemically bonded method.




SLOPE PROTECTION LAYOUT




SKEWED SLOPE PROTECTION LAYOUT




B-B




#4 SHEAR KEY BENT BAR DETAIL




#4 SIDE WALL BENT BAR DETAIL



C-C



A-A




#4 TOE WALL BENT BAR DETAIL

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07/10/14	
REVISIONS	
DATE	CHANGE
07/10/14	CHANGED FROM D-708-1


This document was originally issued and sealed by Terrence R. Udland, Registration Number PE-2674, on 07/10/14 and the original document is stored at the North Dakota Department of Transportation

EROSION AND SILTATION CONTROLS - SILT FENCE




INSTALLATION DETAIL


Minimize disturbance of ground around trench and smooth surface after excavation to avoid concentrating flows. Compact to prevent undercutting flows.




TYPICAL ISOMETRIC



MACHINE SLICED SILT FENCE



SILT FENCE SUPPORTED




SILT FENCE UNSUPPORTED

- NOTES:
1. Install the ends of the silt fence to point slightly upslope to prevent sediment from flowing around the ends of the fence.
  2. Place splices outside low spots.
  3. Install silt fencing parallel to contour lines.
  4. Do not embed silt fence when placed in standing water.
  5. Silt fence material does not need to reach the top of woven wire support.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-03-13	
REVISIONS	
DATE	CHANGE
06-26-14	Standard drawing resulted from splitting standard D-708-2.
06-27-16	Revised details & added new ones.


This document was originally issued and sealed by  
 Roger Weigel  
 Registration Number  
 PE- 2930,  
 on 06/27/16 and the original document is stored at the  
 North Dakota Department  
 of Transportation

EROSION CONTROL  
FIBER ROLL PLACEMENT DETAILS




\*Optional Weir. Use in flat areas, such as the Red River Valley, where there is potential for water to back up on adjacent property. Lower fiber roll enough to prevent water from backing up on adjacent property. Do not use 20-inch fiber rolls in flat areas where there is potential for water to back up on adjacent property.


12 OR 20 INCH FIBER ROLL - DITCH BOTTOM




PLAN VIEW FOR SLOPE APPLICATION



PLAN VIEW FOR DITCH APPLICATION



Detail A  
Fiber Roll Overlapping Staking Detail



Detail B  
Fiber Roll Staking Detail


FIBER ROLL DIAMETER	NOMINAL STAKE SIZE	MINIMUM STAKE LENGTH	MINIMUM TRENCH DEPTH	MAXIMUM TRENCH DEPTH
6"	2" x 2"	18"	2"	2"
12"	2" x 2"	24"	2"	3"
20"	2" x 2"	36"	3"	5"

NOTE: Runoff must not be allowed to run under or around roll.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-18-10	
REVISIONS	
DATE	CHANGE
06-10-13	Added plan view for ditch and slope application, Added table with values for stake and trench dimensions.
10-04-13	Revised fiber roll overlap detail.
06-26-14	Changed standard drawing number from D-708-7 to D-261-1

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 06/26/14 and the original document is stored at the North Dakota Department of Transportation


PILE SPLICE DETAILS



ENLARGED VIEW




Flame scarf inside of both flanges and one side of web of upper section.



PILE	8"	10"	12"	14"
"F" FLANGE	5"	6 1/2"	8"	10"
"W" WEB	4"	5 1/2"	6 1/2"	8"

H-PILE SPLICE DETAIL



ALTERNATE H-PILE SPLICE DETAIL

NOTES:


Steel H-Pile may be spliced with complete penetration groove welds in both flanges and web in lieu of using the reinforcing plates.

AWS classification E70XX Low Hydrogen Electrodes shall be used.


\* Welds made without the use of backing material shall have the root gouged to sound metal and welded from the second side.

All welding shall conform to the current AASHTO/AWS D1.5 Bridge Welding Code.


The thickness of the steel square plates shall at a minimum be as thick as the flanges and web of the pile being spliced.




Backing Ring may be made from pile cut-offs or other material of a like quality.



END PLATE DETAIL



STEEL-ENCASED CONCRETE PILE SPLICE DETAIL





ENLARGED VIEW

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
09/14/11	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Terrence R. Udland, Registration Number PE-2674, on 09/14/11 and the original document is stored at the North Dakota Department of Transportation


ATTENUATION DEVICE



Outer Containers




Cones



Typical Assembly

Typical Module Construction Detail




Reflective Sheet Detail

Note:  
Apply Type IV reflective sheeting (as specified in the NDDOT Standard Specifications) directly to the outer container of the last attenuation device facing traffic, following the details above. Or apply the sheet to a metallic sheet and attach it to the container with approved fasteners.


(A) Use 3" orange sheeting for temporary installations, and 3" yellow sheeting for permanent installations.

	Fill Chart				
	Module Weights (LBS)				
Distance from top edge	8 1/2"	5"	4"	3"	0"



Type B Layout

Note:  
Angle attenuation devices 10 degrees towards traffic when placed at piers offset from roadway.



Section A-A (Type B Layout)

Type B Attenuation Device											
Module Number	Dash Number										
	75	70	65	60	55	50	45	40	35	30	25
Module Weights (LBS)											
B1	2100										
B2	2100										
B3	2100	2100	2100	2100	2100	2100	2100	2100	2100		
B4	2100	2100	2100	2100	2100	2100	2100	2100	2100		
B5	1400	1400	1400	1400	1400	1400	1400	1400	1400	1400	1400
B6	1400	1400	1400	1400	1400	1400	1400	1400	1400	1400	1400
B7	1400	1400	1400	1400	1400	1400	1400	1400	1400	1400	1400
B8	1400	1400	1400	1400	1400	1400	1400	1400	1400	1400	1400
B9	700	700	700	700	700	700	700	700	700	700	700
B10	700	700	700	700	700	700	700	700	700	700	700
B11	700	700	700	700	700	700	700	700	700	700	700
B12	700	700	700	700	700	700	700	700	700	700	700
B13	700	700	700	700	700	700	700	700	700	700	700
B14	400	400	400	400	400	400	400	400	400	400	400
B15	400	400	400	400	400	400	400	400	400	400	400
B16	200	200	200	200	200	200	200	200	200	200	200
Length (L)	34.2'	30.7'	30.7'	30.7'	30.7'	30.7'	30.7'	30.7'	30.7'	27.2'	27.2'
Module Weights (LBS)	Replacement Module										
	2100	1	1	1	1	1	1	1	1	1	1
	1400	1	1	1	1	1	1	1	1	1	1
	700	2	2	2	2	2	2	2	2	2	2
	400	1	1	1	1	1	1	1	1	1	1
200	2	2	2	1	1	1	1	1	1	1	

Notes:

- Materials
  - Use modules manufactured from frangible polyethylene material which shatters upon impact.
  - Fill modules with class 43 aggregate meeting NDDOT Standard Specifications aggregate requirements. Use fill with a unit weight of at least 100 pounds per cubic foot. Use fill with a moisture content of 2% or less when left over winter.
- Modules
 

Provide modules in two sizes containing volumes of either 2, 4, 7, 14, or 21 cubic feet minimum.

  - Provide three components for 2, 4, or 7 cubic foot module containers:
    - A 14 C.F., yellow outer container.
    - A black lid securely locking over the top lip of the container.
    - A variable cone-shaped supporting insert capable of supporting 200, 400, or 700 pounds of sand mass to allow for three sizes of modules. Place cone inserts inside the 14 cubic foot container.
  - Provide two components for the 14 cubic foot module container:
    - A 14 C.F., yellow outer container.
    - A black lid securely locking over the top lip of the container.
  - Provide two components for the 21 cubic foot module container:
    - A 36" height X 36" width yellow outer container.
    - A black lid which locks securely over the top of the container.
- For temporary installations use Energite or Fitch attenuation barrels manufactured by Energy Absorption Systems of Chicago, IL, TrafFix barrels manufactured by TrafFix Devices, Inc. of San Clemente, CA, or approved equal modules. As an option, place attenuation devices on 3 1/2" maximum thickness pallets to facilitate maintenance.
- For permanent installations use Barrel Attenuation Device consisting of one-piece outer sand container modules with separate detachable lid. Energite attenuation barrels manufactured by Energy Absorption Systems of Chicago, IL, TrafFix barrels manufactured by TrafFix Devices, Inc. of San Clemente, CA, or approved equal meet these requirements.
- The Typical Module Construction Detail and Type B Layout are based on the Energite Crash Cushion manufactured by Energy Absorption. Provide any required layouts and details from other sand filled attenuation module manufacturers which differ from those shown here.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
9-25-12	
REVISIONS	
DATE	CHANGE
7-18-14	Revised sheeting in reflective sheet detail
9-27-17	Update to active voice

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 9/27/2017 and the original document is stored at the North Dakota Department of Transportation

CONSTRUCTION SIGN DETAIL

D-704-5

<b>SIGN NUMBER</b>	G20-10-108	STATION(S):           AREA: 36.0 Sq.Ft.				
<b>WIDTH x HEIGHT</b>	9'-0" x 4'-0"					
<b>BORDER WIDTH</b>	1.25" (inset 0.75")					
<b>CORNER RADIUS</b>	3"					
<b>MOUNTING</b>	Ground					
<b>BACKGROUND</b>	TYPE: IV Reflective					
	COLOR: Fluorescent Orange					
<b>LEGEND/BORDER</b>	TYPE: Non-Refl					
	COLOR: Black					
<b>SYMBOL</b>	X Y WID HT ANGLE					
	42.1 6.2 24 4 0					

Dimensions are in inches.tenths      Letter locations are panel edge to lower left corner

LETTER POSITION (X)															LENGTH	SIZE	SERIES		
C	O	N	S	T	R	U	C	T	E	D	B	Y			69.7	6	D 2000		
19.2	24.5	30	35.1	39.7	44.3	49.4	54.8	59.7	64.3	69	73.1	79.1	83.7						
Y	O	U	R		C	O	M	P	A	N	Y	N	A	M	E		91.5	6	D 2000
8.3	14.2	19.8	25.3	29.4	35.4	40.7	46.2	52.4	56.8	62.8	67.8	72.9	78.9	83.9	89.9	96			
Y	O	U	R		T	O	W	N			N	D					64.6	6	D 2000
21.7	27.6	33.2	38.7	42.8	48.8	53.3	58.4	64.6	69.6	70.7	76.7	82.2							

Notes:

1. Post mount sign a distance of 1/2A following the End Road Work (G20-2a-48) sign (maximum 2 signs per project.)
2. Use sign on rural projects with a 30 day or longer duration (not required on seal coats or other short duration projects.)
3. Do not place sign in urban areas or within city limits.


Advance Warning Sign Spacing (A)			
Road Type	Distance between signs min. (ft)		
	A	B	C
Urban - Low Speed (30 mph or less)	150	150	150
Urban - Low Speed (over 30 to 40 mph)	280	280	280
Urban - High Speed (over 40 mph to 50 mph)	360	360	360
Rural - High Speed (over 50 mph to 65 mph)	720	720	720
Urban Expressway and Freeway (55 mph to 60 mph)	850	1350	2200
Rural Expressway and Freeway (70 mph to 75 mph)	1000	1500	2640
Interstate/4-Lane Divided (Maintenance and Surveying)	750	1000	1500

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION		This document was originally issued and sealed by <b>Roger Weigel</b> Registration Number <b>PE- 2930</b> , on <b>9/27/2017</b> and the original document is stored at the North Dakota Department of Transportation
8-22-12		
REVISIONS		
DATE	CHANGE	
7-18-14 9-27-17	Revise sheeting to type IV Updated to active voice	




BREAKAWAY SYSTEMS FOR CONSTRUCTION ZONE SIGNS

Perforated Tube




Multi-Directional Slip Base Assembly

Traffic Flow




Top Post Receiver  
Plate - ASTM A572 grade 50  
Angle Receiver - 2 1/2" x 2 1/2" x 3/8" ASTM A36 structural angle


Traffic Flow





Bottom Soil Stub  
Tube - 3"x3"x7 gauge ASTM A500 grade B tube  
Stabilizing Wing - 7 gauge H.R.P.O. ASTM A1011  
Plate - ASTM A572 grade 50



Anchor Unit and Post Assembly



Multi-Directional Slip Base Anchor Unit and Post Sleeve Assembly



Bolt Retainer for Base Connection  
Bolt Retainer - 1/2" Reprocessed Teflon

Notes:

1. Torque slip base bolts as specified by manufacturer.
2. Use anchor with 43.9 KSI yield strength and 59.3 KSI tensile strength.
3. Provide 4" vertical clearance for anchor or breakaway base. Measure the 4"x60" measurement above and below post location and back and ahead of post.
4. In concrete sidewalk, use same anchor without wings.
5. Provide more than 7' between the first and fourth posts of a four post sign.

Telescoping Perforated Tube

Number of Posts	Post Size in.	Wall Thickness Gauge	Sleeve Size in.	Wall Thickness Gauge	Slip Base	Anchor Size without Slip Base in.
1	2	12			No	2 1/4
1	2 1/4	12			No	2 1/2
1	2 1/2	12			(A)	3
1	2 1/2	10			Yes	
1	2 1/4	12	2	12	Yes	
1	2 1/2	12	2 1/4	12	Yes	
2	2	12			No	2 1/4
2	2 1/4	12			No	2 1/2
2	2 1/2	12			Yes	
2	2 1/2	12			Yes	
2	2 1/4	10	2	12	Yes	
2	2 1/2	12	2 1/4	12	Yes	
3 & 4	2 1/2	12			Yes	
3 & 4	2 1/2	10			Yes	
3 & 4	2 1/2	12	2 1/4	12	Yes	
3 & 4	2 1/4	12	2	12	Yes	
3 & 4	2 1/2	10	2 3/16	10	Yes	

Properties of Telescoping Perforated Tube

Tube Size in.	Wall Thickness in.	U.S. Standard Gauge	Weight per Foot lbs.	Moment of Inertia in. <sup>4</sup>	Cross Sec. Area in. <sup>2</sup>	Section Modulus in. <sup>3</sup>
1 1/2 x 1 1/2	0.105	12	1.702	0.129	0.380	0.172
2 x 2	0.105	12	2.416	0.372	0.590	0.372
2 1/4 x 2 1/4	0.105	12	2.773	0.561	0.695	0.499
2 3/16 x 2 3/16	0.135	10	3.432	0.605	0.841	0.590
2 1/2 x 2 1/2	0.105	12	3.141	0.804	0.803	0.643
2 1/2 x 2 1/2	0.135	10	4.006	0.979	1.010	0.785

Top Post Receiver Data Table

Square Post Sizes (B)	A	B	C	D	E	F
2 3/16" x 10 ga.	1 5/16"	2 1/2"	3 1/2"	2 5/32"	1 33/64"	1 7/8"
2 1/2" x 10 ga.	1 3/32"	2 1/2"	3 5/16"	5/8"	1 21/32"	1 3/4"

(A) Use breakaway base when support is placed in weak soils. Engineer determines if soils are weak.


(B) For additional wind load, insert the 2 3/16" x 10 ga. into 2 1/2" x 10 ga.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
2-28-14	
REVISIONS	
DATE	CHANGE
9-27-17	Updated to active voice


This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 9/27/2017 and the original document is stored at the North Dakota Department of Transportation

BREAKAWAY SYSTEMS FOR CONSTRUCTION ZONE SIGNS

U-Channel Post



Detail A




Front View

Side View


Back View

Breakaway U-Channel Detail Alternate A

Install a maximum of 2 posts within 7'.




Retainer Strap Detail



Breakaway U-Channel Splice Detail Alternate B (2.5 and 3 lb/ft)

Install a maximum of 3 posts within 7'.



Breakaway U-Channel Splice Detail Alternate C (2.5 and 3 lb/ft)

Install a maximum of 3 posts within 7'.

Alternate A Steps of Installation:


1. a) Drive anchor unit to within 12" of ground level.  
b) Establish proper assembly by lining up bottom hole of retainer strap with 6th hole from the top of the anchor unit.  
c) Assemble strap to back of anchor unit using 5/16"x2" bolt, lock washer and nut.  
d) Rotate strap 90° to left.
2. a) Drive anchor unit to 4" above ground.  
b) Rotate strap to vertical position.
3. a) Place 5/16"x2" bolt, lock washer and nut in bottom of sign post to facilitate alignment of sign post with proper hole in anchor unit.  
b) Alternately tighten two connector bolts.
4. Complete assembly by tightening 5/16"x2" bolt (this fastens sign post to retainer strap).
5. Properly nest base post, strap, and sign post. Proper nesting occurs when all flat surfaces of the base post, strap, and sign post at the bolts have full contact across the entire width.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
2-28-14	
REVISIONS	
DATE	CHANGE
9-27-17	Updated to active voice


This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 9/27/2017 and the original document is stored at the North Dakota Department of Transportation

CONSTRUCTION SIGN DETAILS  
TERMINAL AND GUIDE SIGNS


D-704-9




G20-1-60  
Legend: black (non-refl)  
Background: orange




G20-1b-60  
Legend: black (non-refl)  
Background: orange




G20-2-48  
Legend: black (non-refl)  
Background: orange




G20-4b-36  
Legend: black (non-refl)  
Background: orange




G20-50a-72  
Legend: black (non-refl)  
Background: orange




G20-52a-72  
Legend: black (non-refl)  
Background: orange




G20-55-96  
Legend: black (non-refl)  
Background: orange




E5-1(L or R)-48  
Legend: white  
Background: green (orange optional)




M4-8-36  
Legend: black (non-refl)  
Background: orange




M4-9(L or R)-30 & M4-9-30  
Legend: black (non-refl)  
Background: orange




E5-1-48




G20-50a-72  
G20-52a-72



M4-9(L or R)-30  
Right or Left



M4-9(L or R)-30  
Advanced Right or Left



M4-9-30  
Straight

ARROW DETAILS


NOTES:

(A) Arrow may be right or left of the legend to indicate construction to the right or left.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-13-13	
REVISIONS	
DATE	CHANGE
8-17-17	Added sign & background color

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 8/17/17 and the original document is stored at the North Dakota Department of Transportation


CONSTRUCTION SIGN DETAILS  
REGULATORY SIGNS




R1-50P-24  
Legend: black (non-refl)  
Background: white




R11-3c-60  
Legend: black (non-refl)  
Background: white



R2-1aP-24  
Legend: black (non-refl)  
Background: white



R11-4a-60  
Legend: black (non-refl)  
Background: white



R11-2a-48  
Legend: black (non-refl)  
Background: white


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-13-13	
REVISIONS	
DATE	CHANGE
8-17-17	Revised sign number

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 8/17/17 and the original document is stored at the North Dakota Department of Transportation


CONSTRUCTION SIGN DETAILS  
WARNING SIGNS

WORD	LETTER SPACING
AHEAD	Standard
200 FT	Standard
350 FT	Standard
500 FT	Standard
1000 FT	Reduce 40%
1500 FT	Reduce 40%
½ MILE	Reduce 50%
1 MILE	Standard


\* DISTANCE MESSAGES




W5-8-48  
Legend: black (non-refl)  
Background: orange




W8-53-48  
Legend: black (non-refl)  
Background: orange




W8-56-48  
Legend: black (non-refl)  
Background: orange




W5-9-48  
Legend: black (non-refl)  
Background: orange




W8-54-48  
Legend: black (non-refl)  
Background: orange



W9-3a-48  
Legend: black (non-refl)  
Background: orange




W5-9-48




W9-3a-48

ARROW DETAILS



W8-9a-48  
Legend: black (non-refl)  
Background: orange




W8-55-48  
Legend: black (non-refl)  
Background: orange


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-13-13	
REVISIONS	
DATE	CHANGE
8-17-17	Updated sign number
5-31-18	Revised sign and arrow details

This document was originally issued and sealed by  
**Roger Weigel,**  
Registration Number  
PE-2930,  
on 5/31/18 and the original document is stored at the North Dakota Department of Transportation


CONSTRUCTION SIGN DETAILS  
WARNING SIGNS



W20-51-48  
Legend: black (non-refl)  
Background: orange




W21-51-48  
Legend: black (non-refl)  
Background: orange




W22-8-48  
Legend: black (non-refl)  
Background: orange

WORD	LETTER SPACING
AHEAD	Standard
200 FT	Standard
350 FT	Standard
500 FT	Standard
1000 FT	Reduce 40%
1500 FT	Reduce 40%
1/2 MILE	Reduce 50%
1 MILE	Standard


\* DISTANCE MESSAGES




W20-52P-54  
Legend: black (non-refl)  
Background: orange



W21-52-48  
Legend: black (non-refl)  
Background: orange



W21-50-48  
Legend: black (non-refl)  
Background: orange




W21-53-48  
Legend: black (non-refl)  
Background: orange

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
5-31-18	
REVISIONS	
DATE	CHANGE


This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 5/31/18 and the original document is stored at the North Dakota Department of Transportation

BARRICADE AND CHANNELIZING DEVICE DETAILS



DELINEATOR DRUM


Provide horizontal, circumferential, alternating orange and white retroreflective stripes 4" to 6" wide for drum markings. Use a minimum of two orange and two white stripes with the top stripe being orange for each drum. Do not exceed 3" nonretroreflectORIZED spaces between the horizontal orange and white stripes. Avoid placement of stripes on drum ribs or indentations. Use closed top drums that will not allow collection of debris. Do not place ballast on the top of drum.



BACK TO BACK VERTICAL PANEL STACKABLE


Provide alternating orange and white retroreflective stripes, sloping downward in direction vehicular traffic is to pass. Place retroreflective sheeting on both sides of panel with a minimum of 270 square inches of retroreflective area facing vehicular traffic. Where the height of the retroreflective material on the vertical panel is 36 inches or more, use a stripe width of 6 inches.

Molded rubber base (min weight 30 lbs)




TRAFFIC CONE

Provide retroreflectORIZATION of cones more than 36" in height by alternating orange and white retroreflective stripes. Use a minimum of two orange and two white stripes for each cone with the top stripe being orange. Use maximum 3" nonretroreflectORIZED space between the orange and white stripes.



TUBULAR MARKER


Provide retroreflectORIZATION of tubular markers more than 42" in height by alternating four 4" to 6" wide orange and white stripes with the top stripe being orange.



FLEXIBLE DELINEATOR


INSTALLATION NOTES:

1. Drill installation holes to diameter and depth required by manufacturer's specifications.
2. For removal, remove anchors and fill installation hole with an epoxy designed to bond to pavement surface.
3. In lieu of bolted down base, use an 8" x 8" butyl pad or hot melt butyl. Remove butyl as close as possible to pavement surface.




BARRICADE BLADE DETAIL

NOTE: This is the only type of rail acceptable for use with this barricade assembly.




ELEVATION VIEW

BARRICADE ASSEMBLY DETAIL (Aluminum Barricade Rails)



SIDE VIEW




TYPE I BARRICADE

TYPE II BARRICADE


TYPE III BARRICADE

BARRICADE RAIL DETAILS




ELEVATION VIEW

BARRICADE ASSEMBLY DETAIL (Wood or Plastic Rails)



SIDE VIEW



REFLECTOR DETAIL

ELEVATION

DELINEATORS

MINIMUM BALLAST (For each side of barricade support)

Without Sign	4 - 25 lb sandbags
With Sign	6 - 25 lb sandbags


Note: Number of sandbags based on a wind speed of 55 MPH. Sandbags assumed to be placed at or near the ends of the skids.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-3-13	
REVISIONS	
DATE	CHANGE
9-27-17	Updated to active voice


This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 9/27/2017 and the original document is stored at the North Dakota Department of Transportation

CONSTRUCTION SIGN PUNCHING AND MOUNTING DETAILS


Note: In curb sections, place signs a minimum horizontal distance of 2' from face of the curb to near edge of the sign.




TYPICAL SECTION  
(48" x 48" diamond warning sign shown)




24" x 24" ROUTE MARKER ASSEMBLY




36" x 36" ROUTE MARKER ASSEMBLY




18" x 18" DIAMOND SIGN




48" x 48" DIAMOND SIGN  
(with 30" x 30" secondary sign)




48" x 48" DIAMOND SIGN  
(with 30" x 24" secondary sign)




R1-2-60 - YIELD SIGN




W14-3-64 - PENNANT SIGN




R1-1-48 - STOP SIGN  
(with R6-1-54 sign as required)




R1-1-48 - STOP SIGN  
(with R1-50P-24 sign as required)




48" x 48" SIGN  
(with R6-1-54 sign as required)




48" x 48" SIGN  
(with R2-1aP-24 sign as required)




24" x 36" SIGN




30" x 24" SIGN




108" x 48" SIGN




96" x 48" SIGN




72" x 36" SIGN




72" x 24" SIGN




60" x 24" SIGN



48" x 24" SIGN



PORTABLE SIGN SUPPORT  
LOW-MOUNTING HEIGHT



PORTABLE SIGN SUPPORT  
HIGH-MOUNTING HEIGHT

NOTES:

- Sign Supports: Galvanize or paint supports. Minimum post sizes are 2.5 lb/ft u-channel or 2" x 2" x 12 gauge steel perforated tube, except where noted. When installing signs on u-channel, minimum post size for assemblies containing a secondary sign is 3.0 lb/ft. Post sizes based on a wind speed of 55 MPH.  
  
Place signs over 50 square feet on 2 1/2" x 2 1/2" perforated tube supports as a minimum.  
  
Do not attach guy wires to sign supports. Attach wind beams behind sign panels when used with u-posts.
- Sign Panels: Provide sign panels made of 0.100" aluminum, 1/2" plywood, or other approved material, except where noted. Punch all holes round for 5/16" bolts.
- Alternate Messages: Install and remove alternate message signs on reflectorized plate (without borders) as required. (i.e. "Left" and "Right" message on lane closure sign)
- Route Marker Auxiliary Signs: Provide route marker auxiliary signs, such as the cardinal direction and directional arrows, with a background and legend that match the route marker they are used with:

Interstate - white legend on blue background  
Interstate Business Loop - white legend on green background  
US and State - black legend on white background  
County - yellow legend on blue background

- Vertical Clearance: Install signs with a vertical clearance of 5'-0" (see TYPICAL SECTION). In areas where parking or pedestrian movements are likely or the view of the sign may be obstructed, install signs with a vertical clearance of 7'-0" from the top of the curb or from the near edge of the driving lane in absence of a curb.

The vertical clearance to secondary signs is 1'-0" less than the vertical clearance stated above.

Provide a minimum clearance of 7'-0" from the ground at the post for signs with an area exceeding 50 square feet.

- Portable Signs: Provide portable signs that meet the vertical clearance stated above when it is necessary to place signs within the pavement surface.

Use of low-mounting height (minimum 12" vertical clearance) portable signs for 5 days or less, is allowed as long as the view of the sign is not obstructed. Time delays caused by unforeseen circumstances, such as equipment breakdowns, rain, subgrade failures, etc., will not accrue towards the 5 day period. Use of R9-8 through R9-11a series, W1-6 through W1-8 series, M4-10, and E5-1 is allowed for longer than 5 days.

Restrict signs mounted on portable sign supports shown in the LOW-MOUNTING HEIGHT and HIGH-MOUNTING HEIGHT details to a maximum surface area of 16 square feet.

MINIMUM BALLAST  
(For each side of sign support base)

Sign Panel Mounting Height (ft)	Number of 25 lb sandbags for 4' x 4' sign panel
1'	6
5'	8
7'	10


Note: The number of sandbags are based on a wind speed of 55 MPH. Place sandbags at or near the ends of skids.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-4-13	
REVISIONS	
DATE	CHANGE
11-14-13 9-27-17	Revised Note 6, Updated to active voice

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 9/27/2017 and the original document is stored at the North Dakota Department of Transportation



DETOUR AND ROADWAY DIVERSION SIGN LAYOUTS



- Notes**
- Variables  
 S=Numerical value of speed limit or 85th percentile. W=The width of taper.  
 L=Minimum length of taper, or  $S \times W$  for freeways, expressways, and all other roads with speeds of 45 mph or greater, or  $W \times S^2 / 60$  for urban, residential, and other streets with speeds of 40 mph or less.
  - Place barricades on moveable assemblies and signs on portable assemblies when on roadway.
  - Space delineator drums and vertical panels at dimension "S" for tapering traffic. Space delineator drums, tubular markers and vertical panels at 2 times "S" for tangents.
  - Determine the reduced speed limit based on the in place speed limit before construction. Where speed limits exceed 30 MPH, install a second speed limit sign with the desired speed reduction (not to exceed 30 mph.) Place the second speed limit sign at  $\frac{1}{2} B$ .
  - Install flags on warning signs in urban areas when signs are not portable. Mount 24 inches square flags perpendicular to the edges of the sign, and at such a distance above the edge that the flag does not touch the sign when limp.
  - Cover existing speed limit signs within a reduced speed limit zone.
  - Covered (when approved by engineer) or obliterated pavement marking measured as Obliteration of Pavement Marking.
  - As an option, use portable sign supports in lieu of post mounted signs in accordance with NDDOT Standard Specifications.
  - If the tangent between tapers is less than 600', as an option, use sign W24-1-48 in place of double reverse curve signs.
  - Recommend using 40 mph speed limit in vicinity of workers, unless location and conditions dictate otherwise.
  - Re-establish speed limit. Determine exact speed limit in the field, dependent on location and conditions.





**TYPE J**  
 ROAD CLOSURE WITH A DIVERSION SIGN LAYOUT  
 2 lane highway with widened section,  
 traffic maintained in both directions.  
 Use layout when work is less than 5 days or is within a project.

ADVANCE WARNING SIGN SPACING			
Road Type	Distance Between Signs Min. (ft)		
	A	B	C
Urban - Low Speed (30 mph or less)	150	150	150
Urban - Low Speed (over 30 to 40 mph)	280	280	280
Urban - High Speed (over 40 mph to 50 mph)	360	360	360
Rural - High Speed (over 50 mph to 65 mph)	720	720	720
Urban Expressway and Freeway (55 mph to 60 mph)	850	1350	2200
Rural Expressway and Freeway (70 mph to 75 mph)	1000	1500	2640
Interstate/4-Lane Divided (Maintenance and Surveying)	750	1000	1500




NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
9-27-13	
REVISIONS	
DATE	CHANGE
8-17-17	Updated notes. Added speed limit.

This document was originally issued and sealed by  
 Roger Weigel  
 Registration Number  
 PE- 2930,  
 on 08/17/17 and the original document is stored at the  
 North Dakota Department  
 of Transportation

SHOULDER CLOSURES AND BRIDGE PAINTING LAYOUTS



- Notes
- Variables
    - S = Numerical value of speed limit or 85th percentile.
    - W = The width of the taper in feet.
    - L = Minimum length of taper,  $S \times W$  for freeways, expressways, and all other roads with speeds of 45 mph or greater, or  $W \times S^2 / 60$  for urban, residential, and other streets with speeds of 40 mph or less.
  - Space delineator drums for tapering traffic at dimension "S". Space delineator drums or tubular markers for tangents at 2 times "S".
  - Sequencing Arrow Panels
    - Use Type A on roadways with slow moving traffic speeds and low volume (25 mph or less and 750 ADT or less).
    - Use Type B on roadways with moderate traffic speeds and volumes (40 mph or less and 5000 ADT or less).
    - Use Type C on roadways with high traffic speeds and volumes (over 40 mph or over 5000 ADT).
  - Re-establish speed limit. Determine exact speed limit in the field, dependent on location and conditions.
  - Determine the reduced speed limit based on the in-place speed limit before construction. Where speed reductions exceed 30 MPH, install a second speed limit sign with the desired speed reduction (not to exceed 30 mph.) Place the second speed limit sign at 1/2 B.
  - Install flags on warning signs in urban areas when signs are not portable. Mount 24 inch square flags perpendicular to the edges of the sign, and at such a distance above the edge that the flag does not touch the sign when limp.
  - Cover existing speed limit signs within a reduced speed zone.
  - As an option, use portable sign supports in lieu of post mounted signs in accordance with NDDOT Standard Specifications.
  - Recommend 40 mph speed limit in vicinity of workers, unless location and conditions dictate otherwise.




ADVANCE WARNING SIGN SPACING			
Road Type	Distance Between Signs Min. (ft)		
	A	B	C
Urban - Low Speed (30 mph or less)	150	150	150
Urban - Low Speed (over 30 to 40 mph)	280	280	280
Urban - High Speed (over 40 mph to 50 mph)	360	360	360
Rural - High Speed (over 50 mph to 65 mph)	720	720	720
Urban Expressway and Freeway (55 mph to 60 mph)	850	1350	2200
Rural Expressway and Freeway (70 mph to 75 mph)	1000	1500	2640
Interstate/4-Lane Divided (Maintenance and Surveying)	750	1000	1500

Longitudinal Buffer Space	
Speed (mph)	Length Min (feet)
20	115
25	155
30	200
35	250
40	305
45	360
50	425
55	495
60	570
65	645
70	730
75	820

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
9-27-13	
REVISIONS	
DATE	CHANGE
8-17-17	Updated notes & revised signs


This document was originally issued and sealed by Roger Weigel Registration Number PE-2930, on 08/17/17 and the original document is stored at the North Dakota Department of Transportation

SIGN LAYOUT FOR ONE LANE CLOSURE



Speed (mph)*	Length Min (feet)
20	115
25	155
30	200
35	250
40	305
45	360
50	425
55	495
60	570
65	645
70	730
75	820



\*Posted speed, off-peak 85th percentile speed prior to work starting, or the anticipated operating speed in mph.



RIGHT LANE CLOSED WORKERS IN WORK AREA (Detail Mirrored for Left Lane Closure)

Notes:

1. Install advance signs for flagging when flaggers are flagging.
2. Move the advanced flagger sign and speed limit signs as the work area moves through the construction zone. When the work area is not visible from the flagger, move the flagger station so the work area is visible. Place the 40 mph speed limit sign at 1/2 A in advance of the flagger sign and move the 60 mph speed limit sign. Cover or remove the 40 mph speed limit and the Minimum Fee \$80 signs upon completion of the work day or when workers are not present. Determine the exact speed limit in the field, dependent on location and conditions.
3. Approaches: When the work area encompasses an approach, install a 40 mph speed limit sign to control the approach. Cover the existing stop sign and install a new portable stop sign when the approach is on the side of the lane closure. Remove the approach speed limit sign once the main line 40 mph speed zone is moved past the approach.
4. Variables:  
 S=Numerical value of speed limit or 85th percentile  
 W=The width of taper.  
 L=Minimum length of taper, or SxW for freeways, expressways, and all other roads with speeds of 45 mph or greater, or (WxSxS)/60 for urban, residential, and other streets with speeds of 40 mph or less.
5. Space delineator drums for tapering traffic at the dimension "S". Space tubular markers used for tangents at 2 times dimension "S".
6. Place sequencing arrow panels at the beginning of the taper when possible. Where shoulder width does not provide sufficient room, move the panel closer to the work area and place on the roadway surface.  
 Use Type A on roadways with slow moving traffic speeds and low volume (25 mph or less and 750 ADT or less).  
 Use Type B on roadways with moderate traffic speeds and volumes (40 mph or less and 5000 ADT or less).  
 Use Type C on roadways with high traffic speeds and volumes (over 40 mph or over 5000 ADT).
7. Re-establish the speed limit. Determine the exact speed limit in the field, dependent on location and conditions.
8. Cover existing speed limit signs within a reduced speed zone.
9. Install flags on warning signs in urban areas when signs are not portable. Mount 24 inch square flags perpendicular to the edges of the diamond sign, and at such a distance above the edge that the flag does not touch the sign when limp.
10. Determine the reduced speed limit dependent on the in place speed limit before construction. Where speed limits are to be reduced more than 30 mph, install a second speed limit sign with the desired speed reduction (not to exceed 30 mph.) Place the second speed limit sign at 1/2 B.
11. As an option use portable sign supports in lieu of post mounted signs in accordance with NDDOT Standard Specifications.
12. Sign G20-55-96 is not required if this standard is part of other traffic control layouts or the work is less than 15 days.




Road Type	Distance Between Signs Min (ft)		
	A	B	C
Urban - Low Speed (30 mph or less)	150	150	150
Urban - Low Speed (over 30 to 40 mph)	280	280	280
Urban - High Speed (over 40 mph to 50 mph)	360	360	360
Rural - High Speed (over 50 mph to 65 mph)	720	720	720
Urban Expressway and Freeway (55 mph to 60 mph)	850	1350	2200
Rural Expressway and Freeway (70 mph to 75 mph)	1000	1500	2640
Interstate/4-Lane Divided (Maintenance and Surveying)	750	1000	1500

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
9-26-2012	
REVISIONS	
DATE	CHANGE
3-15-16	Removed Do Not Pass signs and updated notes
8-17-17	Updated notes & sign nos. & moved Speed Limit signs




This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 08/17/2017 and the original document is stored at the North Dakota Department of Transportation

# EDGEDRAIN DETAILS


D-714-18




Option #1: Trench before permeable base is placed  
Option #2: Trench after permeable base is placed  
**TRENCH WRAP DETAILS**



**BENT BAR DETAILS**




**PLAN VIEW**




**RODENT SCREEN**

Dimensions are approximate to allow bend and a snug fit in headwall slot



**SECTION PRECAST CONCRETE HEADWALL**




**END**

**SUPERELEVATED CURVES:** The edgeline, outlets, and headwalls shall be omitted from the high side of superelevated curves.

**RODENT SCREEN:** The rodent screen shall be fabricated from flattened expanded metal with screen openings of approximately 0.25 square inches. The screen shall be 16 ga metal, hot dip galvanized after fabrication.

**REINFORCING BARS:** Reinforcing bars shall be No. 4 deformed steel bars.



**SECTION A-A**

Section A-A shows edgeline location for median concrete shoulder installations on Interstate highways. For installations where asphalt shoulders will be constructed, or the outside shoulder is to be concrete, the edgeline is to be trenched adjacent to the roadway concrete pavement, and will be located beneath the shoulder pavement.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-27-2010	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930 , on 10/27/2010 and the original document is stored at the North Dakota Department of Transportation

INLET - SPECIAL

D-722-1B

TYPE 1  
(See Standard Drawing D-722-1)


TYPE 2  
(See Standard Drawing D-722-2)

MOUNTABLE - TYPE A  
(See Standard Drawing D-722-3)


MOUNTABLE - TYPE B  
(See Standard Drawing D-722-3)

CATCH BASIN - TYPE A  
(See Standard Drawing D-722-1A)

CATCH BASIN - BEEHIVE (6 in. or 9 in.)  
(See Standard Drawing D-722-1A)



See Note 1.



RISER DIAMETER	COVER DIAMETER	BASE DIAMETER
48"	58"	66"
60"	72"	78"
72"	86"	92"


See Note 4.

PAY ITEMS

48 in. Riser	Inlet Special - Type 1 48 in. ....	Ea.
	Inlet Special - Type 2 48 in. ....	Ea.
	Inlet Special Mountable - Type A 48 in. ....	Ea.
	Inlet Special Mountable - Type B 48 in. ....	Ea.
	Inlet Special Catch basin 6 in. beehive 48 in. ....	Ea.
	Inlet Special Catch basin - Type A 48 in. ....	Ea.
60 in. Riser	Inlet Special - Type 1 60 in. ....	Ea.
	Inlet Special - Type 2 60 in. ....	Ea.
	Inlet Special Mountable - Type A 60 in. ....	Ea.
	Inlet Special Mountable - Type B 60 in. ....	Ea.
	Inlet Special Catch basin 6 in. beehive 60 in. ....	Ea.
	Inlet Special Catch basin - Type A 60 in. ....	Ea.
72 in. Riser	Inlet Special - Type 1 72 in. ....	Ea.
	Inlet Special - Type 2 72 in. ....	Ea.
	Inlet Special Mountable - Type A 72 in. ....	Ea.
	Inlet Special Mountable - Type B 72 in. ....	Ea.
	Inlet Special Catch basin 6 in. beehive 72 in. ....	Ea.
	Inlet Special Catch basin - Type A 72 in. ....	Ea.

NOTES:

- For inlet casting details, see Standard Drawings D-722-1, D-722-21A, D-722-2, and D-722-3. Other castings, similar in dimension, may be used provided the casting meets the requirements set forth in the referenced Standard Drawings. The grate style shall be as specified on the plans and included in the price bid for "Inlet Special - (casting type & riser size)".
- Metal used in the manufacture of castings shall conform to AASHTO M-105, Class 35B.
- The Class of concrete, aggregate size, and methods of construction for the manhole riser, cover, and base shall be as detailed in Standard Drawing D-722-5.
- See Standard Drawing D-722-5 for manhole riser, cover, and base details, dimensions, and reinforcement requirements.
- The distance between the center of the cover opening and the center of the storm drain shall be noted on the Plan & Profile sheets.
- Manhole steps, if noted on the Plan and Profile sheets, shall be constructed per Standard Drawing D-722-5.
- On projects with P.C.C. pavement, all risers shall be constructed 4 to 5 inches below final elevation and adjusted to final elevation after paving. Adjustments may be made with adjusting rings or cast-in-place concrete. All costs for this adjustment shall be included in the price bid for "Inlet - Special, (casting type & riser size)".



NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
03-18-14	
REVISIONS	
DATE	CHANGE


This document was originally issued and sealed by Terrence R. Udland Registration Number PE-2674, on 03-18-14 and the original document is stored at the North Dakota Department of Transportation

# PERFORATED TUBE ASSEMBLY DETAILS

D-754-23


**Notes:**

1. Curbed Roadways: The clearance from the face of the curb should be 3' except where right of way or sidewalk width is limited, a minimum clearance of 2' shall be provided. The horizontal clearance may need to be increased to maintain a minimum sidewalk clear width of 4' from the sign support, not including any attached curb.
2. Minimum vertical clearance: Signs installed at the side of the road in rural districts shall be at least 5' measured from the bottom of the sign to the edge of the driving lane or auxiliary lane. Where parking or pedestrian movements occur, the clearance to the bottom of the sign shall be at least 7'.
- Signs on expressways shall be installed with a minimum height of 7'.
- Adopt-a-highway signs installed on Freeways shall be at least 7' above the edge of the driving lane.
- The vertical clearance shall have a maximum height of 6" above the vertical clearance specified above.
3. Offset signs: Where signs are placed at least 30 feet or more from the edge of the traveled way, the height to the bottom of such sign shall be 5' above the edge of the driving lane.
4. The clearance from edge of shared use path to edge of sign should be 3' except where width is limited, a minimum clearance of 2' shall be provided.




Typical Section (without curb)

Horizontal Clearance Table	
Shoulder Width ft	Offset ft
0 to 2	16
>2 to 4	18
>4 to 6	20
>6 to 8	22
>8 to 10	24




Typical Section (with curb)  
Residential or Business District



Stop Sign Location  
Wide Throat Intersection

This layout is to be used for the placement of "Stop" signs.

Radius ft.	Y-max. ft.	Y-min. ft.
40	50	15
45	50	18
50	50	21
55	50	25
60	50	28
65	50	32
70	50	35
75	50	39
80	50	43





Shared Use Path  
Bicycle - Pedestrian Path

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-3-13	
REVISIONS	
DATE	CHANGE
7-8-14	Revised note 2, added note 4.

This document was originally issued and sealed by  
**Roger Weigel**  
 Registration Number  
 PE-2930,  
 on 7/8/14 and the original document is stored at the  
 North Dakota Department  
 of Transportation


Number of Posts	Telescoping Perforated Tube						
	Post Size In.	Wall Thickness Gauge	Sleeve Size In.	Wall Thickness Gauge	Slip Base	Anchor Size Without Slip Base In.	Anchor Wall Thickness Gauge
1	2	12			No	2 1/2	12
1	2 1/2	12			No	2 1/2	12
1	2 1/2	12			(B)	3(C)	7
1	2 1/2	10			Yes		7
1	2 1/2	12	2 1/2(D)	12	Yes		7
1	2 1/2	12	2 1/2	12	Yes		7
2	2 1/2	10			Yes		7
2	2 1/2	12	2 1/2(D)	12	Yes		7
2	2 1/2	12	2 1/2	12	Yes		7
3 & 4	2 1/2	12			Yes		7
3 & 4	2 1/2	10			Yes		7
3 & 4	2 1/2	12	2 1/2	12	Yes		7
3 & 4	2 1/2	12	2 1/2(D)	12	Yes		7
3 & 4	2 1/2	10	2 1/2	10	Yes		7

(B) - The 2 1/2", 12 gauge posts do not need breakaway bases when placed in standard soils, but require a shim as specified by the manufacturer. The breakaway base is required when the support is placed in weak soils. The Engineer shall determine if the soils are weak. Weak soils are classified as boggy, wet, or loose soil areas.  
 (C) - 3" anchor unit  
 (D) - 2 1/2" x 12 ga. x 18" minimum length external sleeve required.




MULTI-DIRECTIONAL SLIP BASE ASSEMBLY:  
 2 1/2" x 12 ga. may be inserted with 2 1/2" x 12 ga. & 2 1/2" 10 ga. may be inserted with 2 3/8" x 10 ga. to achieve higher load ability.

Mounting Details Perforated Tube



SLIP BASE FOR 2 1/2" POST




SLIP BASE DETAIL

Properties of Telescoping Perforated Tubes						
Tube Size In.	Wall Thickness in.	U.S. Standard Gauge	Weight Per Foot Lbs.	Moment of Inertia In. <sup>4</sup>	Cross Sect. Area In. <sup>2</sup>	Section Modulus In. <sup>3</sup>
1 1/2 x 1 1/2	0.105	12	1.702	0.129	0.380	0.172
2 x 2	0.105	12	2.416	0.372	0.590	0.372
2 1/2 x 2 1/2	0.105	12	2.773	0.561	0.695	0.499
2 3/8 x 2 3/8	0.135	10	3.432	0.605	0.841	0.590
2 1/2 x 2 1/2	0.105	12	3.141	0.804	0.803	0.643
2 1/2 x 2 1/2	0.135	10	4.006	0.979	1.010	0.783


The 2 3/8" size 10 gauge is shown as 2.19" size on the plans; The 2 1/2" size is shown as 2.51" size on the plans.

NOTE:

- 4" Vertical clearance of anchor or breakaway base. The 4" x 60" measurement shall be made above and below post location and also back and ahead of post.
- Anchor material shall be 7 gauge H.R.P.O. Commercial quality ASTM A569 and 3" x 3" x 7" gauge ASTM A500 grade B. Anchor shall have a yield strength 43.9 KSI and tensile strength of 59.3 KSI. Anchor shall be hot dipped galvanized per ASTM A123/153. All tolerances on anchor unit and slip base bottom assembly are +/- 0.005" unless otherwise noted.
- When used in concrete sidewalk, anchor shall be the same concept without the wings.
- Four post signs shall have over 8" between the first and fourth posts.
- Installation procedures as per manufacturers recommendation.
- Concrete fasteners for surface mount breakaway base shall be a minimum 1/2" diameter x 4" grade 8.



SURFACE MOUNT ANCHOR BASE



3" ANCHOR UNIT

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-6-09	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 08/06/09 and the original document is stored at the North Dakota Department of Transportation






Mounting Details Perforated Tube


Note:

- Horizontal stringers - In lieu of perforated tubes, the contractor may substitute z bar stringers. The z bar stringers shall be 1 1/2" x 3/16" thick, 1.08 lbs./ft aluminum or 3.16 lbs./ft steel.
- Metal washers used on sign face shall have a minimum outside diameter of 5/16" ± 1/64" and 10 gauge thickness.
- No Parking Signs: All no parking signs with directional arrows shall be placed at a 30 to 45 degree angle with the line of traffic flow. No parking signs required at the above angles may have the support turned to the correct angle. If the no parking sign is placed with another sign that has to be placed at a 90 degree angle with the line of traffic flow, the detailed angle strap should be used to mount the no parking sign. Flat washers and lock washers shall be used with all nylon washers.
- In lieu of using the bent bolt to attach the post to the stringer, the contractor may choose to punch the sign backing and place the bolt through the sign, the stringer and the post.
- 4" vertical clearance of anchor or breakaway base. The 4" x 60" measurement shall be made above and below post location and also back and ahead of post.




Side View

STRINGER MOUNTING  
(WITH STRINGER IN FRONT OF POST)




Top View




These stringers shall be the same size as the post. Punch round and partial through angle so that excess metal fits stringer and post holes.

STREET NAME SIGNS  
AND ONE WAY SIGNS  
SINGLE POST ASSEMBLY  
ONE STRINGER OR  
BACK TO BACK MOUNTING




Side View



STRAP DETAIL



Top View




ANCHOR UNIT AND  
POST ASSEMBLY



Top View

BACK TO BACK  
MOUNTING



BOLT MOUNTING

Properties of Telescoping Perforated Tubes						
Tube Size In.	Wall Thickness In.	U.S. Standard Gauge	Weight Per Foot Lbs.	Moment of Inertia In. <sup>4</sup>	Cross Sect. area In. <sup>2</sup>	Section Modulus In. <sup>3</sup>
1 1/2" x 1 1/2"	0.105	12	1.702	0.129	0.380	0.172
2" x 2"	0.105	12	2.416	0.372	0.590	0.372
2 1/4" x 2 1/4"	0.105	12	2.773	0.561	0.695	0.499
2 3/8" x 2 3/8"	0.135	10	3.432	0.605	0.841	0.590
2 1/2" x 2 1/2"	0.105	12	3.141	0.804	0.803	0.643
2 1/2" x 2 1/2"	0.135	10	4.006	0.979	1.010	0.783

The 2 3/8" size 10 gauge is shown as 2.19" size on the plans. The 2 1/2" size is shown as 2.51" size on the plans.


Number of Posts	Telescoping Perforated Tube						
	Post Size In.	Wall Thickness Gauge	Sleeve Size In.	Wall Thickness Gauge	Slip Base	Anchor Size Without Slip Base In.	Anchor Wall Thickness Gauge
1	2	12			No	2 1/4	12
1	2 1/4	12			No	2 1/2	12
1	2 1/2	12			(B)	3(C)	7
1	2 1/2	10			Yes		7
1	2 1/4	12	2 1/2(D)	12	Yes		7
1	2 1/2	12	2 1/4	12	Yes		7
2	2 1/2	10			Yes		7
2	2 1/4	12	2 1/2(D)	12	Yes		7
2	2 1/2	12	2 1/4	12	Yes		7
3 & 4	2 1/2	12			Yes		7
3 & 4	2 1/2	10			Yes		7
3 & 4	2 1/2	12	2 1/4	12	Yes		7
3 & 4	2 1/4	12	2 1/2(D)	12	Yes		7
3 & 4	2 1/2	10	2 3/8	10	Yes		7

(B) - The 2 1/2", 12 gauge posts do not need breakaway bases when placed in standard soils, but require a shim as specified by the manufacturer. The breakaway base is required when the support is placed in weak soils. The Engineer shall determine if the soils are weak. Weak soils are classified as boggy, wet, or loose soil areas.  
(C) - 3" anchor unit  
(D) - 2 1/2" x 12 ga. x 18" minimum length external sleeve required.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-6-09	
REVISIONS	
DATE	CHANGE
7-8-14	Revised Note 3


This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 7/8/14 and the original document is stored at the North Dakota Department of Transportation

SIGN PUNCHING, STRINGER AND SUPPORT LOCATION DETAILS REGULATORY, WARNING AND GUIDE SIGNS




1 Post

Assembly No. 1





2 Posts



1 Post

2 Posts


Assembly No. 2




3 Posts

Notes:

1. See Standard D-754-25 for mounting details.
2. The minimum sign backing material thickness shall be 0.100 inch.
3. Perforated square tube stringer shall be 1½" x 1½".
4. All holes shall be punched round for ⅜" bolt.




1 Post




2 Posts


Assembly No. 3



3 Posts




1 Post




2 Posts

Assembly No. 4




1 Post



2 Posts

Assembly No. 5




3 Posts


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
12-1-10	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 12-1-10 and the original document is stored at the North Dakota Department of Transportation


SIGN PUNCHING, STRINGER AND SUPPORT LOCATION  
DETAILS REGULATORY, WARNING AND GUIDE SIGNS



1 Post



2 Posts




3 Posts

Assembly No. 6


Notes:

1. See Standard D-754-25 for mounting details.
2. The minimum sign backing material thickness shall be 0.100 inch.
3. Perforated square tube stringer shall be 1½" x 1½".
4. All holes shall be punched round for ⅜" bolt.




1 Post

Assembly No. 7




1 Post

Assembly No. 8




1 Post


Assembly No. 9



2 Posts




1 Post




2 Posts


Assembly No. 10



3 Posts




1 Post



2 Posts

Assembly No. 11




3 Posts


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
12-1-10	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 12-1-10 and the original document is stored at the North Dakota Department of Transportation

SIGN PUNCHING, STRINGER AND SUPPORT LOCATION  
DETAILS REGULATORY, WARNING AND GUIDE SIGNS




1 Post




2 Posts

Assembly No. 12




3 Posts




1 Post

Assembly No. 13




1 Post

Assembly No. 14




2 Posts




1 Post


Assembly No. 15



2 Posts




1 Post




2 Posts


Assembly No. 16



3 Posts




1 Post



2 Posts

Assembly No. 17



3 Posts


Notes:

1. See Standard D-754-25 for mounting details.
2. The minimum sign backing material thickness shall be 0.100 inch.
3. Perforated square tube stringer shall be 1½" x 1½".
4. All holes shall be punched round for ⅜" bolt.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
12-1-10	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 12-1-10 and the original document is stored at the North Dakota Department of Transportation




SIGN PUNCHING, STRINGER AND SUPPORT LOCATION  
DETAILS REGULATORY, WARNING AND GUIDE SIGNS






Assembly No. 18



Assembly No. 19



Assembly No. 20



Assembly No. 21


Notes:

1. See Standard D-754-25 for mounting details.
2. The minimum sign backing material thickness shall be 0.100 inch.
3. Perforated square tube stringer shall be 1½" x 1½".
4. All holes shall be punched round for ⅜" bolt.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
12-1-10	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 12-1-10 and the original document is stored at the North Dakota Department of Transportation


SIGN PUNCHING, STRINGER AND SUPPORT LOCATION  
DETAILS REGULATORY, WARNING AND GUIDE SIGNS



1 Post




2 Posts




3 Posts

Assembly No. 24




3 Posts

Assembly No. 25




1 Post

Assembly No. 26




1 Post

Assembly No. 27




1 Post

Assembly No. 28




1 Post

Assembly No. 29



1 Post

Assembly No. 30



2 Posts




- Notes:
1. See Standard D-754-25 for mounting details.
  2. The minimum sign backing material thickness shall be 0.100 inch.
  3. Perforated square tube stringer shall be 1 1/2" x 1 1/2".
  4. All holes shall be punched round for 3/8" bolt.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
12-1-10	
REVISIONS	
DATE	CHANGE




This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 12-1-10 and the original document is stored at the North Dakota Department of Transportation

**SIGN PUNCHING, STRINGER AND SUPPORT LOCATION DETAILS -  
DIVIDED HIGHWAY CONTROL SIGNS**

**D-754-77**



**ASSEMBLY NO. 445 & 449**



**ASSEMBLY NO. 446 & 450**

**Notes:**


1. The minimum sign backing material thickness shall be 0.100 inch.
2. Perforated square tube stringer shall be 1½"x1½".
3. All holes shall be punched round for ⅜" bolt.
4. Assemblies 445 and 446 have single one way signs.  
Assemblies 449 and 450 have back to back one way signs.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-22-12	
REVISIONS	
DATE	CHANGE


This document was originally issued and sealed by  
Roger Weigel  
Registration Number  
PE-2930,  
on 8/22/12 and the original document is stored at the North Dakota Department of Transportation

SIGN PUNCHING, STRINGER AND SUPPORT LOCATION DETAILS FOR STREET NAME SIGNS AND 911 SIGNS

- A - Single sign
- B - Single sign back to back
- C - Single sign each direction
- D - Single sign one direction, back to back other direction
- E - Back to back both directions




Special Assembly 1 (A, B, C, D or E)




Special Assembly 2 (A, B, C, D or E)


Special Assembly 3 (A, B, C, D or E)



Special Assembly 4 (A, B, C, D or E)




Special Assembly 5 (A, B, C, D or E)



Front View Sleeve Splice Detail


Note: The splice method may be used upon approval of the engineer.




Sign Stringer Detail

Stringer shall be the same size as the post


Punch round hole through angle to fit stringer and post holes.



Detail A or B




Detail D or E



Intersection Layout

Note: This layout is to be used for street name signs or 911 signs that are used with Special Assembly 1.




Sign Arrangements

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-3-13	
REVISIONS	
DATE	CHANGE


This document was originally issued and sealed by  
 Roger Weigel  
 Registration Number  
 PE-2930,  
 on 10/3/13 and the original document is stored at the  
 North Dakota Department  
 of Transportation




Pavement Marking Message Details




22 S. F.




29 S. F.




12 S. F.



16 S. F.



27 S. F.




41 S. F.


Note: Rotate merge arrow 20° from edge of roadway.

Speed Limit	Chevron Width	Chevron Spacing 45° to Traffic
0-25 mph	8"	5'
30-40 mph	8"	15'
45 mph and above	12"	25'


Chevron Crosshatching Table




Centerline Pavement Marking Skip Spacing Detail




4 S. F.




22 S. F.




34.5 S. F.



46 S. F.



Railroad cross & 2 R's 60.5 S.F.  
3 Bands (12' lane) 72 S.F.




Continental Crosswalk Detail

Posted or 85th Percentile Speed	Advance Distance
20 mph	min. 100 ft
25 mph	min. 100 ft
30 mph	min. 100 ft
35 mph	min. 100 ft
40 mph	125 ft
45 mph	175 ft
50 mph	250 ft
55 mph	325 ft
60 mph	400 ft
65 mph	475 ft
70 mph	550 ft


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
12-6-11	
REVISIONS	
DATE	CHANGE
10-17-17	Updated to active voice.

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 10-17-2017 and the original document is stored at the North Dakota Department of Transportation



See Standard Drawing D-754-81










Notes:  
Mark a three lane roadway with a centerline for two-lane approach operation on the approach to a crossing. On multi-lane roads, extend the transverse bands across all approach lanes, and use individual R X R symbols in each approach lane.  
See plans for correct message. Use white pavement markings unless noted otherwise.



R15-1

# MGS FLARED ENERGY ABSORBING TERMINAL - WOOD POST

D-764-38



**GENERAL NOTES:**

- Wood posts are required with the Flared Energy Absorbing Terminal except posts 1 and 2.
- Galvanize all bolts, nuts, cable assemblies, cable anchors, and bearing plates.
- Flare the Flared Energy Absorbing Terminal when the approach guardrail is parallel with the roadway. When the approach guardrail is flared at 16:1 to 10:1, ensure the Flared Energy Absorbing Terminal has only the flare rate of the guardrail. When the guardrail flare is between 10:1 and 7:1, ensure the Flared Energy Absorbing Terminal is turned parallel to the roadway.
- Ensure the lower sections of the posts do not protrude more than 4" above the ground (measured along a 5' cord). Site grading may be necessary to meet this requirement.
- Install the lower section of the hinged posts without the upper post attached. If the post is placed in a drilled hole, the backfill material must be compacted to prevent settlement.
- The breakaway cable assembly must be taut. Use a locking device (vice grips or channel lock pliers) to prevent cable from twisting when tightening nuts.
- "Toe nail" the wood blockouts to the rectangular wood posts. Use two 20 penny galvanized nails.

ITEM	ITEM NO.	BILL OF MATERIALS	QTY
A	F3000	IMPACT HEAD	1
B	SF1303	W-BEAM GUARDRAIL END SECTION, 12 Ga	1
C	G12025	9'-4 1/2" MGS W-BEAM RAIL SECTION, 12 Ga	1
D	G1203A	12'-6" MGS W-BEAM RAIL SECTION, 12 Ga	2
E	UHP1A	FIRST POST ASSEMBLY TOP	1
F	HP1B	FIRST POST ASSEMBLY BOTTOM	1
G	UHP2A	SECOND POST ASSEMBLY TOP	1
H	HP2B	SECOND POST ASSEMBLY BOTTOM	1
J	UP671	WOOD CRT POST	5
K	P675	WOOD BLOCKOUT OR RECYCLE EQUIVALENT	5
L	E750	BEARING PLATE	1
M	S760	CABLE ANCHOR BOX	1
N	E770	BCT CABLE ANCHOR ASSEMBLY	1
O	S785	GROUND STRUT HINGED POST	1
<b>HARDWARE</b>			
a	B5160304A	5/16" x 3" HEX BOLT A325	2
b	W0516	5/16" WASHER	4
c	N0516	5/16" HEX NUT	2
d	B580122	5/8" Dia x 1 1/4" SPLICE BOLT	33
e	B581802	5/8" Dia X 18" HGR BOLT	5
f	B580904A	5/8" Dia x 9" HEX BOLT GRD 5	1
g	W050	5/8" WASHER	7
h	N050	5/8" Dia HGR NUT	39
j	B340854A	3/4" Dia x 8 1/2" HEX BOLT GRD A449	1
k	N030	3/4" Dia HEX NUT	1
l	N100	1" ANCHOR CABLE HEX NUT	2
m	W100	1" ANCHOR CABLE WASHER	2
n	SB12A	1/2" RSI SHOULDER BOLT WITH WASHER	8
o	N012A	1/2" STRUCTURAL NUT	8
p	W012A	1/2" STRUCTURAL WASHER	8
r	CT-100ST	BEARING PLATE RETAINER TIE	1




NOTE: Standard wood line post, block, and associated hardware not included in Bill of Materials Table.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
7-14-17	
REVISIONS	
DATE	CHANGE


This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 7/14/17 and the original document is stored at the North Dakota Department of Transportation

# MGS SLOTTED RAIL TERMINAL - STEEL POST

D-764-39




**DETAIL B**  
Posts 3 through 6




**SECTION A-A**  
Post 2


**SECTION B-B**  
Posts 3 and 5




**SECTION C-C**  
Post 4



**SECTION D-D**  
Post 6



**SECTION E-E**  
Posts 7 and 8



**SECTION F-F**  
Post 1

**GENERAL NOTES:**

- Galvanize all bolts, nuts, cable assemblies, cable anchors, bearing plates, slot guards, struts, nails, pipes soil tubes and soil plates.
- The breakaway cable assembly must be taut. A locking device (vice grips or channel lock pliers) should be used to prevent cable from twisting when tightening nuts.
- For curb installation, the curb must end prior to post 7. Where the curb is extended beyond post 7, the flared Slotted Rail Terminal can not be used. Use a straight end treatment at the end of the straight guardrail that is placed at the face of the curb.
- For details not shown, see the manufacturer's installation manual.
- The Slotted Rail Terminal is only to be used as an end terminal when a minimum length of 175 feet, including the length of the end terminal, can be provided in advance of fixed objects.

**OFFSET NOTES:**

- Post offset dimensions are given to the center of the traffic face of posts, except at posts 7 and 8 where dimensions are to the center of the traffic face of the blockouts.
- Guardrail between posts 1-7 is on a straight line flare.
- Install the Slotted Rail Terminal with a 4' flare for either a straight or flared guardrail installation.

ITEM	ITEM NO.	BILL OF MATERIALS	QTY
A	7G	12/6"/FLANGE PROTECTOR (POSTS 2, 4, 6)	3
B	30G	12/12-6"/S SRT-1 RAIL SECTION	1
C	39G	12/12-6"/S SRT-2 RAIL SECTION	1
D	700A	CABLE ANCHOR BRACKET	1
E	907G	TERMINAL BUFFER ROLLED	1
F	3000G	3/4" x 6'-6" CABLE	1
G	9960G	SLOT GUARD BRACKET	4
H	15000G	SYT W6x8.5 6' STEEL POST	5
J	10967G	12/9-4 1/2"/3'-1 1/2"/S SRT-3 RAIL SECTION	1
K	33875G	ANGLE STRUT 3" x 3" x 1/4"	1
L	33909G	CABLE ANCHOR BRACKET (POST 1)	1
M	34052A	CR POST 1 BOTTOM W6x15	1
N	34053A	CR POST 1 TOP W6x8.5	1
O	34054G	POST SHELF ANGLE (POST 2)	1
HARDWARE			
a	3240G	5/8" WASHER	2
b	3245G	5/8" HEX NUT	2
c	3300G	5/8" WASHER	12
d	3340G	5/8" HGR HEX NUT	75
e	3360G	5/8" Dia x 1 1/4" HGR SPLICE BOLT	60
f	3380G	5/8" Dia x 1 1/2" HEX HD BOLT	8
g	3391G	5/8" Dia x 1 3/4" HEX BOLT A325 (AT STRUT)	2
h	3400G	5/8" Dia x 2" HGR POST BOLT (POSTS 1, 2, 4)	4
j	3900G	1" WASHER (AT CABLE)	2
k	3910G	1" HEX NUT (AT CABLE)	2
l	4211G	5/8" Dia x 1 3/4" HEX BOLT (POST 1)	2
m	4419G	5/8" Dia x 1 3/4" COUNTERSUNK HD BOLT (POST 6)	1

NOTE: Standard rail section and standard wood line posts (including the blocks, and associated hardware) not included in Bill of Materials Table. All splice bolts (including associated nuts) are included in the Bill of Materials Table.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
7-14-17	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 7/14/17 and the original document is stored at the North Dakota Department of Transportation


MGS W-BEAM GUARDRAIL GENERAL DETAILS

NOTES:


1. Begin reflector plates at the first post and space at 25' centers on guardrail less than 250' length and at 50' centers for guardrail over 250' length. Provide the reflector the same color as the pavement marking adjacent to it unless noted otherwise on the plans.
2. Replacing bituminous material at guardrail post: Dispose all excess earth from excavations for guard posts as directed by the engineer. Replace bituminous material wherever guardrail is installed after mat has been laid. Cost of excavation and replacing of bituminous material to be included in the price bid for other items.
3. Fit the Object Marker within the vertical edges of the Impact Plate. Provide type XI retroreflective sheeting meeting the requirements of Section 894.02.E of the standard specifications. Apply the sheeting to 0.100 Aluminum sheeting meeting the requirements of Section 894.01.A. Attach the Object Marker to the Impact Head Plate with rivets or other attachment device. Ensure the rivets or attachment device are non-rust. Slope the stripes downward toward the roadway side.
4. Guardrail installation height tolerance = ±1".




Splice Plate



Splice Detail





C6x8.2 RUB RAIL AND SPLICE PLATE




5/8" Diameter Guardrail Bolt	
L	Thread Length
1 1/4"	Full length thread
2"	1 3/4" Min thread length
9 1/2"	4" Min thread length
18"	4" Min thread length
20"	4" Min thread length
22"	4" Min thread length
25"	4" Min thread length

5/8" GUARDRAIL BOLT & RECESS NUT




W BEAM TERMINAL CONNECTOR




SPLICE DETAIL


NOTE: Do not install center bolt in the 3/4" x 2 1/2" slot at mid span splices.



5/8" Diameter Carriage Bolt	
L	Thread Length
1 1/2"	Full length thread
3"	1 1/2" Min thread length
11"	1 3/4" Min thread length
13"	1 3/4" Min thread length




5/8" CARRIAGE BOLT & NUT




REFLECTORIZED PLATE DETAIL

NOTE: Additional reflectors are added to the W-beam guardrail quantities for placement on end treatment.




TYPICAL WOOD POST ATTACHMENT DETAIL




6" x 8" WOOD POST & BLOCK


NOTE: Where soil conditions require, alternate lengths may be specified, in 6" increments.




IMPACT HEAD OBJECT MARKER



STANDARD MGS GUARDRAIL PANEL



STANDARD MGS GUARDRAIL SYSTEM




W-BEAM CROSS SECTION

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
7-14-17	
REVISIONS	
DATE	CHANGE


This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 7/14/17 and the original document is stored at the North Dakota Department of Transportation

TYPICAL GRADING AT BRIDGE ENDS  
WITH MGS W-BEAM GUARDRAIL


D-764-48




TYPICAL SECTION



PLAN LAYOUT  
FLARED GUARDRAIL WITH END TERMINAL



PLAN LAYOUT  
NON-FLARED GUARDRAIL WITH TANGENT END TERMINAL



PLAN LAYOUT  
NON-FLARED GUARDRAIL WITH FLARED END TERMINAL

NOTES:

- (A) Slope flatter than 10:1 may be required to provide proper guardrail height.
- (B) Where normal foreslope is 4:1 the added fill shall be 4:1. Where normal foreslope is 6:1 the added fill shall be 6:1.
- (C) Measured from top of guardrail to top of surfacing at front face of guardrail.
- (D) Dimension at end terminals may vary per Plan Layouts shown on this sheet.

NORTH DAKOTA  
DEPARTMENT OF TRANSPORTATION

7-14-17






REVISIONS

DATE	CHANGE





This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 7/14/17 and the original document is stored at the North Dakota Department of Transportation

# MASH SOFTSTOP END TERMINAL - STEEL POST

D-764-50



- GENERAL NOTES:
- Galvanize all bolts, nuts, cable assemblies, cable anchors, and bearing plates.
  - The SoftStop can be flared at a rate of 25:1 or flatter.
  - Do not curve the guardrail within the SoftStop under any circumstances.
  - It is acceptable to install the SoftStop impact head parallel to the grade line or with an upward tilt. See softstop assembly manual for specific details.



ITEM	ITEM NO.	BILL OF MATERIALS	QTY
A	000011	12 / 12'-6" / 3'-1 1/2" / S MGS W-BEAM RAIL SECTION	3
B	000533	6'-0" STEEL POST W6 x 8.5	6
C	006777	KING BLOCK 4" X 7 1/2" X 1'-2"	7
D	015000	6'-0" SYT POST / 8.5 / 31" GR HT	1
E	015200	SFST - ANCHOR GUARDRAIL 12'-6"	1
F	015201	SFST - ANCHOR ANGLE	2
G	015202	SFST - ANGLE STRUT	1
H	015203	SFST - POST #1 SYTP	1
J	015204	SFST - ANCHOR PADDLE	1
K	015205	SFST - POST #0	1
L	015206	SFST - PLATE WASHER	1
M	015207	SFST - KEEPER PLATE	1
N	015208	SFST - IMPACT HEAD	1



HARDWARE			
a	003240	5/16" ROUND WASHER WIDE	6
b	003245	5/16" HEX NUT	3
c	003340	5/8" GR HEX NUT	41
d	003360	5/8" x 1 1/4" GR BOLT	32
e	003391	5/8" x 1 1/4" HEX BOLT A325	1
f	003500	5/8" x 10" GR BOLT A307	7
g	003701	3/4" ROUND WASHER F436	4
h	003704	3/4" HVY HEX NUT A563 DH	2
j	003717	3/4" x 2 1/2" HEX BOLT A325	2
k	003908	1" HVY HEX NUT A563 DH	1
l	004372	5/8" WASHER F436	4
m	004489	5/8" x 9" HEX BOLT A325	1
n	004902	1" ROUND WASHER F436	1
o	105285	5/16" x 2 1/2" HEX BOLT GRD 5	2
p	105286	5/16" x 1 1/2" HEX BOLT GRD 5	1

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
7-14-17	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 7/14/17 and the original document is stored at the North Dakota Department of Transportation

# MASH SEQUENTIAL KINKING TERMINAL - WOOD POST








D-764-51



- GENERAL NOTES:
- Galvanize all bolts, nuts, cable assemblies, cable anchors, and bearing plates.
  - The MSKT can be flared at a rate of up to 25:1 to prevent the impact head from encroaching on the shoulder.
  - Ensure the lower sections of the posts do not protrude more than 4" above the ground (measured along a 5' cord). Site grading may be necessary to meet this requirement.
  - Install the lower section of the hinged posts without the upper post attached. If the post is placed in a drilled hole, the backfill material must be compacted to prevent settlement.
  - The breakaway cable assembly must be taut. Use a locking device (vice grips or channel lock pliers) to prevent the cable from twisting when tightening nuts.
  - "Toe nail" the wood blockouts to the rectangular wood posts at post 3 through post 8. Use two 20 penny galvanized nails.

ITEM	ITEM NO.	BILL OF MATERIALS	QTY
A	MS3000	IMPACT HEAD	1
B	SF1303	W-BEAM GUARDRAIL END SECTION, 12 Ga	1
C	G12025	9'-4 1/2" MGS W-BEAM RAIL SECTION, 12 Ga	1
D	G1203A	12'-6" MGS W-BEAM RAIL SECTION, 12 Ga	2
E	MTPHP1A	FIRST POST ASSEMBLY TOP (6" X 6" X 1/8" Tube)	1
F	MTPHP1B	FIRST POST ASSEMBLY BOTTOM (6" W6X15)	1
G	UHP2A	SECOND POST ASSEMBLY TOP	1
H	HP2B	SECOND POST ASSEMBLY BOTTOM	1
K	E750	BEARING PLATE	1
L	S760	CABLE ANCHOR BOX	1
M	E770	BCT CABLE ANCHOR ASSEMBLY	1
N	MS785	STRUT	1
P	UP671	6" WOOD CRT POST	6
R	P675	WOOD BLOCKOUT OR RECYCLED EQUIVALENT	6

HARDWARE			
a	B5160104A	5/16" x 1" HEX BOLT GR 5	2
b	W0516	5/16" WASHER	4
c	N0516	5/16" HEX NUT	2
d	B580122	5/8" Dia x 1 1/4" SPLICE BOLT	33
e	B581802	5/8" Dia x 18" HGR BOLT (POSTS 3 THRU 8)	6
f	B580904A	5/8" x 9" HEX BOLT GR 5	2
g	W050	5/8" WASHER	9
h	N050	5/8" Dia HGR NUT	35
j	B340854A	3/4" Dia x 8 1/2" HEX BOLT GRD A449	1
k	N030	3/4" Dia HEX NUT	1
l	N100	1" ANCHOR CABLE HEX NUT	2
m	W100	1" ANCHOR CABLE WASHER	2
n	SB12A	1/2" RSI SHOULDER BOLT WITH WASHER	8
o	N012A	1/2" STRUCTURAL NUT	8
p	W012A	1/2" STRUCTURAL WASHER	8
r	CT-100ST	BEARING PLATE RETAINER TIE	1





NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
7-14-17	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 7/14/17 and the original document is stored at the North Dakota Department of Transportation


# MGS W-BEAM TRANSITION WITH APPROACH CURB TO CONCRETE SINGLE SLOPE OR JERSEY BARRIER

D-764-60




WOOD BLOCK TO RECTANGULAR WOOD POST (At posts 1 to 11)

5  $\frac{7}{8}$ " Dia. (ASTM A325 or A449) Heavy Hex Head Bolts, with two  $1\frac{1}{2}$ " O.D. washers under each head and nut. Bolts shall be of sufficient length to extend through the full thickness of the rail, washer, and nut. Install with bolt heads on traffic face.




TRANSITION POST AND TIMBER BLOCKOUT SIZING		
POST NO.	POST SIZE	BLOCKOUT SIZE
1-6	6" X 8" X 7'-0" long	6" X 8" X 19"
7-12	6" X 8" X 6'-0" long	6" X 8" X 19"
13-16	6" X 8" X 6'-0" long	6" X 8" X 14"

## ELEVATION VIEW




THRIE-BEAM TERMINAL CONNECTION

NON-SYMMETRICAL TRANSITION TO W-BEAM (10 GAUGE)




TRANSITION SECTIONS



SECTION D-D

CONNECTION TO CONCRETE SINGLE SLOPE BRIDGE RAIL AND TRAFFIC BARRIERS



SECTION E-E

CONNECTION TO CONCRETE JERSEY BARRIER BRIDGE RAIL AND TRAFFIC BARRIERS


- (A) Where curb is required to continue past 15' length, taper the curb down to 3" height at the terminal point shown above, instead of 0" height. Between posts 10 and 16 the curb must be 3" height.
- (B) Install a 12'-6" length W-beam double rail section at this location where curb extends past 15' length.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
7-14-17	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 7/14/17 and the original document is stored at the North Dakota Department of Transportation




SINGLE SLOPE TO THRIE BEAM CONNECTOR PLATE DETAILS




PLAN


NOTE: Assembly Detail is shown for guardrail installation on right hand side of entrance end of bridge barrier. Mirror for opposite side installation.



SECTION A-A




PICTORIAL DRAWING  
(Showing Back of Connector Plate)




ELEVATION

ASSEMBLY DETAIL  
(Front View)



END



ELEVATION

WELDING DETAIL  
(Back View)

WELDING INSTRUCTIONS:

- (A) Cover plate P3 shall be welded as follows: 3/16" continuous back weld on exterior sides and 3/16" fillet weld 1" long spaced at 2" center-to-center on interior sides.
- (B) Stiffeners located on the inside of the cover plates shall be welded as follows: 3/16" fillet weld 1" long spaced at 2" center-to-center.
- (C) Cover plates P1 and P2 shall be welded together with full penetration groove weld.




PLATE P3  
Quantity: 1






PLATE P2  
Quantity: 1

PLATE P1  
Quantity: 1


COVER PLATES




TYPE S1  
Quantity: 4



TYPE S7  
Quantity: 1




TYPE S8  
Quantity: 1




TYPE S9  
Quantity: 1

VERTICAL PLATES




TYPE S10  
Quantity: 1




TYPE S11  
Quantity: 1


STIFFENER PLATES




TYPE S2  
Quantity: 1




TYPE S3  
Quantity: 1



TYPE S4  
Quantity: 1



TYPE S5  
Quantity: 1



TYPE S6  
Quantity: 1


HORIZONTAL PLATES

NOTES:

- 1. Cover plates P1, P2, and P3 shall be fabricated from 3/16" thick ASTM A36 Grade structural steel.
- 2. Stiffener plates shall be fabricated from 1/4" thick ASTM A36 Grade structural steel.
- 3. Connector plate shall be galvanized in accordance with AASHTO M111.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
7-14-17	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 7/14/17 and the original document is stored at the North Dakota Department of Transportation




**Circuit Breaker Cabinet Pad Mounted**

(A) Provide weatherproof cabinet, 56 in. high x 26 in. wide x 14 in. deep, 12 gauge steel (min.) or aluminum with provisions for padlock. Place one coat of primer and two coats of exterior dark green enamel on steel cabinet.




**Conduit Standoff Bracket**

Use when required by local Utility Company.





**Controller Cabinet Interconnect and Power Cable Lightning Protection**

**Feed Point Cabinet Lightning Protection**




NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-14-13	
REVISIONS	
DATE	CHANGE
10-17-17	Updated to active voice.



This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 10-17-2017 and the original document is stored at the North Dakota Department of Transportation






Alternate Signal Standard Base  
For use only with Type V, VI, and VII signal standards.



Side View Front View  
Pedestrian Push Button Post Details (A)



Anchor Bolt Detail



Signal Standard Minimum Clearance Details

- (A) Use positioning of the sign, pushbutton, and direction of arrow to clearly indicate which crosswalk is actuated by the push button. Place type of sign based on the jurisdiction in which placed.
- (B) Attach sign to post using rust resistant 0.081 aluminum bracket and banding. See Standard Signs book for dimensions and legend series. See plans for type of sign.


Notes:

- Signal Heads: See traffic signal layout for correct mounting position, number, size, and arrangement of lenses.
- Steel Standards: Place signal standard a minimum of 3 ft. from the face of the curb to center of signal standard, unless shown otherwise on layout sheets.
- Paint: See note sheet for required color of paint.
- Transformer Base: In lieu of transformer base use alternate signal standard base.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-14-13	
REVISIONS	
DATE	CHANGE
10-17-17	Updated to active voice.

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 10-17-2017 and the original document is stored at the North Dakota Department of Transportation


## TRAFFIC SIGNAL STANDARDS (MAST ARM TYPE)



Anchor Bolt Detail




3/4" Top Plate




3/4" Bottom Plate

Detail A



Note: In lieu of the plate type connection, use a telescoping clamp type extension.



Twin Mast Arm



Truss Type Mast Arm




Combination Signal and Light Standard			
Signal Standard Type	Luminaire Mounting height (ft)	Install Light Standard Extension and Luminaire	Luminaire Mast Arm
A	30	yes	single
B	30	(A)	single
C	40	yes	single
D	40	(A)	single
E	30	yes	twin
F	30	(A)	twin
G	40	yes	twin
H	40	(A)	twin
I	50	yes	single
J	50	yes	twin

(A) Install the light standard extension for these signal standards at a later date under a separate contract.


**Notes:**

- Light standard extension: Mast arm is 6 ft. unless otherwise noted on the plans. Use light standard extension galvanized in accordance with ASTM A 123.
- Luminaire: Use internal ballast - constant wattage 120 x 240 voltage luminaires. See layout sheets for type of luminaire, wattage, and I.E.S. distribution.
- Signal head: See Traffic Signal Layout for correct mounting position, number, size, and arrangement of lenses. Place mast arm mounted signal heads with a clearance between 17 ft. and 19 ft. from the centerline of the roadway to the bottom of signal heads.
- Multi-sided poles: Provide a means, other than friction, that will not allow the mast arm to be rotated by wind forces. Fabricate the pole so the mast arm is rotatable. This feature to be as approved by the Engineer.
- Transformer base: In lieu of the transformer base, use the alternate signal standard base.




Section A-A

Section B-B




Alternate Signal Standard Base


Note: For use with Type IV and combination signal standards only



Combination Signal and Light Standard



Signal Standard Minimum Clearance Detail








Type IV Signal Standard

(B) On combination signal and light standards Type B, D, F, and H, and on all Type IV signal standards install a suitable pole cap as per manufacturer's specifications.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-14-13	
REVISIONS	
DATE	CHANGE
10-17-17	Updated to active voice.

This document was originally issued and sealed by  
Roger Weigel,  
Registration Number  
PE-2930,  
on 10-17-2017 and the original document is stored at the  
North Dakota Department  
of Transportation

TRAFFIC SIGNAL HEAD MOUNTING




Light Standard Mounted Pedestrian Signal Head (A)

Type II Pedestal Mounted - Pedestrian (A)


Type IV Post Mounted - Vehicular Post Mounted - Pedestrian (A)

Type V Post Mounted - Vehicular Post Mounted - Pedestrian (A)


Type VI Post Mounted - Vehicular Post Mounted - Pedestrian (A)



Side View Mid-Span Mounted and Mast Arm Rigid Mounted Signal Heads




Mast Arm Signal Head Bracket




Plan Layout (typical)

Note: Place signal heads behind the face of the curb.


- Notes:
- Reinforcing Plates:** Install reinforcing plates where mounting hardware attaches to signal heads when using polycarbonate signal heads. Where a plumbizer is used, place reinforcing plates on each side of the plumbizer.
  - Clearance:** Place the bottom of post or pedestal mounted vehicular signal heads a minimum of 10 ft. and pedestrian signal heads a minimum of 8 ft. above the ground line or sidewalk.
  - Signal Heads:** See traffic signal layout for correct mounting position, numbers, size, and arrangement of lenses.
  - Pole Clamps:** A pole plate with suitable banding material, as approved by the Engineer, is allowed in place of pole clamps. Where traffic signal heads and pedestrian signal heads are mounted one above the other, one pole clamp assembly is allowed.
  - Paint:** Paint signal housing yellow and backplates dull black. Paint pole clamps and signal head mounting hardware the same color as the signal standard shaft. When pedestrian heads are light standard mounted, paint the lower 12 ft. the same color as the other traffic signal standards.
  - Mounting Details:** All signal heads shown viewed from direction of travel.




Type VII Post Mounted - Vehicular Post Mounted - Pedestrian (A)




Front View



Isometric View



Front View




Isometric View

End Mounted and Mast Arm Rigid Mounted Signal Heads


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-14-13	
REVISIONS	
DATE	CHANGE
7-8-14 10-17-17	Added reinforcing plate note Updated to active voice.

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 10-17-2017 and the original document is stored at the North Dakota Department of Transportation

LOOP DETECTOR DETAILS  
(SAW SLOT)



Multiple Loop Details  
(Presence Loops)




Loop Detector Detail  
(Passage or Calling Loops)  
Number of loops and number of turns as shown in the plans

Notes:


1. Saw cut each loop in roadway.
2. The number of turns, size of loop, and size of conductor shown on the plans.
3. Place leads from the loop to the pull box in saw slots and conduits to minimize interaction.

(A) 1" minimum on concrete surface  
2" minimum on asphalt surface



Saw Slot Details

Drill detector loop corners 2" deep then saw pavement slots to form loops. Dimensions and location shown in plans.




Single Loop Connection

Label all conductors in the pull box as shown. Splice loop connections in the pull box.

Multiple Loop Connection


Where multiple loops are connected to create one detection zone, label all conductors in the pull box as shown and splice loop connections in the pull box as shown. Number of loops varies with connections made following the same pattern.




Plan View

Construction Joint Detail

Use Construction Joint Detail when a crack in the roadway is encountered.



Section B-B



Curb Section


Rural Section

Saw Slot to Pull Box Details


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-14-13	
REVISIONS	
DATE	CHANGE
10-17-17	Updated to active voice.

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 10-17-2017 and the original document is stored at the North Dakota Department of Transportation

LOOP DETAILS




Plan with curb



Elevation  
Preformed Loop Detector Layout

Installation of Preformed Loop detector when placed in new pavement.



Elevation with curb


Elevation without curb

Microloop Placement in New Pavement

Notes:


After the installation and compaction of the aggregate base, trench a 4 in. trench and drill the 1 1/2 in. dia. holes. Embed microloop detectors in the sand as shown. Recompact aggregate base to the density of surrounding material and test microloops prior to placing PCC pavement.

Drill 1 1/2 in. dia. holes a minimum of 2 in. below bottom of microloop detector probe.




Saw Slot Details

(A) 1" minimum on concrete surface  
2" minimum on asphalt surface




Preformed Loop Detector Layout

Securely tie down Preformed Loop to prevent loop from floating while placing concrete.



Plan with curb



Elevation with curb

Elevation without curb

Microloop Placement in Existing Pavement

Notes:


Drill 1 1/2 in. dia. holes, cut saw slot in the pavement, install 1 in. conduit, and install microloop detectors so tops of probes are 15 in. below road surface. Fill 1 in. dia. conduit with sand, seal saw slot, and test microloops.

Drill 1 1/2 in. dia. holes a minimum of 2 in. below bottom of microloop detector probe.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-14-13	
REVISIONS	
DATE	CHANGE
10-17-17	Updated to active voice.

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 10-17-2017 and the original document is stored at the North Dakota Department of Transportation

SPAN WIRE MOUNTED TRAFFIC SIGNALS




- Notes:
1. Place span wired mounted traffic signals in accordance with Standard Specifications Section 772 and 896.
  2. If a guy wire angle of less than 45° is used, increase the capability of the expanding soil anchor to resist tensions on site.
  3. Maintain the required 17 to 19 ft. signal height over the roadway for a minimum period of 90 calendar days after installation, unless written permission is granted by the Engineer to waive the 90 day requirement. Include all costs to maintain the signal head elevation in the price bid for span wire mounted signals.
  4. Operate traffic signal controller on 120 volts.
  5. Use thimble type connections for span wire and stability wire.


Length of pole (ft)	Depth of pole min. (ft)
35	6
40	6
45	6.5
50	7
55	7.5

Angle	Anchor Resistance min.
30°	12,000 lbs.
15°	24,500 lbs.


Span Wire Mounted



Signal Mounting Disconnect Hanger Assembly





Top View




End View

Detail B



Detail A




Eye Bolt Detail


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
2-28-14	
REVISIONS	
DATE	CHANGE
7-8-14	Title change, span wire size and sag
10-17-17	Updated to active voice.

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 10-17-2017 and the original document is stored at the North Dakota Department of Transportation






GENERAL LAYOUT FOR SINGLE SPAN




GENERAL LAYOUT FOR MULTIPLE SPAN

BRIDGE BENCH MARKS



CHECK POINT LOCATION DETAIL



BENCH MARK DETAIL

NOTES:

Elevation check points shall consist of 3/8" ø x 3" galvanized carriage bolts (or equal) set in the concrete barrier at the points indicated on the General Layout sketches. The top of the bolt head shall project above the finished concrete 1/8". Elevation check points shall be placed on each barrier over each unit of the substructure for each bridge at a structural location.

Two bench marks as detailed hereon shall be set at diagonal opposite positions away from the structure location and at least 300 feet from the nearest point on the bridge or bridges (if more than one at a location). These bench marks shall be constructed as detailed on this sheet and located near the Highway Right of Way lines. The two pipes shall extend 4'-0" above ground and be painted with two coats of white paint suitable for galvanized steel surfaces.

The Project Engineer shall run a set of levels determining the elevation of each check point on the structure and the two bench marks immediately after the completion of the bridge. Bench Mark #1 can be listed as having elevation 1000 or the actual surveyed elevation. This information shall be recorded on SFN 13420 and submitted to the Bridge Engineer with adequate information locating each check point and bench mark.

All metal parts are to be hot dip galvanized after punching, shearing, welding and fabrication.

Threads of cap and pipe are not to be galvanized. At the time of installation these threads are to be coated with synthetic grease with teflon and cap screwed to a snug fit.

METHOD OF MEASUREMENT:

Each set of Bridge Bench Marks consisting of two bench marks and the required number of elevation check points shall be considered as one unit for bidding purposes and the quantity to be paid for shall be the number of sets of bridge bench marks which have been installed complete in place and accepted by the Engineer.

BASIS OF PAYMENT:

Bridge Bench Marks shall be paid for at the contract price bid for each set of Bridge Bench Marks, which price shall be full compensation for all excavation, backfill and clean-up, and for furnishing, hauling and placing all elevation check points, galvanized pipe, caps, rods, sand backfill, concrete, rock equipment, tools and incidentals, including galvanizing and greasing, necessary to complete this item.

GALVANIZING:

After fabrication the complete assembly shall be hot-dip galvanized.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
09/14/11	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Terrence R. Udland, Registration Number PE-2674, on 09/14/11 and the original document is stored at the North Dakota Department of Transportation