

STATE COUNTY MAP


DESIGN DATA

Traffic ~ BRO-0045(066)		Average Daily			Est. 30th Max. Hr.
		Passenger	Trucks	Total	
Current Traffic	2020	<100	-	<100	-
Forecast Traffic	2020	<100	-	<100	-

Clear Zone Distance: 14 Feet
Design Speed: 45 MPH
Minimum Sight Dist. for Stopping: 360 Feet
Structure Design Loading: HL-93

END PROJECT BRO-0045(066):
Sta 115+50.00. A point 1626.08 feet south and 84.29 feet west of the Nouttheast Corner of Section 5, Township 137 N, Range 93 W of the 5th P.M., Stark County, North Dakota.

BEGIN PROJECT BRO-0045(066):
Sta 109+50.00. A point 2225.68 feet south and 99.61 feet west of the Nouttheast Corner of Section 5, Township 137 N, Range 93 W of the 5th P.M., Stark County, North Dakota.



JOB #14
STARK COUNTY
NORTH DAKOTA

FEDERAL AID PROJECT
BRO-0045(066)

CMC 4537/94th Avenue Southwest
Removal of Structure, Precast RCB Culvert, Grading & Incidentals
Existing Structure No. 45-138-21.0
New Structure No. 45-138-21.1
6 miles east and 2 miles north of Lefor

GOVERNING SPECIFICATIONS

2020 Standard Specifications adopted by the North Dakota
Department of Transportation and the Supplemental Specifications
effective on the date the project is advertised.

PROJECT LENGTH

Project	Gross Miles	Net Miles
BRO-0045(066)	0.114	0.114

This project consists of Removing the existing structure,
the installation of a 21' x 12' x 58' Precast Reinforced
Concrete Box Culvert, and 0.114 miles of grading located
in Stark County, North Dakota.

SURVEY FIELD BOOK: C-765 Pgs 21-28

DESIGNERS

Andrew Krebs, PE

Wade Thompson, PE

Charlie Bowen, EI

CERTIFICATION

I HEREBY CERTIFY THAT THESE PLANS WERE PREPARED
BY ME OR UNDER MY DIRECT SUPERVISION, AND THAT
I AM A DULY REGISTERED PROFESSIONAL ENGINEER
UNDER THE LAWS OF THE STATE OF NORTH DAKOTA.

Andrew J. Krebs /s/

ANDREW J. KREBS, P.E.
KLJ ENGINEERING LLC

DATE 8/21/2020

REGISTRATION NUMBER PE-7876



677 27TH AVENUE EAST
DICKINSON, ND 58601
(701) 483-1284, FAX (855) 288-8055

© KLJ 2020

TABLE OF CONTENTS

SECTION NO.	SHEET NO.	DESCRIPTION
1	1	Title Sheet
2	1	Table of Contents, List of Special Provisions, & List of Standard Drawings
6	1-2	Plan Notes
6	3	Environmental Notes
8	1	Estimate of Quantities
10	1	Basis of Estimate & Earthwork Summary
11	1	Earthwork Values
30	1	Typical Sections
60	1	Plan & Profile
75	1-2	Wetlands, Mitigation and Environmental
76	1	Temporary Sediment and Erosion Control
77	1	Permanent Sediment and Erosion Control
81	1	Survey Coordinate Data
100	1-3	Work Zone Traffic Control
170	1-3	Precast RCB Details and Notes
200	1-6	Cross Sections


LIST OF SPECIAL PROVISIONS

SP #	DESCRIPTION
SSP 1	Temporary Erosion and Sediment Best Management Practices
SSP 2	Federal Migratory Bird Treaty Act
SSP 3	Local Agency Contracts
SP 103(20)	Temporary Water Diversion
PSP 23(20)	Permits and Environmental Considerations

LIST OF STANDARD DRAWINGS

STANDARD NO.	DESCRIPTION
D-101-1, 2 & 3	NDDOT Abbreviations
D-101-10	NDDOT Utility Company and Organization Abbreviations
D-101-20 & 21	Line Styles
D-101-30, 31 & 32	Symbols
D-101-40	Cross Section Legend
D-255-2	Erosion and Siltation Control – Erosion Control Blanket Installation
D-261-1	Erosion Control – Fiber Roll Placement Details
D-704-7	Breakaway Systems for Construction Zone Signs – Perforated Tube
D-704-8	Breakaway Systems for Construction Zone Signs – U Channel Post
D-704-9	Construction Sign Details – Terminal and Guide Signs
D-704-10	Construction Sign Details – Regulatory Signs
D-704-11	Construction Sign Details – Warning Signs
D-704-13	Barricade and Channelizing Device Details
D-704-14	Construction Sign Punching and Mounting Details
D-704-19	Road Closure and Lane Closure on a Two Way Road Layouts
D-704-22	Construction Truck and Temporary Detour Layouts
D-704-50	Portable Sign Support Assembly
D-714-22	Concrete Pipe, Cattle Pass, or Precast Concrete Box Culvert Ties



PLAN NOTES			STATE	PROJECT NO.	SECTION NO.	SHEET NO.														
			ND	BRO-0045(066)	6	1														
GENERAL NOTES																				
100-P01	FENCES: The County will attend to the removal of existing fences to the new highway right-of-way line.																			
105-P01	UTILITIES: The vertical and horizontal utility locations shown in the plans are approximate. Plan locations should not be interpreted as exact for bidding or construction purposes.																			
105-P02	UTILITIES: No utility relocations or adjustments are planned. All utilities on the project need to be protected and remain in existing location.																			
202-P01	SALVAGE EXISTING AGGREGATE SURFACING: Remove and stockpile the aggregate surfacing on the existing roadway for reuse. Use the material as a traffic surface gravel upon completion of the newly constructed roadbed, or as deemed necessary by the Engineer. Do not use the salvaged aggregate as foundation fill. The salvaged material is included in the topsoil quantity. Include the salvaging, stockpiling, re-spreading and laying of the salvaged material in the unit price bid for "TOPSOIL".																			
202-P02	REMOVED ITEMS: The following removal and salvage items will remain County property. Remove without further damage to these items: <ul style="list-style-type: none">All signs and hazard markers.Bridge components (refer to Section 170 Sheet 2)All removed and salvaged items will be reviewed by the Engineer. If the Engineer determines that the item is not salvageable based on the condition, it becomes the Contractor's property.																			
203-010	SHRINKAGE: 25 percent additional volume is included for shrinkage in earth embankment.																			
203-385	AVERAGE HAUL: No average haul has been computed for this project.																			
203-P01	COMMON EXCAVATION-TYPE C: In Section 203.04 E.4 insert the following after the 2nd paragraph: The addition of water or drying of fill material is required when directed by the Engineer. Include all costs for drying and manipulation of the fill material in the unit price bid for "COMMON EXCAVATION-TYPE C". In cut areas, scarify and recompact the finish subgrade to a minimum depth of 12-inches. Manipulate substandard areas by working the soil as needed. Include all costs for this work in the unit price bid for "COMMON EXCAVATION-TYPE C".																			
203-P02	CONTRACT QUANTITY PAYMENT: The quantities of "COMMON EXCAVATION-TYPE C" to be paid will be those shown in the Contract, provided the Project is constructed to the lines and grades shown on the plans. When disagreement exists between the Contractor and the Owner as to the accuracy of the Plan quantities, either party may request that the quantities be measured. The party requesting the measurement is responsible for all costs associated with the measurement. Any additional required excavation will be measured as per Section 203.05 A or 203.05 B of the Standard Specifications.																			
203-P03	BACKSLOPE ROUNDING: Round backslopes on all cut sections as shown on the Typical Sections. Include this work in the unit price bid for "COMMON EXCAVATION-TYPE C".																			
203-P04	TOPSOIL: Include all costs associated with the stabilization of topsoil stockpiles in the unit price bid for "TOPSOIL".																			
203-P05	TOPSOIL-WETLAND: Excavate the wetland mitigation area to the elevations as specified in Section 200. Place 6 inches of stockpiled topsoil from impacted Wetland 2a, Wetland 2b, and Wetland 3 in the proposed wetland mitigation area. Include all associated costs for the wetland mitigation and any necessary manipulating and drying of material in the unit price bid for "TOPSOIL-WETLAND". Stockpiled topsoil from impacted Wetlands 2a, 2b, and 3 spread on the proposed wetland mitigation area will be used as the seed source for the establishment of wetland vegetation. In addition, furnish wetland seed mix according to Section 251.03 F of the Standard Specifications and seed both the temporary wetland impacts and the mitigation area after placing wetland topsoil in the mitigation area. Include all associated costs with seeding temporary wetland impacts and the mitigation area in the unit price bid for "WETLAND SEED".																			
203-P06	COMMON EXCAVATION-SUBCUT: 100 CY of "COMMON EXCAVATION-SUBCUT" has been provided, if needed, for use to remove existing unsuitable material in the roadbed as determined by the Engineer. The Engineer will direct the location and actual quantity of "COMMON EXCAVATION-SUBCUT". Backfill subcut areas with suitable onsite material. Spread the subcut material in the fills outside the main roadbed, or outside the road right of way, not adjacent to the construction site, in accordance with Section 107.17 of the Standard Specifications. The unit price bid for "COMMON EXCAVATION-SUBCUT" will govern regardless of the quantity used. An increase or decrease from plan quantity will not be accepted as a reason to negotiate any pay adjustment under this bid item. The bid item "COMMON EXCAVATION-SUBCUT" may be eliminated at the discretion of the Engineer.																			
203-P07	BORROW-EXCAVATION: Density and moisture requirements shall be the same as Common Excavation-Type C. Borrow material shall consist of approved natural compactable soil. The soil shall not be saturated or contain organic material.																			
251-P01	SEEDING: Seeding Class III shall consist of the following mixture: <table><tr><th>Species</th><th>Lbs. of PLS/Acre</th></tr><tr><td>Alfalfa</td><td>9</td></tr><tr><td>Western Wheatgrass</td><td>4</td></tr><tr><td>Fairway Crested Wheatgrass</td><td>5</td></tr><tr><td>Slender Wheatgrass</td><td>2</td></tr><tr><td>Oats</td><td>10</td></tr><tr><td>Total</td><td>30</td></tr></table>						Species	Lbs. of PLS/Acre	Alfalfa	9	Western Wheatgrass	4	Fairway Crested Wheatgrass	5	Slender Wheatgrass	2	Oats	10	Total	30
Species	Lbs. of PLS/Acre																			
Alfalfa	9																			
Western Wheatgrass	4																			
Fairway Crested Wheatgrass	5																			
Slender Wheatgrass	2																			
Oats	10																			
Total	30																			
251-P02	WETLAND SEED: Wetland seeding areas will not be measured for payment unless changes are made in the field. Payment for "WETLAND SEED" will be at plan quantity.																			
<div>This document was originally issued and sealed by Andrew J. Krebs Registration Number PE-7876 on August 21, 2020, and the original document is stored at KLJ, Dickinson, ND.</div>																				
<div><div><div>BRO-0045(066)</div><div>CMC 4537/94" Ave SW</div></div><div><div></div><div><div>Plan Notes</div><div>Stark County, ND</div><div><div>DRWN. BY AK</div><div>CHKD. BY AK</div><div>PROJECT NO. 3316111</div></div></div></div></div>																				

PLAN NOTES

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	BRO-0045(066)	6	2

- 256-P01

RIPRAP GRADE II: Riprap Grade II will be paid according to designated length, width, and depth as shown on the plans unless otherwise designated by the Engineer.
- 261-P01

FIBER ROLLS: Fiber rolls have been provided for temporary and permanent erosion control. The temporary erosion control has been provided for placement prior to disturbing the topsoil or as indicated by the Engineer.

Preserve the temporary erosion control throughout the duration of the project. If the erosion control is damaged due to negligence, repair at the Contractor's expense.

Place permanent fiber rolls within the construction limits as construction progresses. Locations are shown in Section 77.

An additional 200 LF of Fiber Rolls 12IN have been provided for locations to be determined by the Engineer. Include all costs for labor, equipment, and materials necessary to complete this work and all costs to relocate fiber rolls as needed for construction related activities in the unit price bid for "FIBER ROLLS 12IN".
- 261-P02

EROSION CONTROL SEQUENCING: In areas where erosion control blankets and fiber rolls are both specified, follow the following installation sequence:

1.

Trench for fiber rolls per Standard Drawing D-261-1

2.

Install erosion control blanket per Standard Drawing D-255-2

3.

Install fiber rolls per Standard Drawing D-261-1
- 302-P01

AGGREGATE SURFACE COURSE: County forces will haul, lay, & compact the 6 inches of aggregate surfacing, as noted on the Typical Sections. Coordinate grading operation with Stark County so that the surfacing can be placed within 48 hours after the finished grading is complete. The County is available to haul, lay, and compact Aggregate Surface Course from Monday through Thursday only.

The Contractor is responsible for all roadway maintenance from the project start through final acceptance. The only exception is if the County does not begin delivery of aggregate surface course within the 48 hours notice period, not including Friday through Sunday. The contact is Al Heiser at (701) 290-8429.
- 704-P01

TRAFFIC CONTROL DEVICES LIST: The traffic control devices list has been developed using the following layouts on the Standard Drawing for traffic control:

•

Standard D-704-19, Type E: For road closure to all traffic. Detour is not provided.

•

Standard D-704-22, Type K: For trucks hauling material.

•

Standard Drawings D-704-7, 8, 9, 10, 11, 13, 14, and 50 are applicable.

•

Traffic Control Layouts for construction are in Section 100 of the plans.
- 704-P02


TRAFFIC CONTROL GENERAL: Leave roadway open to local traffic during construction. Cover or remove signs that do not apply.
- 704-P03

PRECAST RCB CULVERT INSTALLATION: Close the roadway to all traffic during the installation of the box culvert as shown on Section 100 Sheet 3. Open the roadway to local traffic after the box culvert is backfilled. The roadway can be closed to all traffic for a maximum of 10 working days. If the roadway is not open to local traffic after 10 working days, the Engineer will assess liquidated damages of \$1,000 per calendar day it remains closed.

This document was originally issued and sealed by
Andrew J. Krebs
Registration Number
PE-7876
on September 23, 2020,
and the original
document is stored at KLJ,
Dickinson, ND.

BRO-0045(066)

CMC 4537/94th Ave SW



Plan Notes

Stark County, ND

DRWN. BY
AK

CHKD. BY
AK

PROJECT NO.
3316111

9/23/20202:48:32 PMandrew.krebsK:\Projects\County\ND\Stark\3316111\CAD\Design\Plans\Sections\006NT_001.doc

© KLJ 2020

ENVIRONMENTAL NOTES

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	BRO-0045(066)	6	3

ENVIRONMENTAL NOTES (EN): Stark County, the North Dakota Department of Transportation, and the Federal Highway Administration have made environmental commitments to secure approval of this project. The following environmental notes are requirements to comply with these commitments:

EN-1 SPAWNING RESTRICTION: Do not work within Plum Creek from April 15 to June 1.

EN-2 AQUATIC NUISANCE SPECIES (ANS): Equipment that was last used outside of North Dakota or within a Class I infested waterbody (identified on the North Dakota Game and Fish Department (NDGFD) website) requires an inspection by NDGFD. Notify the NDGFD at least 10 business days prior to pumps, watercraft, or any equipment entering a public water to allow the NDGFD sufficient time to inspect any and all such equipment for ANS. Contact the NDGFD ANS Coordinator, Jessica Howell by e-mail jmhowell@nd.gov for equipment inspections. Supply one of the following to the engineer as proof of compliance prior to work taking place in the water: (1) the NDGFD inspection report, (2) documented NDGFD correspondence (email or signed letter). If an inspection is not required, no follow up documentation is required.

EN-3 MIGRATORY BIRDS: Active migratory bird nests with eggs or chicks are protected by the Federal Migratory Bird Treaty Act. NDDOT's special provision, SSP 2 for compliance with the Federal Regulation is to be followed.

EN-4 TEMPORARY WETLAND IMPACT: Temporary impact areas within wetlands and or other waters are incorporated into the plans for this project. Remove temporary fill placed and sedimentation in wetlands or other waters. Restore these wetlands to preconstruction contours.

EN-5 WETLAND MITIGATION: Wetland mitigation is required for unavoidable permanent wetland impacts. The wetland mitigation plan is incorporated into the plans for this project. After completion of the mitigation area, the Engineer will complete the Onsite Mitigation Certification Form SFN 61042. Any sedimentation occurring within the mitigation area will be removed.

EN-6 CONSTRUCTION DEBRIS: Take steps to prevent construction debris from falling into the waterway.

NOTIFICATIONS TO BE FILED BY CONTRACTOR:

EN-7 An Asbestos Survey was completed by a certified inspector from KLJ on August 22, 2018. Based on visual inspection of the site, no building or structure materials were determined to contain asbestos. The results from the Asbestos Survey are available upon request from the Engineer. Complete and submit North Dakota Department of Health SFN 17987 Asbestos Notification of Demolition and Renovation.


PERMITS REQUIRED:

United States Army Corp of Engineers – Section 404 Permit
Status: Has been obtained for the project.

Stark County – Non-Building Floodplain Development Permit
Status: Has been obtained for the project.

North Dakota Department of Environmental Quality – NDPDES Permit
Status: To be obtained by the Contractor prior to construction. Owner is to be listed as Stark County on the permit.

This document was originally issued and sealed by
Andrew J. Krebs
Registration Number
PE-7876
on September 23, 2020,
and the original
document is stored at KLJ,
Dickinson, ND.

BRO-0045(066)		
CMC 4537/94 th Ave SW		
	Environmental Notes	
	Stark County, ND	
DRWN. BY AK	CHKD. BY AK	PROJECT NO. 3316111

ESTIMATE OF QUANTITIES


	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	BRO-0045(066)	8	1

Spec	Code	Description	Unit	Total Quantities
103	0100	CONTRACT BOND	LSUM	1
201	0330	CLEARING & GRUBBING	LSUM	1
202	0105	REMOVAL OF STRUCTURE	LSUM	1
203	0103	COMMON EXCAVATION-TYPE C	CY	691
203	0109	TOPSOIL	CY	830
203	0121	TOPSOIL-WETLAND	CY	66
203	0138	COMMON EXCAVATION-SUBCUT	CY	100
203	0140	BORROW-EXCAVATION	CY	3,566
210	0050	BOX CULVERT EXCAVATION	EA	1
210	0210	FOUNDATION FILL	CY	418
210	0405	FOUNDATION PREPARATION-BOX CULVERT	EA	1
216	0100	WATER	MGAL	109
251	0300	SEEDING CLASS III	ACRE	1.14
251	1000	WETLAND SEED	ACRE	0.10
251	2000	TEMPORARY COVER CROP	ACRE	1.24
253	0101	STRAW MULCH	ACRE	2.48
255	0103	ECB TYPE 3	SY	662
256	0200	RIPRAP GRADE II	CY	74
261	0112	FIBER ROLLS 12IN	LF	1,260
261	0113	REMOVE FIBER ROLLS 12IN	LF	540
606	2112	21FT X 12FT PRECAST RCB CULVERT	LF	58
606	6112	21FT X 12FT PRECAST RCB END SECTION	EA	2
702	0100	MOBILIZATION	LSUM	1
704	1000	TRAFFIC CONTROL SIGNS	UNIT	316
704	1052	TYPE III BARRICADE	EA	8
709	0151	GEOSYNTHETIC MATERIAL TYPE R1	SY	635
709	0155	GEOSYNTHETIC MATERIAL TYPE RR	SY	149
900	1000	TEMPORARY STREAM DIVERSION	EA	1



	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	BRO-0045(066)	10	1

Earthwork and Topsoil Summary					
Project	Excavation (CY)	Embankment (CY)	Borrow (CY)	Topsoil (CY)	Topsoil-Wetland (CY)
BRO-0045(066)	691	4,257	3,566	830	66

<p align="center">BRO-0045(066)</p> <p align="center">CMC 4537/94th Ave SW</p>			
		<p align="center">Basis of Estimate and Earthwork Summary</p> <p align="center">Stark County, ND</p>	
<p>DRWN. BY AK</p>		<p>CHKD. BY AK</p>	
		<p>PROJECT NO. 3316111</p>	

EARTHWORK VALUES


	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	BRO-0045(066)	11	1

BRO-0045(066)					
Station	End Area (SF)		Adjusted Volume (CY)		Mass Ordinate
	Exc	Fill	Exc	Fill	
109+50.00	15.24	2.07	0.0	0.0	0.0
110+00.00	54.60	1.36	64.7	4.0	60.7
110+50.00	14.78	46.86	64.2	55.8	69.1
111+00.00	10.05	194.77	23.0	279.7	-187.5
111+50.00	13.52	351.58	21.8	632.4	-798.1
112+00.00	36.93	341.04	46.7	801.6	-1553.0
112+50.00	58.50	294.82	88.4	736.0	-2200.6
112+79.00	0.00	905.78	31.4	806.0	-2975.1
112+80.00	0.00	162.45	0.0	24.7	-2999.9
112+91.00	0.00	141.42	0.0	77.4	-3077.2
113+02.00	0.00	121.84	0.0	67.0	-3144.3
113+03.00	0.00	788.64	0.0	21.1	-3165.4
113+13.00	19.15	256.57	3.5	242.0	-3403.8
113+50.00	47.46	58.56	45.6	269.9	-3628.1
114+00.00	46.02	35.91	86.6	109.3	-3650.8
114+50.00	47.96	22.67	87.0	67.8	-3631.6
114+90.00	61.38	14.49	81.0	34.4	-3585.1
114+95.00	56.77	12.95	10.9	3.2	-3577.3
115+00.00	16.64	11.46	6.8	2.8	-3573.4
115+50.00	14.76	7.38	29.1	21.8	-3566.1
			Volume (CY)		Mass Ordinate
			Exc	Fill	
Totals			691	4,257	-3,566

This document was originally issued and sealed by
Andrew J. Krebs
Registration Number
PE-7876
on August 21, 2020,
and the original
document is stored at KLJ,
Dickinson, ND.

BRO-0045(066)

CMC 4537/94th Ave SW



Earthwork Values

Stark County, ND

DRWN. BY
AK

CHKD. BY
AK




PROJECT NO.
3316111

BENCHMARKS			
NO.	DESCRIPTION	LOCATION	ELEVATION
BM 1	REBAR	111+69.6 - 43.4' Lt	2344.3
BM 3	REBAR	114+07.9 - 39.9' Lt	2336.2
BM 2	REBAR	118+12.1 - 39.6' Rt	2339.2

Curve CMC45372
PI = 112+33.90
Delta = 3° 37' 49.99" (RT)
Da = 0° 36' 31.97"
R = 9,410.00
T = 298.23
L = 596.27

S1/2NE1/4, Sec 5
T-137-N, R-93-W
Curtis P. Naumann & Doretta M. Naumann

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	BRO-0045(066)	60	1



SCALE

Horizontal 1"=100'
Vertical 1"=10'

SURVEY COMPLETED USING NAVD 88 DATUM

This document was originally issued and sealed by
Andrew J. Krebs
Registration Number
PE-7876
on August 21, 2020,
and the original
document is stored at KLJ,
Dickinson, ND.

BRO-0045(066)

CMC 4537/94th Ave SW



Plan & Profile
Sta 107+00 to 117+00
Stark County, ND

DRAWN BY: AK
CHKD BY: AK
PROJECT NO.: 3316111

WETLANDS, MITIGATION AND ENVIRONMENTAL

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	BRO-0045(066)	75	1

Wetland Impact Table																				
Wetland Number	Location	Wetland Feature	USACE Jurisdictional Wetlands ¹	Wetland Impacts Acre(s)		USFWS Easement Impacts Acre(s)		Wetland Mitigation												
								Mitigation Required			USACE/11990 Bank		11990 Bank		USFWS Bank		Onsite			
				Temp.	Perm.	Temp.	Perm.	EO 11990	USACE	USFWS	Location	Acre(s)	Location	Acre(s)	Location	Acre(s)	Mitigation Location; Ratio	Acre(s)	Constructed Site #	Constructed Size Acre(s)
1	Sec.4, T137N, R93W	Natural	Yes	0.00	0.00			N	N	N										
2a	Sec.4, T137N, R93W	Natural	Yes	0.01	0.03			Y	N	N							Adjacent to WL2a & WL3 (1:1)	0.06	Site 1	0.06
2b	Sec.5, T137N, R93W	Natural	Yes	0.01	0.03			Y	N	N										
3	Sec.4, T137N, R93W	Natural	Yes	0.02	0.00			N	N	N										
4	Sec.5, T137N, R93W	Natural	Yes	0.00	0.00			N	N	N										
				0.04	0.06	0	0					0		0		0		0.06		0.06

¹ A wetland Jurisdictional Determination was issued by the USACE on 1/23/2019; NWO-2018-02143-BIS.

² 1199 Mitigation requirements - All impacts to natural wetlands (natural/jurisdictional and natural/non-jurisdictional), regardless of size, as well as impacts greater than 0.10 acre to wetlands require mitigation. USACE Mitigation Requirements - All jurisdictional impacts greater than 0.10 acre to each resource (cumulative. eg 1a ,1b,1c..etc.) requires mitigation. Other Water impact greater than 300 linear feet requires mitigation.

³ All artificial/non-jurisdictional, deep water (impacts greater than 6.6 feet), Other Waters less than 300 linear feet (determined by the USACE on a case by case), and temporary impacts do not require mitigation.


Impact Summary Table			
Permanent Impact Summary		Temporary Impacts and additional information	
Wetland Type	Total (Acres)	Wetland Type	Total (Acres/Lf)
Natural/JD	0.06	Temporary JD	0.04
Natural/Non-JD	0.00	Non-JD Temporary	0.00
Artificial/JD	0.00	Permanent JD > 0.10	0.00
Artificial /Non-JD	0.00	Permanent OW	0.00 ac/00 ft.
Total	0.06	Temporary OW	0.00 ac/00 ft.

Mitigation Summary Table					
	Location	Onsite Acre(s)	11990 Bank Acre(s)	USACE/11990 Bank Acre(s)	USFWS Bank Acre(s)
USACE Only					
EO 11990 Only	Onsite	0.06			
USACE/11990					
USFWS					
Total		0.06	0	0	0

This document was originally issued and sealed by Andrew J. Krebs Registration Number PE-7876 on August 21, 2020, and the original document is stored at KLJ, Dickinson, ND.

BRO-0045(066)

CMC 4537/94th Ave SW



Wetlands, Mitigation and Environmental Wetlands 1-4 Stark County, ND

DRWN. BY AK

CHKD. BY AK

PROJECT NO. 3316111

8/21/202010:45:03 AMandrew krebsK:\Projects\County\ND\Stark\3316111\CAD\Design\Plans\Sections\075WL_001.doc

© KLJ 2020

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	BRO-0045(066)	100	1

SIGN NUMBER	SIGN SIZE	DESCRIPTION	AMOUNT REQUIRED	UNITS PER AMOUNT	UNITS SUB TOTAL
E5-1-48	48"x48"	EXIT GORE		35	
G20-1-60	60"x24"	ROAD WORK NEXT ____ MILES		28	
G20-1b-60	60"x24"	NO WORK IN PROGRESS (Sign and installation only)		18	
G20-2-48	48"x24"	END ROAD WORK	2	26	52
G20-4-36	36"x18"	PILOT CAR FOLLOW ME (Mounted to back of pilot car)		18	
G20-10-108	108"x48"	CONTRACTOR SIGN		70	
G20-50a-72	72"x36"	ROAD WORK NEXT ____ MILES RT & LT ARROWS		43	
G20-52a-72	72"x24"	ROAD WORK NEXT ____ MILES RT or LT ARROW		36	
G20-55-96	96"x48"	SPEED LIMIT ENFORCED - MINIMUM FEE \$80 WHEN WORKERS PRESENT		59	
M1-1-36	36"x36"	INTERSTATE ROUTE MARKER (Post and installation only)		10	
M1-4-24	24"x24"	U.S. ROUTE MARKER (Post and installation only)		10	
M1-5-24	24"x24"	STATE ROUTE MARKER (Post and installation only)		10	
M3-1-24	24"x12"	NORTH (Mounted on route marker post)		7	
M3-2-24	24"x12"	EAST (Mounted on route marker post)		7	
M3-3-24	24"x12"	SOUTH (Mounted on route marker post)		7	
M3-4-24	24"x12"	WEST (Mounted on route marker post)		7	
M4-8-24	24"x12"	DETOUR (Mounted on route marker post)		7	
M4-9-30	30"x24"	DETOUR ARROW RIGHT or LEFT/AHD AND RT or LT		15	
M4-10-48	48"x18"	DETOUR (INSIDE ARROW) RIGHT or LEFT (Mounted on barricade)		7	
M5-1-21	21"x15"	ADVANCE TURN ARROW RT or LT(Mounted on route marker post)		7	
M5-1-30	30"x21"	ADVANCE TURN ARROW RT or LT(Mounted on route marker post)		9	
M6-1-21	21"x15"	DIRECTIONAL ARROW RT or LT (Mounted on route marker post)		7	
M6-1-30	30"x21"	DIRECTIONAL ARROW RT or LT (Mounted on route marker post)		9	
M6-3-21	21"x15"	DIRECTIONAL ARROW UP (Mounted on route marker post)		7	
R1-1-48	48"x48"	STOP		32	
R1-2-60	60"x60"	YIELD		29	
R2-1-36	36"x48"	SPEED LIMIT ____ (Portable only)		30	
R2-1-48	48"x60"	SPEED LIMIT ____		39	
R2-1aP-24	24"x18"	MINIMUM FEE \$80 (Mounted on Speed Limit post)		10	
R3-2-48	48"x48"	NO LEFT TURN		35	
R4-1-48	48"x60"	DO NOT PASS		39	
R4-7-48	48"x60"	KEEP RIGHT		39	
R5-1-48	48"x48"	DO NOT ENTER		35	
R6-1-54	54"x18"	ONE WAY RIGHT or LEFT (Mounted on STOP or DO NOT ENTER post)		14	
R7-1-12	12"x18"	NO PARKING ANY TIME		11	
R10-6-24	24"x36"	STOP HERE ON RED		16	
R11-2-48	48"x30"	ROAD CLOSED (Mounted on barricade)	2	12	24
R11-2a-48	48"x30"	STREET CLOSED (Mounted on barricade)		12	
R11-3a-60	60"x30"	ROAD CLOSED ____ MILES AHEAD LOCAL TRAFFIC ONLY (Mtd on barricade)	2	15	30
R11-3c-60	60"x30"	STREET CLOSED ____ MILES AHEAD LOCAL TRAFFIC ONLY (Mtd on barricade)		15	
R11-4a-60	60"x30"	STREET CLOSED TO THRU TRAFFIC (Mounted on barricade)		15	
W1-3-48	48"x48"	REVERSE TURN RIGHT or LEFT		35	
W1-4-48	48"x48"	REVERSE CURVE RIGHT or LEFT		35	
W1-4b-48	48"x48"	TWO LANE REVERSE CURVE RIGHT or LEFT		35	
W1-6-48	48"x24"	ONE DIRECTION LARGE ARROW		26	
W3-1-48	48"x48"	STOP AHEAD		35	
W3-3-48	48"x48"	SIGNAL AHEAD		35	
W3-4-48	48"x48"	BE PREPARED TO STOP		35	
W3-5-48	48"x48"	SPEED REDUCTION AHEAD		35	
W4-2-48	48"x48"	LANE ENDS RIGHT or LEFT		35	
W5-1-48	48"x48"	ROAD NARROWS		35	
W5-8-48	48"x48"	THRU TRAFFIC RIGHT LANE		35	
W5-9-48	48"x48"	ROAD WORK TRAFFIC ONLY DOWN & LT or RT ARROW		35	
W6-3-48	48"x48"	TWO WAY TRAFFIC		35	
W8-1-48	48"x48"	BUMP		35	
W8-3-48	48"x48"	PAVEMENT ENDS		35	
W8-7-48	48"x48"	LOOSE GRAVEL		35	
W8-11-48	48"x48"	UNEVEN LANES		35	
W8-12-48	48"x48"	NO CENTER LINE		35	
W8-17-48	48"x48"	SHOULDER DROP-OFF SYMBOL		35	
W8-53-48	48"x48"	TRUCKS ENTERING HIGHWAY		35	
W8-54-48	48"x48"	TRUCKS ENTERING AHEAD or ____ FT or ____ MILE	2	35	70
W8-55-48	48"x48"	TRUCKS CROSSING AHEAD or ____ FT or ____ MILE		35	
W8-56-48	48"x48"	TRUCKS EXITING HIGHWAY		35	
W9-3a-48	48"x48"	CENTER LANE CLOSED SYMBOL		35	
W12-2-48	48"x48"	LOW CLEARANCE		35	
W13-1P-30	30"x30"	____ MPH ADVISORY SPEED PLAQUE (Mounted on warning sign post)		14	
W14-3-64	64"x48"	NO PASSING ZONE		28	
W16-2P-30	30"x24"	____ FEET PLAQUE (Mounted on warning sign post)		10	
W20-1-48	48"x48"	ROAD WORK AHEAD or ____ FT or ____ MILE		35	
W20-2-48	48"x48"	DETOUR AHEAD or ____ FT or ____ MILE		35	
W20-3-48	48"x48"	ROAD or STREET CLOSED AHEAD or ____ FT or ____ MILE	4	35	140
W20-4-48	48"x48"	ONE LANE ROAD AHEAD or ____ FT or ____ MILE		35	
W20-5-48	48"x48"	RIGHT or CENTER or LEFT LANE CLOSED AHEAD or ____ FT or ____ MILE		35	
W20-7-48	48"x48"	FLAGGER		35	
W20-8-18	18"x18"	STOP - SLOW PADDLE Back to Back		5	
W20-52P-54	54"x12"	NEXT ____ MILES (Mounted on warning sign post)		12	
W21-1-48	48"x48"	WORKERS		35	
W21-2-48	48"x48"	FRESH OIL		35	
W21-3-48	48"x48"	ROAD MACHINERY AHEAD or ____ FT or ____ MILE		35	
W21-5-48	48"x48"	SHOULDER WORK		35	
W21-5a-48	48"x48"	RIGHT or LEFT SHOULDER CLOSED		35	

[illegible][illegible]

SPEC & CODE			
704-1000	TRAFFIC CONTROL SIGNS	TOTAL UNITS	316

[illegible]

NOTE:
If additional signs are required, units will be calculated using the formula from Section III-18.06 of the Design Manual.
<http://www.dot.nd.gov/>

This document was
originally issued
and sealed by
Andrew J. Krebs,
Registration Number
PE-7876,
on 8/21/20 and the
original document
is stored at the office of KLJ,
Dickinson, ND.


Traffic Control Devices List

Work Zone Traffic Control

Stark County, ND

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	BRO-0045(066)	100	3

CONSTRUCTION SIGN LAYOUT



This document was originally issued and sealed by Andrew J. Krebs Registration Number PE-7876 on August 21, 2020, and the original document is stored at KLJ, Dickinson, ND.

BRO-0045(066)
CMC 4537/94th St SW

Work Zone Traffic Control
Road Closed to
All Traffic Detail
Stark County, ND


DRWN BY
AK

CHKD BY
AK


PROJECT NO.
3316111

The sign layout as shown is for general information purposes only. The Contractor will be required to conform to MUTCD and the Standard Drawings when installing the traffic control signing.

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	BRO-0045(066)	170	1



PLAN



ELEVATION

PRECAST BOX CULVERT BID ITEMS


SPEC	CODE	ITEM DESCRIPTION	UNIT	QUANTITY
202	0105	REMOVAL OF STRUCTURE	L SUM	1
210	0050	BOX CULVERT EXCAVATION	EA	1
210	0210	FOUNDATION FILL	CY	418
210	0405	FOUNDATION PREPARATION-BOX CULVERT	EA	1
256	0200	RIPRAP GRADE II	CY	74
606	2112	21FT X 12FT PRECAST RCB CULVERT	LF	58
606	6112	21FT X 12FT PRECAST RCB END SECTION	EA	2
709	0151	GEOSYNTHETIC MATERIAL TYPE R1	SY	635
709	0155	GEOSYNTHETIC MATERIAL TYPE RR	SY	149

HYDRAULIC DATA:


Drainage Area	26.3	sq mi
Stream Gradient	0.0022	ft/ft
Design Frequency	25	yr
Design Discharge	1,280	cfs
Design Headwater Stage	2,335.6	ft
Design Tailwater Stage	2,332.9	ft
Velocity of Flow Under Bridge	9.8	fps
100-Year Frequency Discharge	2,010	cfs
100-Year Frequency Stage	2,338.5	ft
Overtopping Stage	N/A	ft
Overtopping Discharge	N/A	cfs

NOTE:

The invert elevations shown represent an elevation 1 foot below the existing streambed.



END VIEW
(Showing Dimensions)



END VIEW
(Showing Finished Section)

This document was originally issued and sealed by
Wade M Thompson
Registration Number
PE-10777
on August 21, 2020,
and the original
document is stored at KLJ,
Dickinson, ND.

BRO-0045(066)
Structure # 45-138-21.1
CMC 4537/94th Ave SW






Precast Box Culvert
Layout

Stark County, ND

DRAWN BY: BJJ
CHKD BY: CDB
PROJECT NO.: 3316111




Note: All elevations, offsets, and slopes, shown are top of proposed subgrade.

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	BRO-0045(066)	200	1



Note: All elevations, offsets, and slopes, shown are top of proposed subgrade.

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	BRO-0045(066)	200	2



Note: All elevations, offsets, and slopes, shown are top of proposed subgrade.

STATE

PROJECT NO.

SECTION NO.




SHEET NO.

ND

BRO-0045(066)

200

3



Note: All elevations, offsets, and slopes, shown are top of proposed subgrade.

STATE

PROJECT NO.

SECTION NO.




SHEET NO.

ND

BRO-0045(066)

200

4



Note: All elevations, offsets, and slopes, shown are top of proposed subgrade.

STATE

PROJECT NO.

SECTION NO.





SHEET NO.

ND

BRO-0045(066)

200

5



Note: All elevations, offsets, and slopes, shown are top of proposed subgrade.

STATE

PROJECT NO.

SECTION NO.





SHEET NO.

ND

BRO-0045(066)

200

6



?

This is a special text character used in the labeling of existing features. It indicates a feature that has an unknown characteristic, potentially based on: lack of description, location accuracy or purpose.

Abn abandoned
Abut abutment
Ac acres
Adj adjusted
Aggr aggregate
Ahd ahead
ARV air release valve
Align alignment
Al alley
Alt alternate
Alum aluminum
ADA Americans with Disabilities Act
A ampere
& and
Appr approach
Approx approximate
ACP asbestos cement pipe
Asph asphalt
AC asphalt cement
Assmd assumed
@ at
Atten attenuation
ATR automatic traffic recorder
Ave Avenue
Avg average
ADT average daily traffic
Az azimuth
Bk back
BF back face
Bs backsight
Balc balcony
B Wire barbed wire
Barr barricade
Btry battery
Brg bearing
BI beehive inlet
Beg begin
BG below grade
BM bench mark
Bkwy bikeway
Bit bituminous
Blk block
Bd Ft board feet
BH bore hole
BS both sides
Bot bottom
Blvd Boulevard
Bndry boundary
BC brass cap
Brkwy breakaway
Br bridge

Bldg building
BV butterfly valve
Byp bypass
C Gdrl cable guardrail
Calc calculate
Cd candela
CIP cast iron pipe
CB catch basin
CRS cationic rapid setting
C Gd cattle guard
C To C center to center
Cl or C centerline
Cm centimeter
Ch chain
Chnlk chain-link
Ch Blk channel block
Ch Ch channel change
Chk check
Chsld chiseled
Cir circle
Cl class
Cl clay
Cl F clay fill
Cl Hvy clay heavy
Cl Lm clay loam
Clnt clean-out
Clr clear
Cl&gr clearing & grubbing
Co S coal slack
C Gr coarse gravel
CS coarse sand
Comb. combination
Coml commercial
Compr compression
CADD computer aided drafting & design
Conc concrete
CECB concrete erosion control blanket
Cond conductor
Const construction
Cont continuous
CSB continuous split barrel sample
Contr contraction
Contr contractor
CP control point
Coord coordinate
Cor corner
Corr corrected
CAES corrugated aluminum end section
CAP corrugated aluminum pipe
CMES corrugated metal end section
CMP corrugated metal pipe
CPVCP corrugated poly-vinyl chloride pipe
CSES corrugated steel end section
CSFES corrugated steel flared end section

CSP corrugated steel pipe
CSTES corrugated steel traversable end section
C coulomb
Co County
Crse course
Ct Court
Xarm cross arm
Xbuck cross buck
Xsec cross sections
Xing crossing
Xrd Crossroad
Crn crown
CF cubic feet
M3 cubic meter
M3/s cubic meters per second
CY cubic yard
Cy/mi cubic yards per mile
Culv culvert
C&G curb & gutter
CI curb inlet
CR curb ramp
CS curve to spiral
C cut
Dd Ld dead load
Defl deflection
Defm deformed
Deg or D degree
DInt delineate
DIntr delineator
Depr depression
Desc description
Det detail
DWP detectable warning panel
Dtr detour
Dia or \varnothing diameter
Dir direction
Dist distance
DM disturbed material
DB ditch block
DG ditch grade
Dbl double
Dn down
Dwg drawing
Dr drive
Drwy driveway
DI drop inlet
D dry density
DSDS dynamic speed display sign
Ea each
Esmt easement
E East
EB Eastbound
Elast elastomeric
EL electric locker
E Mtr electric meter
Elec electric/al

EDM electronic distance meter
Elev or El elevation
Ellipt elliptical
Emb embankment
Emuls emulsion/emulsified
ES end section
Engr engineer
ESS environmental sensor station
Eq equal
Eq equation
Evgr evergreen
Exc excavation
Exst existing
Exp expansion
Expy Expressway
E external of curve
Extru extruded
FOS factor of safety
F Fahrenheit
FS far side
F farad
Fed Federal
FP feed point
Ft feet/foot
Fn fence
Fn P fence post
FO fiber optic
FB field book
FD field drive
F fill
FAA fine aggregate angularity
FS fine sand
FH fire hydrant
Fl flange
Flrd flared
FES flared end section
F Bcn flashing beacon
FA flight auger sample
FL flow line
Ftg footing
FM force main
Fs foresight

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07-01-14	
REVISIONS	
DATE	CHANGE
04-23-18 09-20-18	General Revisions General Revisions

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930 , on 09/20/18 and the original document is stored at the North Dakota Department of Transportation

NDDOT ABBREVIATIONS

D-101-2

Fnd	found	ID	inside diameter	Mkg	marking	PMT	pad mounted transformer
Fdn	foundation	Inst	instrument	MA	mast arm	Pg	pages
Frac	fractional	Intchg	interchange	Matl	material	Pntd	painted
Frwy	freeway	Intmdt	intermediate	Max	maximum	Pr	pair
Frt	front	Intscn	intersection	MC	meander corner	Pnl	panel
FF	front face	Inv	invert	Meas	measure	Pk	park
F Disp	fuel dispenser	IM	iron monument	Mdn	median	PK	Parker-Kalon nail
FFP	fuel filler pipes	I Pn	Iron Pin	MD	median drain	Pa	pascal
FLS	fuel leak sensor	IP	iron Pipe	MC	medium curing	PSD	passing sight distance
Furn	furnish/ed	Jt	joint	M	mega	Pvmt	pavement
Gal	gallon	J	joule	Mer	meridian	Ped	pedestal
Galv	galvanized	Jct	junction	M	meter	Ped	pedestrian
Gar	garage	K	kelvin	M/s	meters per second	PPP	pedestrian pushbutton post
Gs L	gas line	Kn	kilo newton	M	mid ordinate of curve	Pen.	penetration
G Reg	gas line regulator	Kpa	kilo pascal	MGS	Midwest Guardrail System	Perf	perforated
GMV	gas main valve	Kg	kilogram	Mi	mile	Per.	perimeter
G Mtr	gas meter	Kg/m3	kilogram per cubic meter	MM	mile marker	PL	pipeline
GSV	gas service valve	Km	kilometer	MP	mile post	PI	place
GVP	gas vent pipe	K	Kip(s)	MI	milliliter	P&P	plan & profile
GV	gate valve	LS	Land Surveyor (licensed)	Mm	millimeter	PL	plastic limit
Ga	gauge	LSIT	Land Surveyor In Training	Mm/hr	millimeters per hour	P Cap	plastic cap
Geod	geodetic	Ln	lane	Min	minimum	PI or \overline{P}	plate
GIS	Geographical Information System	Lg	large	Misc	miscellaneous	Pt	point
G	giga	Lat	latitude	Mon	monument	PCC	point of compound curve
GPS	Global Positioning System	Lt	left	Mnd	mound	PC	point of curve
Gov	government	L	length of curve	Mtbl	mountable	PI	point of intersection
Grd	graded/grade	Lens	lenses	Mtd	mounted	PRC	point of reverse curvature
Gr	gravel	Lvl	level	Mtg	mounting	PT	point of tangent
Grnd	ground	LB	level book	Mk	muck	POC	point on curve
GWM	ground water monitor	Lving	leveling	Mun	municipal	POT	point on tangent
Gdrl	guardrail	Lht	light	N	nano	PE	polyethylene
Gtr	gutter	LP	light pole	NGS	National Geodetic Survey	PVC	polyvinyl chloride
H Plg	H piling	Ltg	lighting	NS	near side	PCC	Portland Cement concrete
Hdwl	headwall	Lig Co	lignite coal	Neop	neoprene	Lb or #	pounds
Ha	hectare	Lig Sl	lignite slack	Ntwk	network	PP	power pole
Ht	height	LF	linear foot	N	newton	Preempt	preemption
HI	height of instrument	Liq	liquid	N	North	Prefab	prefabricated
Hel	helical	LL	liquid limit	NE	North East	Prfmd or Pref	preformed
H	henry	L	litre	NW	North West	Prep	preperation
Hz	hertz	Lm	loam	NB	Northbound	Press.	pressure
HDPE	high density polyethylene	Loc	location	No. or #	number		
HM	high mast	LC	long chord	Obsc	obscure(d)		
HP	high pressure	Long.	longitude	Obsn	observation		
HPS	high pressure sodium	Lp	loop	Ocpd	occupied		
Hwy	highway	LD	loop detector	Ocpy	occupy		
Hor	horizontal	Lm	lumen	Off Loc	office location		
HBP	hot bituminous pavement	Lum	luminaire	O/s	offset		
HMA	hot mix asphalt	L Sum	lump sum	OC	on center		
Hr	hour(s)	Lx	lux	C	one dimensional consolidation		
Hyd	hydrant	Mb	mailbox	OC	organic content		
Ph	hydrogen ion content	ML	main line	Orig	original		
Id	identification	M Hr	man hour	O To O	out to out		
In or "	inch	MH	manhole	OD	outside diameter		
Incl	inclinometer tube	Mkd	marked	OH	overhead		
IMH	inlet manhole	Mkr	marker				

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07-01-14	
REVISIONS	
DATE	CHANGE
08-03-15 04-23-18	General Revisions General Revisions

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930 , on 04/23/18 and the original document is stored at the North Dakota Department of Transportation

NDDOT ABBREVIATIONS

D-101-3

PRV	pressure relief valve	Sc	scoria	St	street	Vert	vertical
Prestr	prestressed	Sec	seconds	SPP	structural plate pipe	VC	vertical curve
Pvt	private	Sec	section	SPPA	structural plate pipe arch	VCP	vitrified clay pipe
PD	private drive	SL	section line	Str	structure	V	volt
Prod.	production/produce	Sep	separation	Subd	subdivision	Vol	volume
Prog	programmed	Seq	sequence	Sub	subgrade	Wkwy	walkway
Prop.	property	Serv	service	Sub Prep	subgrade preperation	W	water content
Prop Ln	property line	Sh	shale	Ss	subsoil	WGV	water gate valve
Ppsd	proposed	Sht	sheet	SE	superelevation	WL	water line
PB	pull box	Shtng	sheeting	SS	supplement specification	WM	water main
Qty	quantity	Shldr	shoulder	Supp	supplemental	WMV	water main valve
Qtr	quarter	Sw or Sdwk	sidewalk	Surf	surfacing	W Mtr	water meter
Rad or R	radius	S	siemens	Surv	survey	WSV	water service valve
RR	railroad	SD	sight distance	Sym	symmetrical	WW	water well
Rlwy	railway	SN	sign number	SI	systems international	W	watt
Rsd	raised	Sig	signal	Tan	tangent	Wrng	wearing
RTP	random traverse point	Si Cl	silt clay	T	tangent (semi)	Wb	weber
Rge or R	range	Si Cl Lm	silty clay loam	TS	tangent to spiral	WIM	weigh in motion
RC	rapid curing	Si Lm	silty loam	Tel	telephone	W	west
Rec	record	Sgl	single	Tel B	Telephone Booth	WB	westbound
Rcy	recycle	SRCP	slotted reinforced concrete pipe	Tel P	telephone pole	Wrng	wiring
RAP	recycled asphalt pavement	SC	slow curing	Tv	television	W/	with
RPCC	recycled portland cement concrete	SS	slow setting	Temp	temperature	W/o	without
Ref	reference	Sm	small	Temp	temporary	WC	witness corner
R Mkr	reference marker	S	South	TBM	temporary bench mark	WGS	world geodetic system
RM	reference monument	SE	South East	T	tesla	Z	zenith
RP	reference point	SW	South West	T	thinwall tube sample		
Refl	reflectorized	SB	Southbound	T/mi	tons per mile		
RCB	reinforced concrete box	Sp	spaces	Ts	topsoil		
RCES	reinforced concrete end section	Spcl	special	Twp or T	township		
RCFES	reinforced concrete flared end section	SA	special assembly	Traf	traffic		
RCTES	reinforced concrete traversable end section	SP	special provisions	TSCB	traffic signal control box		
RCP	reinforced concrete pipe	G	specific gravity	Tr	trail		
RCPS	reinforced concrete pipe sewer	Spk	spike	Transf	transformer		
Reinf	reinforcement	SC	spiral to curve	TB	transit book		
Res	reservation	ST	spiral to tangent	Trans	transition		
Rs	residence	SB	split barrel sample	TT	transmission tower		
Ret	retaining	SH	sprinkler head	TES	traversable end section		
Rev	reverse	SV	sprinkler valve	Trans	transverse		
Rt	right	Sq	square	Trav	traverse		
R/W	right of way	SF	square feet	TP	traverse point		
Riv	river	Km2	square kilometer	Trtd	treated		
Rd	road	M2	square meter	Trmt	treatment		
Rdbd	road bed	SY	square yard	Qc	triaxial compression		
Rdwy	roadway	Stk	stake	TERO	tribal employment rights ordinance		
RWIS	roadway weather information system	Std	standard	Tpl	triple		
Rk	rock	N	standard penetration test	TP	turning point		
Rt	route	Std Specs	standard specifications	Typ	typical		
Salv	salvage(d)	Sta	station	Qu	unconfined compressive strength		
Sd	sand	Sta Yd	station yards	Ugrnd	underground		
Sdy Cl	sandy clay	Stm L	steam line	USC&G	US Coast & Geodetic Survey		
Sdy Cl Lm	sandy clay loam	SEC	steel encased concrete	USGS	US Geologic Survey		
Sdy Fl	sandy fill	SMA	stone matrix asphalt	Util	utility		
Sdy Lm	sandy loam	SSD	stopping sight distance	VG	valley gutter		
San	sanitary sewer line	SD	storm drain	Vap	vapor		

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07-01-14	
REVISIONS	
DATE	CHANGE
08-03-15 04-23-18	General Revisions General Revisions

This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930 , on 04/23/18 and the original document is stored at the North Dakota Department of Transportation

NDDOT UTILITY COMPANY AND ORGANIZATION ABBREVIATIONS

D-101-10

702COM
ACCENT
AGASSIZ WU
AGC
All PI
ALL SEAS WU
AMOCO PI
AMRDA HESS
AT&T
B PAW
BAKER ELEC
BASIN ELEC
BEK TEL
BELLE PL
BLM
BNSF
BOEING
BRNS RWD
BURK-DIV ELEC
BURL WU
Cable One
CABLE SERV
CAP ELEC
CASS CO ELEC
CASS RWU
CAV ELEC
CBLCOM
CENEX PL
CENT PL WATER DIST
CENT PWR ELEC
COE
CONS TEL
CONT RES
CPR
D O E
DAK CARR
DAK CENT TEL
DAK RWD
DGC
DICKY R NET
DICKY RWU
DICKY TEL
DNRR
DOME PL
DVELEC
DVMW
ENBRDG
ENVENTIS
FALK MNG
FHWA
G FKS-TRL WD
GETTY TRD & TRAN
GLDN W ELEC
GRGS CO TEL
GTR RAMSEY WD

702 Communications
Accent Communications
Agassiz Water Users Incorporated
Associated General Contractors of America
Alliance Pipeline
All Seasons Water Users Association
Amoco Pipeline Company
Amerada Hess Corporation
AT&T Corporation
Bear Paw Energy Incorporated
Baker Electric
Basin Electric Cooperative Incorporated
Bek Communications Cooperative
Belle Fourche Pipeline Company
Bureau of Land Management
Burlington Northern Santa Fe Railway
Boeing
Barnes Rural Water District
Burke-Divide Electric Cooperative
Burleigh Water Users
Cable One
Cable Services
Capital Electric Cooperative Incorporat
Cass County Electric Cooperative
Cass Rural Water Users Incorporated
Cavalier Rural Electric Cooperative
Cablecom Of Fargo
Cenex Pipeline
Central Pipe Line Water District
Central Power Electric Cooperative
Corps of Engineers
Consolidated Telephone
Continental Resource Inc
Canadian Pacific Railway
Department Of Energy
Dakota Carrier Network
Dakota Central Telephone
Dakota Rural Water District
Dakota Gasification Company
Dickey Rural Networks
Dickey Rural Water Users Association
Dickey Telephone
Dakota Northern Railroad
Dome Pipeline Company
Dakota Valley Electric Cooperative
Dakota, Missouri Valley & Western
Enbridge Pipelines Incorporated
Enventis Telephone
Falkirk Mining Company
Federal Highway Administration
Grand Forks-trail Water District
Getty Trading & Transportation
Golden West Electric Cooperative
Griggs County Telephone
Greater Ramsey Water District

GT PLNS NAT GAS
HALS TEL
IDEA1
INT-COMM TEL
KANEB PL
KEM ELEC
KOCH GATH SYS
LKHD PL
LNGDN RWU
LWR YELL R ELEC
MCKNZ CON
MCKNZ ELEC
MCKNZ WRD
MCLEOD
MCLN ELEC
MCLN-SHRDN R WAT
MDU
MID-CONT CABLE
MIDSTATE TEL
MINOT CABLE
MINOT TEL
MISS VALL COMM
MISS W W S
MNKOTA PWR
MOR-GRAN-SOU ELEC
MOUNT-WILLI ELEC
MRE LBTY TEL
MUNICIPAL
MUNICIPAL
N CENT ELEC
N VALL W DIST
ND PKS & REC
ND TEL
NDDOT
NDSU SOIL SCI DEPT
NEMONT TEL
NODAK R ELEC
NOON FRMS TEL
NPR
NSP
NTH PRAIR RW
NTHN BRDR PL
NTHN PLNS ELEC
NTHWSTRN REF
NW COMM
NWRWD
ONEOK
OSHA
OTTR TL PWR
P L E M
POLAR COM
PVT ELEC
QWEST
R&T W SUPPLY

Great Plains Natural Gas Company
Halstad Telephone Company
Idea1
Inter-Community Telephone Company
Kaneb Pipeline Company
Kem Electric Cooperative Incorporated
Koch Gathering Systems Incorporated
Lakehead Pipeline Company
Langdon Rural Water Users Incorporated
Lower Yellowstone Rural Electric
McKenzie Consolidated Telcom
McKenzie Electric Cooperative
McKenzie County Water Resource District
McLeod USA
McLean Electric Cooperative
McLean-Sheridan Rural Water
Montana-dakota Utilities
Mid-Continent Cable
Midstate Telephone Company
Minot Cable Television
Minot Telephone Company
Missouri Valley Communications
Missouri West Water System
Minnkota Power
Mor-gran-sou Electric Cooperative
Mountrail-williams Electric Cooperative
Moore & Liberty Telephone
City Water And Sewer
City Of '.....'
North Central Electric Cooperative
North Valley Water District
North Dakota Parks And Recreation
North Dakota Telephone Company
North Dakota Department of Transportation
NDSU Soil Science Department
Nemont Telephone
Nodak Rural Electric Cooperative
Noonan Farmers Telephone Company
Northern Plains Railroad
Northern States Power
Northern Prairie Rural Water Association
Northern Border Pipeline
Northern Plains Electric Cooperative Incorporated
Northwestern Refinery Company
Northwest Communication Cooperation
Northwest Rural Water District
Oneok gas
Occupational Safety and Health Administration
Otter Tail Power Company
Prairielands Energy Marketing
Polar Communications
Private Electric
Qwest Communications
R & T Water Supply Association
























RED RIV TEL
RESVTN TEL
ROBRTS TEL
R-RIDER ELEC
RRVW
S CENT REG WD
S E W U
SCOTT CABLE
SHERDN ELEC
SHEYN VLY ELEC
SKYTECH
SLOPE ELEC
SOURIS RIV TELCOM
ST WAT COMM
STATE LN WATER
STER ENG
STUT RWU
SW PL PRJ
T M C
TCI
TESORO HGH PLNS PL
TRI-CNTY WU
TRL CO RWU
UNTD TEL
UPPR SOUR WUA
US SPRINT
USAF MSL CABLE
USFWS
USW COMM
VRNDRY ELEC
W RIV TEL
WEB
WILLI RWA
WILSTN BAS PL
WLSH RWD
WOLVRTN TEL
XLENER
YSVR













Red River Rural Telephone
Reservation Telephone
Roberts Company Telephone
Roughrider Electric Cooperative
Red River Valley & Western Railroad
South Central Regional Water District
South East Water Users Incorporated
Scott Cable Television Dickinson
Sheridan Electric Cooperative
Sheyenne Valley Electric Cooperative
Skyland Technologies Incorporated
Slope Electric Cooperative Incorporated
Souris River Telecommunications
State Water Commission
State Line Water Cooperative
Sterling Energy
Stutsman Rural Water Users
Southwest Pipeline Project
Turtle Mountain Communications
TCI of North Dakota
Tesoro High Plains Pipeline
Tri-County Water Users Incorporated
Traill County Rural Water Users
United Telephone
Upper Souris Water Users Association
U.S. Sprint
U.S.A.F. Missile Cable
US Fish and Wildlife Service
U.S. West Communications
Verendrye Electric Cooperative
West River Telephone Incorporated
W. E. B. Water Development Association
Williams Rural Water Association
Williston Basin Interstate Pipeline Company
Walsh Water Rural Water District
Wolverton Telephone
Xcel Energy
Yellowstone Valley Railroad

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07-01-14	
REVISIONS	
DATE	CHANGE
04-23-18 09-20-18	General Revisions General Revisions








This document was originally
issued and sealed by
Roger Weigel,
Registration Number
PE- 2930 ,
on 09/20/18 and the original
document is stored at the
North Dakota Department
of Transportation

Existing Topography























	Existing Ground Void
	Existing Cemetary Boundary
	Existing Box Culvert Bridge
	Existing Concrete Surface
	Existing Drainage Structure
	Existing Gravel Surface
	Existing Riprap
	Existing Dirt Surface
	Existing Asphalt Surface
	Existing Tie Point Line
	Existing Railroad Centerline
	Existing Guardrail Cable
	Existing Guardrail Metal
	Existing Edge of Water
	Existing Fence
	Existing Railroad
	Existing Field Line
	Exst Flow
	Existing Curb
	Existing Valley Gutter
	Existing Driveway Gutter
	Existing Curb and Gutter
	Existing Mountable Curb and Gutter

	Existing 3-Cable w Posts
	Site Boundary
	Existing Berm, Dike, Pit, or Earth Dam
	Existing Ditch Block
	Existing Tree Boundary
	Existing Brush or Shrub Boundary
	Existing Retaining Wall
	Existing Planter or Wall
	Existing W-Beam Guardrail with Posts
	Existing Railroad Switch
	Gravel Pit - Borrow Area
	Existing Wet Area-Vegetation Break





Proposed Topography

	3-Cable w Posts
	Flow
	Fence
	Remove Line
	Wall
	Retaining Wall (Plan View)
	W-Beam w Posts










Existing Utilities

	Existing Electrical
	Existing Fiber Optic Line
	Existing TV Fiber Optic
	Existing Gas Pipe
	Existing Overhead Utility Line
	Existing Power
	Existing Fuel Pipeline
	Existing Undefined Above Ground Pipe Line
	Existing Sanitary Sewer
	Existing Sanitary Force Main
	Existing Storm Drain
	Existing Storm Drain Force Main
	Existing Culvert
	Existing Telephone Line
	Existing TV Line
	Existing Water or Steam Line
	Existing Under Drain
	Existing Slotted Drain
	Existing Conduit
	Existing Conductor
	Existing Down Guy Wire Down Guy
	Existing Underground Vault or Lift Station




Proposed Utilities

	24 Inch Pipe
	Reinforced Concrete Pipe
	Under Drain
	Edge Drain

Traffic Utilities

	Conductor
	Fiber Optic
	Existing Loop Detector
	Existing Double Micro Loop Detector
	Micro Loop Detector Double
	Existing Micro Loop Detector
	Micro Loop Detector
	Signal Head with Mast Arm
	Existing Signal Head with Mast Arm

Sign Structures














	Existing Overhead Sign Structure
	Existing Overhead Sign Structure Cantilever
	Overhead Sign Structure Cantilever

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07-01-14	
REVISIONS	
DATE	CHANGE
09-23-16	Added and Revised Items, Organized by Functional Groups










This document was originally issued and sealed by
Roger Weigel,
Registration Number
PE-2930,
on 09/23/16 and the original document is stored at the
North Dakota Department
of Transportation

Line Styles









Right Of Way

	Easement
	Existing Easement
	Right of Way
	Existing Right of Way
	Existing Right of Way Railroad
	Existing Right of Way Not State Owned
	Existing Government Lot Line
	Existing Adjacent Block Lines
	Existing Adjacent Lot Lines
	Existing Adjacent Property Line
	Existing Adjacent Subdivision Lines
	Sight Distance Triangle Line
	Dimension Leader







Boundary Control



	Existing City Corporate Limits or Reservation Boundary
	Existing State or International Line
	Existing Township
	Existing County
	Existing Section Line
	Existing Quarter Section Line
	Existing Sixteenth Section Line
	Existing Centerline
	Tangent Line

Cross Sections and Typicals



	Existing Ground
	Existing Topsoil (Cross Section View)
	Existing Ground Void (Not Surveyed)
	Existing Concrete
	Existing Aggregate (Cross Section View)
	Existing Curb and Gutter (Cross Section View)
	Existing Asphalt (Cross Section View)
	Existing Reinforcement Rebar

Geotechnical



	Geotextile Fabric Type D
	Geogrid
	Geotextile Fabric Type R
	Geotextile Fabric Type R1
	Geotextile Fabric Type RR
	Geotextile Fabric Type S

	Subgrade Reinforcement
	Failure Line







Countours

	Depression Contours
	Supplemental Contour





Profile

	Subgrade, Subcut or Ditch Grade
	Topsoil Profile










Striping

	Centerline Pavement Marking
	Barrier with Centerline Pavement Marking
	Barrier Pavement Marking
	Stripe 4 IN Dotted Extension White
	Stripe 8 IN Dotted Extension White
	Stripe 8 IN Lane Drop








Pavement Joints

	Doweled Joint
	Tie Bar 30 Inch 4 Foot Center to Center
	Tie Bar 18 Inch 3 Foot Center to Center
	Tie Bar at Random Spacing






Bridge Details

	Hidden Object
	Small Hidden Object
	Large Hidden Object
	Phantom Object
	Centerline Main
	Centerline
	Existing Ground (Details)
	Existing Conditions
	Sheet Piling

Erosion Control

	Limits of Const Transition Line
	Bale Check
	Rock Check
	Floating Silt Curtain
	Silt Fence
	Excavation Limits
	Fiber Rolls
































































































Environmental

	Wetland Mitigation
	Existing Wetland Easement USFWS
	Existing Wetland Jurisdictional
	Existing Wetland
	Tree Row

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07-01-14	
REVISIONS	
DATE	CHANGE
09-23-16	Added and Revised Items, Organized by Functional Groups






























































































This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930 , on 09/23/16 and the original document is stored at the North Dakota Department of Transportation

Symbols

	North Arrow (Half Scale)		Attenuation Device		Existing Railroad Battery Box		Existing Delineator Type E														
	Truck Mounted Attenuator		Diamond Grade Delineator Type A		Existing Bush or Shrub		Existing EFB Misc														
	Type I Barricade		Diamond Grade Delineator Type B		Existing Gas Cap or Stub		Existing Flashing Beacon														
	Type II Barricade		Diamond Grade Delineator Type C		Existing Sanitary Cap or Stub		Existing Pipe Mounted Flasher														
	Type III Barricade		Diamond Grade Delineator Type D		Existing Storm Drain Cap or Stub		Existing Pad Mounted Feed Point														
	Catch Basin		Diamond Grade Delineator Type E		Existing Water Cap or Stub		Existing Pipe Mounted Feed Point with Pad														
	Cairn or Stone Circle		Flexible Delineator		Existing Sanitary Cleanout		Existing Pole Mounted Feed Point														
	Video Detection Camera		Flexible Delineator Type A		Existing Concrete Foundation		Existing Railroad Frog														
	Storm Drain Cap or Stub		Flexible Delineator Type B		Existing Traffic Signal Controller		Existing Snow Gate 18														
	Corrugated Metal End Section 18 Inch		Flexible Delineator Type C		Existing Pad Mounted Signal Controller		Existing Snow Gate 28														
	Corrugated Metal End Section 24 Inch		Flexible Delineator Type D		Existing Sixteenth Section Corner		Existing Snow Gate 40														
	Corrugated Metal End Section 30 Inch		Flexible Delineator Type E		Existing Quarter Section Corner		Existing Headwall														
	Corrugated Metal End Section 36 Inch		Delineator Type A		Existing Section Corner		Existing Pedestrian Head with Number														
	Corrugated Metal End Section 42 Inch		Delineator Type A Reset		Existing Railroad Crossbuck		Existing Signal Head														
	Corrugated Metal End Section 48 Inch		Delineator Type B		Existing Satellite Dish		Existing Sprinkler Head														
	Concrete Foundation		Delineator Type B Reset		Existing Fuel Dispensers		Existing Fire Hydrant														
	Ground Connection Conductor		Delineator Type C		Existing Flexible Delineator Type A		Existing Catch Basin Drop Inlet														
	Neutral Connection Conductor		Delineator Type D		Existing Flexible Delineator Type B		Existing Curb Inlet														
	Phase 1 Connection Conductor		Delineator Type E		Existing Flexible Delineator Type C		Existing Manhole Inlet														
	Phase 2 Connection Conductor		Delineator Drums		Existing Flexible Delineator Type D		Existing Junction Box														
	Traffic Cone		Spot Elevation		Existing Flexible Delineator Type E	<table><tr><th colspan="2">NORTH DAKOTA DEPARTMENT OF TRANSPORTATION</th></tr><tr><th colspan="2">07-01-14</th></tr><tr><th colspan="2">REVISIONS</th></tr><tr><th>DATE</th><th>CHANGE</th></tr><tr><td></td><td></td></tr><tr><td></td><td></td></tr><tr><td></td><td></td></tr></table> <div>This document was originally issued and sealed by Roger Weigel, Registration Number PE- 2930, on 07/01/14 and the original document is stored at the North Dakota Department of Transportation</div>		NORTH DAKOTA DEPARTMENT OF TRANSPORTATION		07-01-14		REVISIONS		DATE	CHANGE						
NORTH DAKOTA DEPARTMENT OF TRANSPORTATION																					
07-01-14																					
REVISIONS																					
DATE	CHANGE																				
	Signal Controller		Existing Access Control Arrow		Existing Delineator Type A																
	Pad Mounted Signal Controller		Existing Artifact		Existing Delineator Type B																
	Alignment Data Point		Existing Flashing Beacon		Existing Delineator Type C																
	Emergency Vehicle Detector		Existing Benchmark		Existing Delineator Type D																

Symbols



























































D-101-31

	Existing Light Standard		Existing Manhole with Valve Water		Existing Telephone Pole		Existing Undefined Manhole
	Existing High Mast Light Standard 10 Luminaire		Existing Water Manhole		Existing Wood Pole		Existing Undefined Pull Box
	Existing High Mast Light Standard 3 Luminaire		Existing Mile Post Type A		Existing Post		Existing Undefined Pedestal
	Existing High Mast Light Standard 4 Luminaire		Existing Mile Post Type B		Existing Pedestrian Push Button Post		Existing Undefined Valve
	Existing High Mast Light Standard 5 Luminaire		Existing Mile Post Type C		Existing Control Point CP		Existing Undefined Pipe Vent
	Existing High Mast Light Standard 6 Luminaire		Existing Reference Marker		Existing Control Point GPS-RTK		Existing Gas Valve
	Existing High Mast Light Standard 7 Luminaire		Existing RW Marker		Existing Control Point TRI		Existing Water Valve
	Existing High Mast Light Standard 8 Luminaire		Existing Utility Marker		Existing Reference Marker Point NGS		Existing Fuel Pipe Vent
	Existing High Mast Light Standard 9 Luminaire		Iron Monument Found		Existing Pull Box		Existing Gas Pipe Vent
	Existing Overhead Sign Structure Load Center		Iron Pin R/W Monument		Existing Intelligent Transportation Pull Box		Existing Sanitary Pipe Vent
	Existing Luminaire		Existing Object Marker Type I		Existing Water Pump		Existing Storm Drain Pipe Vent
	Existing Light Standard Luminaire		Existing Object Marker Type II		Existing Slotted Reinforced Concrete Pipe		Existing Water Pipe Vent
	Existing Federal Mailbox		Existing Object Marker Type III		Existing RR Profile Spot		Existing Weather Station
	Existing Private Mailbox		Existing Electrical Pedestal		Existing Fuel Leak Sensors		Existing Ground Water Well Bore Hole
	Existing Meander Section Corner		Existing Telephone Pedestal		Existing Highway Sign		Existing Windmill or Tower
	Existing Meter		Existing Fiber Optic Telephone Pedestal		Existing Miscellaneous Spot		Existing Witness Corner
	Existing Electrical Manhole		Existing TV Pedestal		Existing Lighting Standard Pole		Flashing Beacon
	Existing Gas Manhole		Existing Fiber Optic TV Pedestal		Existing Traffic Signal Standard		Flagger
	Existing Sanitary Manhole		Existing Fuel Filler Pipes		Existing Transformer		Pipe Mounted Flasher
	Existing Sanitary Force Main Manhole		Existing Traverse PI Aerial Panel		Existing Large Evergreen Tree		Sanitary Force Main with Valve
	Existing Sanitary Manhole with Valve		Existing Pole		Existing Small Evergreen Tree		
	Existing Storm Drain Manhole		Existing Power Pole		Existing Large Tree		
	Existing Force Main Storm Drain Manhole		Existing Power Pole with Transformer		Existing Small Tree		
	Existing Force Main Storm Drain Manhole with Valve				Existing Tree Trunk		
	Existing Telephone Manhole				Existing Pad Mounted Traffic Signal Control Box		

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07-01-14	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 07/01/14 and the original document is stored at the North Dakota Department of Transportation

Symbols

	Pad Mounted Feed Point		Light Standard 1000 Watt High Pressure Sodium Vapor Luminaire		Object Marker Type I		Reinforced Concrete End Section 48 Inch
	Pipe Mounted Feed Point with Pad		Light Standard 150 Watt High Pressure Sodium Vapor Luminaire		Object Marker Type II		Reinforced Concrete End Section 54 Inch
	Pole Mounted Feed Point		Light Standard 175 Watt High Pressure Sodium Vapor Luminaire		Object Marker Type III		Reset Right of Way Marker
	Headwall		Light Standard 200 Watt High Pressure Sodium Vapor Luminaire		Caution Mode Arrow Panel		Reset USGS Marker
	Double Headwall with Vegetation Barrier		Light Standard 250 Watt High Pressure Sodium Vapor Luminaire		Back to Back Vertical Panel Sign		Right of Way Markers
	Single Headwall with Vegetation Barrier		Light Standard 310 Watt High Pressure Sodium Vapor Luminaire		Double Direction Arrow Panel		Riser 30 Inch
	Pole Mounted Head		Light Standard 35 Watt High Pressure Sodium Vapor Luminaire		Left Directional Arrow Panel		Continuous Split Barrel Sample
	Sprinkler Head		Light Standard 400 Watt High Pressure Sodium Vapor Luminaire		Right Directional Arrow Panel		Flight Auger Sample
	Fire Hydrant		Light Standard 50 Watt High Pressure Sodium Vapor Luminaire		Sequencing Arrow Panel		Split Barrel Sample
	Inlet Type 1		Light Standard 70 Watt High Pressure Sodium Vapor Luminaire		Truck Mounted Arrow Panel		Thinwall Tube Sample
	Inlet Type 2		Light Standard 700 Watt High Pressure Sodium Vapor Luminaire		Power Pole		Highway Sign
	Double Inlet Type 2		Manhole		Wood Pole		SNOW GATE 18 FT
	Inlet Grate Type 2		Manhole 48 Inch		Pedestrian Push Button Post		SNOW GATE 28 FT
	Junction Box		Sanitary Force Main Manhole		Property Corner		SNOW GATE 40 FT
	High Mast Light Standard 10 Luminaire		Sanitary Sewer Manhole		Pull Box		Standard Penetration Test
	High Mast Light Standard 3 Luminaire		Storm Drain Manhole		Intelligent Transportation Pull Box		Transformer
	High Mast Light Standard 4 Luminaire		Storm Drain Manhole with Inlet		Sanitary Pump		Inclinometer Tube
	High Mast Light Standard 5 Luminaire		Reset Mile Post		Storm Drain Pump		Underdrain Cleanout
	High Mast Light Standard 6 Luminaire		Mile Post Type A		Reinforced Pavement		Excavation Unit
	High Mast Light Standard 7 Luminaire		Mile Post Type B		Reinforced Concrete End Section 15 Inch		Water Valve
	High Mast Light Standard 8 Luminaire		Mile Post Type C		Reinforced Concrete End Section 18 Inch		
	High Mast Light Standard 9 Luminaire		Right of Way Marker		Reinforced Concrete End Section 24 Inch		
	Relocate Light Standard		Tubular Marker		Reinforced Concrete End Section 30 Inch		
	Overhead Sign Structure Load Center		Alignment Monument		Reinforced Concrete End Section 36 Inch		
	Light Standard 100 Watt High Pressure Sodium Vapor Luminaire		Iron Pin Reference Monument		Reinforced Concrete End Section 42 Inch		

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
07-01-14	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by Roger Weigel, Registration Number PE-2930, on 07/01/14 and the original document is stored at the North Dakota Department of Transportation

Cross Section Legend


Description	Longitudinal Parallel to Roadway	Transverse Perpendicular to Roadway*
Cable Line	● CBL1	● CBL2
Conduit Line	● CDU1	● CDU2
Electric Line	● E1	● E2
Fiber Optic Line	● F1	● F2
Gas Main Line	● GM1	● GM2
Gas Service Line	● GS1	● GS2
Gas Transmission Line	● GT1	● GT2
Fuel Pipeline	● PL1	● PL2
Sanitary Sewer Force Main	● SSF1	● SSF2
Sanitary Sewer	● SS1	● SS2
Steam Line	● STE1	● STE2
Storm Drain (Assumed Depth)	● SD1	● SD2
Telephone Line	● T1	● T2
TV Line	● TV1	● TV2
Water Main Line	● WM1	● WM2
Water Service Line	● WS1	● WS2

Description	Longitudinal Parallel to Roadway	Transverse Perpendicular to Roadway*
Overhead Power Transmission Line	OHT1 ↑	OHT2 ↑
Overhead Line	OH1 ↑	OH2 ↑



When storm drain invert elevations are NOT used to draw pipe, they will appear as shown to the left. When invert elevations are used to draw pipe, they will be a cross section similar to the graphics shown below.

* Usually the transverse utilities are shown on a cross section with 2 or more symbols. The utility runs from one symbol to the other, but the connection may not be shown.




On the right side of most cross sections there is a earthwork table. The following example (values not related to project) details the earthwork table layout.

Cut Area	CA: 34.34 SF
Fill Area	FA: 0.017 SF
Cut Volume	CV: 64.44 CY
Fill Volume	FV: 0.031 CY
Mass Ordinate	MO: 65.13 CY






NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
9-20-18	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by
Roger Weigel,
Registration Number
PEPE-2930
on 9/20/18 and the original document is stored at the
North Dakota Department
of Transportation

EROSION AND SILTATION CONTROL
EROSION CONTROL BLANKET INSTALLATION





NOTE:
If a Single Net Blanket is used the side with the netting should be on the top once the blanket is installed.



BLANKET LAYOUT
CHANNEL OR SLOPE INSTALLATION

3.8 staples per square yard
using 8-inch 11 gauge wire
"u" staples.




NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-03-13	
REVISIONS	
DATE	CHANGE
06-26-14	Changed standard drawing number from D-708-S to D-255-2.
07-27-15	Changed installation details such as trench depth and overlap dimensions.
08-27-19	New Design Engineer PE Stamp.

This document was originally issued and sealed by
Kirk J Hoff,
Registration Number
PE- 4683,
on 08/27/19 and the original document is stored at the
North Dakota Department
of Transportation


EROSION CONTROL
FIBER ROLL PLACEMENT DETAILS

D-261-1




*Optional Weir. Use in flat areas, such as the Red River Valley, where there is potential for water to back up on adjacent property. Lower fiber roll enough to prevent water from backing up on adjacent property. Do not use 20-inch fiber rolls in flat areas where there is potential for water to back up on adjacent property.


12 OR 20 INCH FIBER ROLL - DITCH BOTTOM




PLAN VIEW FOR SLOPE APPLICATION



PLAN VIEW FOR DITCH APPLICATION



Detail A
Fiber Roll Overlapping Staking Detail



Detail B
Fiber Roll Staking Detail

FIBER ROLL DIAMETER	NOMINAL STAKE SIZE	MINIMUM STAKE LENGTH	MINIMUM TRENCH DEPTH	MAXIMUM TRENCH DEPTH
6"	2" x 2"	18"	2"	2"
12"	2" x 2"	24"	2"	3"
20"	2" x 2"	36"	3"	5"




NOTE: Runoff must not be allowed to run under or around roll.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-18-10	
REVISIONS	
DATE	CHANGE
06-10-13	Added plan view for ditch and slope application. Added table with values for stake and trench dimensions.
10-04-13	Revised fiber roll overlap detail.
06-26-14	Changed standard drawing number from D-708-7 to D-261-1.
08-27-19	New Design Engineer PE Stamp

This document was originally issued and sealed by
Kirk J Hoff,
Registration Number
PE- 4683,
on 08/27/19 and the original document is stored at the
North Dakota Department
of Transportation

Perforated Tube

- Notes:
1. Torque slip base bolts as specified by manufacturer.
 2. Use anchor with 43.9 KSI yield strength and 59.3 KSI tensile strength.
 3. Provide 4" vertical clearance for anchor or breakaway base. Measure the 4"x60" measurement above and below post location and back and ahead of post.
 4. In concrete sidewalk, use same anchor without wings.
 5. Provide more than 7' between the first and fourth posts of a four post sign.





Telescoping Perforated Tube						
Number of Posts	Post Size in.	Wall Thick-ness Gauge	Sleeve Size in.	Wall Thick-ness Gauge	Slip Base	Anchor Size without Slip Base in.
1	2	12			No	2 1/4
1	2 1/4	12			No	2 1/2
1	2 1/2	12			(A)	3
1	2 1/2	10			Yes	
1	2 1/4	12	2	12	Yes	
1	2 1/2	12	2 1/4	12	Yes	
2	2	12			No	2 1/4
2	2 1/4	12			No	2 1/2
2	2 1/2	12			Yes	
2	2 1/2	12			Yes	
2	2 1/4	10	2	12	Yes	
2	2 1/2	12	2 1/4	12	Yes	
3 & 4	2 1/2	12			Yes	
3 & 4	2 1/2	10			Yes	
3 & 4	2 1/2	12	2 1/4	12	Yes	
3 & 4	2 1/4	12	2	12	Yes	
3 & 4	2 1/2	10	2 3/16	10	Yes	

Properties of Telescoping Perforated Tube						
Tube Size in.	Wall Thickness in.	U.S. Standard Gauge	Weight per Foot lbs.	Moment of Inertia in. ⁴	Cross Sec. Area in. ²	Section Modulus in. ³
1 1/2 x 1 1/2	0.105	12	1.702	0.129	0.380	0.172
2 x 2	0.105	12	2.416	0.372	0.590	0.372
2 1/4 x 2 1/4	0.105	12	2.773	0.561	0.695	0.499
2 3/8 x 2 3/8	0.135	10	3.432	0.605	0.841	0.590
2 1/2 x 2 1/2	0.105	12	3.141	0.804	0.803	0.643
2 1/2 x 2 1/2	0.135	10	4.006	0.979	1.010	0.785






Top Post Receiver Data Table						
Square Post Sizes (B)	A	B	C	D	E	F
2 3/16"x10 ga.	1 5/16"	2 1/2"	3 1/2"	2 5/32"	1 33/64"	1 7/8"
2 1/2"x10 ga.	1 3/32"	2 1/2"	3 5/16"	5/8"	1 21/32"	1 3/4"

- (A) Use breakaway base when support is placed in weak soils. Engineer determines if soils are weak.
- (B) For additional wind load, insert the 2 3/8"x10 ga. into 2 1/2"x10 ga.



NORTH DAKOTA DEPARTMENT OF TRANSPORTATION		This document was originally issued and sealed by Kirk J Hoff, Registration Number PE- 4683, on 10/03/19 and the original document is stored at the North Dakota Department of Transportation
2-28-14		
REVISIONS		
DATE	CHANGE	
9-27-17 10-03-19	Updated to active voice New Design Engr PE Stamp	

U-Channel Post



Alternate A Steps of Installation:


- a) Drive anchor unit to within 12" of ground level.
b) Establish proper assembly by lining up bottom hole of retainer strap with 6th hole from the top of the anchor unit.
c) Assemble strap to back of anchor unit using 5/16"x2" bolt, lock washer and nut.
d) Rotate strap 90° to left.
- a) Drive anchor unit to 4" above ground.
b) Rotate strap to vertical position.
- a) Place 5/16"x2" bolt, lock washer and nut in bottom of sign post to facilitate alignment of sign post with proper hole in anchor unit.
b) Alternately tighten two connector bolts.
- Complete assembly by tightening 5/16"x2" bolt (this fastens sign post to retainer strap).
- Properly nest base post, strap, and sign post. Proper nesting occurs when all flat surfaces of the base post, strap, and sign post at the bolts have full contact across the entire width.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
2-28-14	
REVISIONS	
DATE	CHANGE
9-27-17 10-03-19	Updated to active voice New Design Engr PE Stamp


This document was originally issued and sealed by
Kirk J Hoff,
Registration Number
PE- 4683,
on 10/03/19 and the original document is stored at the
North Dakota Department
of Transportation

CONSTRUCTION SIGN DETAILS
TERMINAL AND GUIDE SIGNS


D-704-9




G20-1-60
Legend: black (non-refl)
Background: orange




G20-50a-72
Legend: black (non-refl)
Background: orange




E5-1(L or R)-48
Legend: white
Background: green (orange optional)




E5-1-48




G20-1b-60
Legend: black (non-refl)
Background: orange




G20-52a-72
Legend: black (non-refl)
Background: orange




M4-8-36
Legend: black (non-refl)
Background: orange




G20-50a-72
G20-52a-72




G20-2-48
Legend: black (non-refl)
Background: orange




G20-55-96
Legend: black (non-refl)
Background: orange



M4-9(L or R)-30
Right or Left



M4-9(L or R)-30
Advanced Right or Left




M4-9-30
Straight

ARROW DETAILS






NOTES:
(A) Arrow may be right or left of the legend to indicate construction to the right or left.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-13-13	
REVISIONS	
DATE	CHANGE
8-17-17 10-03-19	Added sign & background color New Design Engineer PE Stamp

This document was originally issued and sealed by
Kirk J Hoff,
Registration Number
PE- 4683,
on 10/03/19 and the original document is stored at the
North Dakota Department
of Transportation



M4-9(L or R)-30 &
M4-9-30
Legend: black (non-refl)
Background: orange




NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-13-13	
REVISIONS	
DATE	CHANGE
8-17-17 10-03-19	Revised sign number New Design Engineer PE Stamp

This document was originally issued and sealed by
Kirk J Hoff,
Registration Number
PE- 4683 ,
on 10/03/19 and the original document is stored at the
North Dakota Department
of Transportation


CONSTRUCTION SIGN DETAILS
WARNING SIGNS

D-704-11




W5-8-48

Legend: black (non-refl)
Background: orange




W8-53-48

Legend: black (non-refl)
Background: orange




W8-56-48

Legend: black (non-refl)
Background: orange




W5-9-48

Legend: black (non-refl)
Background: orange




W8-54-48

Legend: black (non-refl)
Background: orange




W9-3a-48

Legend: black (non-refl)
Background: orange



W8-9a-48

Legend: black (non-refl)
Background: orange




W8-55-48


Legend: black (non-refl)
Background: orange

WORD	LETTER SPACING
AHEAD	Standard
200 FT	Standard
350 FT	Standard
500 FT	Standard
1000 FT	Reduce 40%
1500 FT	Reduce 40%
½ MILE	Reduce 50%
1 MILE	Standard

* DISTANCE MESSAGES



W5-9-48




W9-3a-48

ARROW DETAILS

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
8-13-13	
REVISIONS	
DATE	CHANGE
8-17-17 5-31-18 10-03-19	Updated sign number Revised sign and arrow details New Design Engineer PE Stamp


This document was originally
issued and sealed by
Kirk J Hoff,
Registration Number
PE- 4683,
on 10/03/19 and the original
document is stored at the
North Dakota Department
of Transportation

BARRICADE AND CHANNELIZING DEVICE DETAILS




Provide horizontal, circumferential, alternating orange and white retroreflective stripes 4" to 6" wide for drum markings. Use a minimum of two orange and two white stripes with the top stripe being orange for each drum. Do not exceed 3" nonretroreflectORIZED spaces between the horizontal orange and white stripes. Avoid placement of stripes on drum ribs or indentations. Use closed top drums that will not allow collection of debris. Do not place ballast on the top of drum.


Provide alternating orange and white retroreflective stripes, sloping downward in direction vehicular traffic is to pass. Place retroreflective sheeting on both sides of panel with a minimum of 270 square inches of retroreflective area facing vehicular traffic. Where the height of the retroreflective material on the vertical panel is 36 inches or more, use a stripe width of 6 inches.




Provide retroreflectORIZATION of cones more than 36" in height by alternating orange and white retroreflective stripes. Use a minimum of two orange and two white stripes for each cone with the top stripe being orange. Use maximum 3" nonretroreflectORIZED space between the orange and white stripes.



Provide retroreflectORIZATION of tubular markers more than 42" in height by alternating four 4" to 6" wide orange and white stripes with the top stripe being orange.




- INSTALLATION NOTES:
1. Drill installation holes to diameter and depth required by manufacturer's specifications.
 2. For removal, remove anchors and fill installation hole with an epoxy designed to bond to pavement surface.
 3. In lieu of bolted down base, use an 8" x 8" butyl pad or hot melt butyl. Remove butyl as close as possible to pavement surface.



BARRICADE BLADE DETAIL


BARRICADE ASSEMBLY DETAIL (Aluminum Barricade Rails)

NOTE: For barricade markings use alternating orange and white retroreflective stripes, sloping downward in the direction traffic is to pass. Place retroreflective sheeting on both sides of the rails with a minimum of 270 square inches of visible retroreflective area facing vehicular traffic. When the barricade length is less than 36", use a rail stripe width of 4".




TYPE I BARRICADE


TYPE II BARRICADE
BARRICADE RAIL DETAILS



SIDE VIEW




TYPE III BARRICADE



ELEVATION VIEW

BARRICADE ASSEMBLY DETAIL (Wood or Plastic Rails)

SIDE VIEW



REFLECTOR DETAIL

ELEVATION

DELINEATORS

MINIMUM BALLAST (For each side of barricade support)

Without Sign	4 - 25 lb sandbags
With Sign	6 - 25 lb sandbags


Note: Number of sandbags based on a wind speed of 55 MPH. Sandbags assumed to be placed at or near the ends of the skids.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-3-13	
REVISIONS	
DATE	CHANGE
9-27-17 11-01-19	Updated to active voice Revised details for Flexible Delineator


This document was originally issued and sealed by
Kirk J Hoff,
Registration Number
PE- 4683,
on 11/1/19 and the original document is stored at the North Dakota Department of Transportation

CONSTRUCTION SIGN PUNCHING AND MOUNTING DETAILS


Note: In curb sections, place signs a minimum horizontal distance of 2' from face of the curb to near edge of the sign.




TYPICAL SECTION
(48" x 48" diamond warning sign shown)




24" x 24"
ROUTE MARKER
ASSEMBLY




36" x 36"
ROUTE MARKER
ASSEMBLY




48" x 48" DIAMOND SIGN
(with 30" x 30" secondary sign)




R1-2-60 - YIELD SIGN




R1-1-48 - STOP SIGN
(with R6-1-54 sign as required)




48" x 48" SIGN
(with R6-1-54 sign as required)




24" x 36" SIGN




48" x 48" DIAMOND SIGN
(with 30" x 24" secondary sign)




W14-3-64 - PENNANT SIGN




R1-1-48 - STOP SIGN
(with R1-50P-24 sign as required)




48" x 48" SIGN
(with R2-1aP-24 sign as required)




30" x 24" SIGN




108" x 48" SIGN




96" x 48" SIGN




72" x 36" SIGN




72" x 24" SIGN




60" x 24" SIGN



48" x 24" SIGN



PORTABLE SIGN SUPPORT
LOW-MOUNTING HEIGHT



PORTABLE SIGN SUPPORT
HIGH-MOUNTING HEIGHT

NOTES:

1. Sign Supports: Galvanize or paint supports. Minimum post sizes are 2.5 lb/ft u-channel or 2" x 2" x 12 gauge steel perforated tube, except where noted. When installing signs on u-channel, minimum post size for assemblies containing a secondary sign is 3.0 lb/ft. Post sizes based on a wind speed of 55 MPH.

Place signs over 50 square feet on 2½" x 2½" perforated tube supports as a minimum.

Do not attach guy wires to sign supports. Attach wind beams behind sign panels when used with u-posts.
2. Sign Panels: Provide sign panels made of 0.100" aluminum, ½" plywood, or other approved material, except where noted. Punch all holes round for ⅝" bolts.
3. Alternate Messages: Install and remove alternate message signs on reflectorized plate (without borders) as required. (i.e. "Left" and "Right" message on lane closure sign)
4. Route Marker Auxiliary Signs: Provide route marker auxiliary signs, such as the cardinal direction and directional arrows, with a background and legend that match the route marker they are used with:

Interstate - white legend on blue background
Interstate Business Loop - white legend on green background
US and State - black legend on white background
County - yellow legend on blue background

5. Vertical Clearance: Install signs with a vertical clearance of 5'-0" (see TYPICAL SECTION). In areas where parking or pedestrian movements are likely or the view of the sign may be obstructed, install signs with a vertical clearance of 7'-0" from the top of the curb or from the near edge of the driving lane in absence of a curb.

The vertical clearance to secondary signs is 1'-0" less than the vertical clearance stated above.

Provide a minimum clearance of 7'-0" from the ground at the post for signs with an area exceeding 50 square feet.

6. Portable Signs: Provide portable signs that meet the vertical clearance stated above when it is necessary to place signs within the pavement surface.

Use of low-mounting height (minimum 12" vertical clearance) portable signs for 5 days or less, is allowed as long as the view of the sign is not obstructed. Time delays caused by unforeseen circumstances, such as equipment breakdown, rain, subgrade failures, etc., will not accrue towards the 5 day period. Use of R9-8 through R9-11a series, W1-6 through W1-8 series, M4-10, and E5-1 is allowed for longer than 5 days.

Restrict signs mounted on portable sign supports shown in the LOW-MOUNTING HEIGHT and HIGH-MOUNTING HEIGHT details to a maximum surface area of 16 square feet.

MINIMUM BALLAST
(For each side of sign support base)

Sign Panel Mounting Height (ft)	Number of 25 lb sandbags for 4' x 4' sign panel
1'	6
5'	8
7'	10

Note: The number of sandbags are based on a wind speed of 55 MPH. Place sandbags at or near the ends of skids.


NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-4-13	
REVISIONS	
DATE	CHANGE
11-14-13	Revised Note 6
9-27-17	Updated to active voice
11-01-19	Revised 60"x24" sign detail

This document was originally issued and sealed by

Kirk J Hoff,
Registration Number
PE-4683,
on 11/1/19 and the original document is stored at the North Dakota Department of Transportation

CONSTRUCTION TRUCK AND TEMPORARY DETOUR LAYOUTS

D-704-22



Notes

- Place barricades on a moveable assemblies and signs on portable assemblies when located on roadway.
- Where necessary, safe speed to be determined by the Engineer.
- Determine the reduced speed limit based on the in-place speed limit before construction. Where speed reductions exceed 30 mph, install a second speed limit sign with the desired speed reduction (not to exceed 30 mph.) Place the second speed limit sign at $\frac{1}{2}$ B.
- Install flags on warning signs in urban areas when signs are not portable. Mount 24 inch square flags perpendicular to the edges of the sign, and at such a distance above the edge that the flag does not touch the sign when limp.
- Cover existing speed limit signs within a reduced speed zone.
- Covered (when approved by engineer) or obliterated pavement marking measured as Obliteration of Pavement Marking.
- As an option, use portable sign supports in lieu of post mounted signs in accordance with NDDOT Standard Drawing D-704-14.
- Install sign G20-1b-60 when work is suspended for winter.
- If existing stop sign is in place, a 48" stop sign is not required.
- Sign G20-55-96 is not required if layout is part of other traffic control or if work is less than 15 days.
- Recommend using 40 mph speed limit in vicinity of workers, unless location and conditions dictate otherwise.


ADVANCE WARNING SIGN SPACING			
Road Type	Distance Between Signs Min. (ft)		
	A	B	C
Urban - Low Speed (30 mph or less)	150	150	150
Urban - Low Speed (over 30 to 40mph)	280	280	280
Urban - High Speed (over 40 mph to 50 mph)	360	360	360
Rural - High Speed (over 50 mph to 65 mph)	720	720	720
Urban Expressway and Freeway (55 mph to 60 mph)	850	1350	2200
Rural Expressway and Freeway (70 mph to 75 mph)	1000	1500	2640
Interstate/4-Lane Divided (Maintenance and Surveying)	750	1000	1500

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
9-27-13	
REVISIONS	
DATE	CHANGE
8-17-17 11-01-19	Update notes & sign numbers Revised sign numbers & note 7

This document was originally issued and sealed by
Kirk J Hoff,
Registration Number
PE- 4683,
on 11/1/19 and the original document is stored at the
North Dakota Department
of Transportation

PORTABLE SIGN SUPPORT ASSEMBLY

D-704-50



Notes:




- ① The maximum weight of the assembly is 250 pounds.
- ② Use a 14" wheel and tire.
- ③ Automotive and equipment axle assemblies may not be used for trailer-mounted sign supports.
- ④ Other NCHRP 350 crash tested assemblies are acceptable.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-23-10	
REVISIONS	
DATE	CHANGE

This document was originally issued and sealed by
Roger Weigel
Registration Number
PE- 2930 ,
on 11/23/10 and the original document is stored at the
North Dakota Department
of Transportation

CONCRETE PIPE, CATTLE PASS, OR
PRECAST CONCRETE BOX CULVERT TIES




D-714-22






SECTION A-A

REQUIRED SIZE OF TIE BOLTS		
Pipe Size	Thread ϕ	XXS Pipe Sleeve Inner ϕ
18" - 24"	$\frac{5}{8}$ " See note 2	$\frac{3}{4}$ "
30" - 66"	$\frac{3}{4}$ "	1"
72" - 78"	1"	1 $\frac{1}{4}$ "
RCB/Cattle Pass		


- NOTES:
- The pipe size listed is the inside diameter of round pipe or the equivalent diameter of pipe arch.
 - Cattle Pass and Jacked and Bored pipes shall have pipe ties inserted from the inside of the pipes and grouted into place. Jacked and bored pipes with a diameter of 24" or less do not require pipe ties.
 - Nuts and washers are not required on Jacked and Bored pipes or pipes with a 24" diameter or less. Where nuts and washers are not used, the tie bars shall be inserted and grouted into place.
 - Ties are only for holding pipe or RCB sections together, not for pulling sections tight.
 - Tie bolt assembly shall be hot dip galvanized in accordance with AASHTO M232.
 - Holes in pipes to accommodate tie bolts can be precast or drilled. Tapered holes are permitted when precast. Holes shall have a diameter $\frac{1}{4}$ " larger than the diameter of the thread. Holes in precast RCB's shall contain cast-in bolt sleeves with an inside diameter of 1 $\frac{1}{4}$ ".
 - The contractor has the option of selecting the type of tie bolt used from those shown.
 - The cost of precasting or drilling the required holes and furnishing and installing the tie bolts shall be included in the price bid for the appropriate conduit or RCB pay item.
 - All centerline and approach RCP culvert joints shall be tied. Storm drain systems shall have the first three joints including the end section of all free ends tied. Free ends are defined as any storm drain end which does not terminate at an inlet or manhole. Outfall culverts with end sections which drain adjacent ditches are examples of free ends.
 - Place joint wrap prior to installing ties. Overlap the joint by 12" in both directions.
 - Tie bolts shall conform to ASTM A 36. Nuts shall be heavy hex and conform to ASTM A 563. Washers shall conform to ASTM F 436, Type 1. Welded pipe sleeves and cast-in bolt sleeves shall conform to ASTM A 53, Grade B.
 - RCB tie locations shall be as shown on the plans.





DETAIL A




DETAIL B



PLAN VIEW



END VIEW



NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
3-18-14	
REVISIONS	
DATE	CHANGE
7-21-15 6-6-17	Note 8 Notes 2-11, Table, Title, Labels

This document was originally issued and sealed by Jonathan David Ketterling, Registration Number PE-4684, on 6/6/2017 and the original document is stored at the North Dakota Department of Transportation