

DESIGN DATA


Traffic ~ HEC-0004(202)		Average Daily (All Locations)			Est. 30th Max. Hr.
		Passenger	Trucks	Total	
Current Traffic	2025	<100	-	<100	-
Forecast Traffic	2045	<100	-	<100	-

Clear Zone Distance:

14 Feet
45 MPH
360 Feet

Design Speed:

Minimum Sight Dist. for Stopping:



STATE COUNTY MAP

BILLINGS COUNTY

NORTH DAKOTA

PLANS FOR FEDERAL AID PROJECT

BEGIN SITE 1
Sta 10+90.79. A point 97.09 feet west and 757.09 feet north of the South Quarter Corner of Section 32, Township 142 N, Range 101 W, of the 5th P.M., Billings County, North Dakota

END SITE 1
Sta 15+05.39. A point 53.09 feet west and 344.85 feet north of the South Quarter Corner of Section 32, Township 142 N, Range 101 W, of the 5th P.M., Billings County, North Dakota

BEGIN SITE 2
Sta 1003+35.95. A point 128.25 feet west and 907.81 feet south of the Northwest Corner of Section 3, Township 141 N, Range 101 W, of the 5th P.M., Billings County, North Dakota

BEGIN SITE 3
Sta 2013+37.88. A point 376.07 feet west and 1569.56 feet south of the Northeast Corner of Section 3, Township 141 N, Range 101 W, of the 5th P.M., Billings County, North Dakota

END SITE 6
Sta 5013+38.00. A point 43.29 feet east and 1337.30 feet north of the Southeast Corner of Section 33, Township 144 N, Range 98 W, of the 5th P.M., Billings County, North Dakota

BEGIN SITE 6
Sta 5009+50.31. A point 30.75 feet east and 949.82 feet north of the Southeast Corner of Section 33, Township 144 N, Range 98 W, of the 5th P.M., Billings County, North Dakota

END SITE 2
Sta 1007+59.62. A point 165.58 feet east and 602.61 feet south of the Northwest Corner of Section 3, Township 141 N, Range 101 W, of the 5th P.M., Billings County, North Dakota

R-101-W
Str 04-109-19.0
Str 04-108-18.0
Str 04-110-19.0
Str 04-126-17.0
Str 04-127-21.0
Str 04-127-06.0

R-99-W

R-98-W


T-144-N

T-142-N

T-141-N

Belfield
8 miles

END SITE 3
Sta 2017+24.07. A point 241.94 feet west and 1931.70 feet south of the Northeast Corner of Section 3, Township 141 N, Range 101 W, of the 5th P.M., Billings County, North Dakota



BEGIN SITE 7
Sta 6008+35.12. A point approximately 3413 feet east and 876 feet north of the Southwest Corner of Section 32, Township 137 N, Range 101 W, of the 5th P.M., Billings County, North Dakota

PROJECT NO.

ND

HEC-0004(202)

23759

1

1

PCN

SECTION

NO.

SHEET

NO.

HEC-0004(202)

MULTIPLE LOCATIONS

Guardrail Embankment, W-Beam Guardrail, Bridge Rail Retrofit, & Incidents

GOVERNING SPECIFICATIONS

Date Published and Adopted
by the North Dakota
Department of Transportation

Standard Specifications

7/1/2025

Supplemental Specifications

NONE

PROJECT NUMBER \ DESCRIPTION	NET MILES	GROSS MILES
Site 1 (04-108-18.0)	0.079	0.079
Site 2 (04-109-19.0)	0.080	0.080
Site 3 (04-110-19.0)	0.073	0.073
Site 4 (04-127-21.0)	0.070	0.070
Site 5 (04-126-17.0)	0.071	0.071
Site 6 (04-127-06.0)	0.073	0.073
Site 7 (04-110-48.0)	0.082	0.082
Totals	0.528	0.528


This project consists of approximately 0.527 miles of guardrail embankment and guardrail installation at existing bridges in multiple locations located in Billings County, North Dakota.

BEGIN SITE 5
Sta 4036+12.87. A point 1672.26 feet west and 59.85 feet north of the Northeast Corner of Section 32, Township 142 N, Range 98 W, of the 5th P.M., Billings County, North Dakota

END SITE 5
Sta 4039+89.33. A point 1296.03 feet west and 46.39 feet north of the Northeast Corner of Section 32, Township 142 N, Range 98 W, of the 5th P.M., Billings County, North Dakota

END SITE 4
Sta 3027+52.03. A point 3.72 feet west and 117.48 feet north of the Northwest Corner of Section 15, Township 141 N, Range 98 W, of the 5th P.M., Billings County, North Dakota

BEGIN SITE 4
Sta 3023+79.84. A point 8.03 feet west and 254.52 feet south of the Northwest Corner of Section 15, Township 141 N, Range 98 W, of the 5th P.M., Billings County, North Dakota



U.S.D.A. FOREST SERVICE DAKOTA PRAIRIE GRASSLANDS

CURTIS GRUDNIEWSKI

Approved By _____
Grasslands Engineer Date _____Digitally signed by CURTIS
GRUDNIEWSKI
Date: 2025.10.29 11:24:43 -06'00'

677 27TH AVENUE EAST
DICKINSON, ND 58601
(701) 483-1284, FAX (855) 288-8055
© KLJ 2025

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	HEC-0004(202)	2	1

TABLE OF CONTENTS

<u>SECTION NO.</u>	<u>SHEET NO.</u>	<u>DESCRIPTION</u>
1	1	Title Sheet
2	1	Table of Contents, List of Special Provisions, & List of Standard Drawings
6	1-2	Plan Notes
6	3	Environmental Notes
8	1	Estimate of Quantities
10	1	Basis of Estimate
20	1-3	Details
30	1	Typical Sections
40	1-5	Removals
75	1-2	Wetland, Mitigation and Environmental
76	1-7	Temporary Sediment and Erosion Control
77	1-7	Permanent Sediment and Erosion Control
80	1-3	Fencing Layouts
81	1-2	Survey Coordinate and Curve Data
100	1-5	Work Zone Traffic Control
130	1-8	Guardrail
170	1-3	Bridges
200	1-3	Cross Sections – Site 1
200	4-6	Cross Sections – Site 3
200	7-11	Cross Sections – Site 6

LIST OF STANDARD DRAWINGS

<u>STANDARD NO.</u>	<u>DESCRIPTION</u>
D-101-1, 2, 3 & 4	NDDOT Abbreviations
D-101-10	NDDOT Utility Company and Organization Abbreviations
D-101-20 & 21	Line Styles
D-101-30, 31, 32 & 33	Symbols
D-101-40	Cross Section Legend
D-261-1	Erosion Control – Fiber Roll Placement Details
D-704-7	Breakaway Systems for Construction Zone Signs – Perforated Tube
D-704-8	Breakaway Systems for Construction Zone Signs – U-Channel Post
D-704-9	Construction Sign Details – Terminal and Guide Signs
D-704-10	Construction Sign Details – Regulatory Signs
D-704-11	Construction Sign Details – Warning Signs
D-704-13	Barricade and Channelizing Device Details
D-704-14	Construction Sign Punching and Mounting Details
D-704-19	Road Closure and Lane Closure on a Two Way Road Layouts
D-704-22	Construction Truck and Temporary Detour Layouts
D-704-50	Portable Sign Support Assembly
D-714-4	Round Corrugated Steel Pipe Culverts and End Sections
D-764-1	W-Beam Guardrail General Details
D-764-5	Sequential Kinking Terminal
D-764-6	Flared Energy Absorbing Terminal
D-764-10	Thrie Beam Transition to Double Box Beam Retrofit
D-764-13	W-Beam Guardrail with Approaches near Bridge for Low Volume Low Speed Roadways
D-764-14	Special W-Beam Guardrail Anchor
D-764-22	Typical Grading at Bridge Ends with W-Beam Guardrail
D-764-38	MGS Flared Energy Absorbing Terminal – Wood Post
D-764-40	MGS W-Beam Guardrail General Details
D-764-48	Typical Grading at Bridge Ends with MGS W-Beam Guardrail
D-764-51	MASH Sequential Kinking Terminal – Wood Post

LIST OF SPECIAL PROVISIONS

<u>SP #</u>	<u>DESCRIPTION</u>
PSP 48(25)	Permits and Environmental Considerations
SSP 1	Temporary Erosion and Sediment Best Management Practices
SSP 3	Local Agency Contracts



PLAN NOTES

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	HEC-0004(202)	6	1

100-P01 EXISTING SIGNS: Billings County will remove the existing signs as needed after the Contractor has installed the work zone traffic control. Billings County will reset the existing signs after the Contractor has constructed the project. The contact for Billings County is Pat Redmond at (701) 690-6827.

105-P01 UTILITIES: The vertical and horizontal utility locations shown in the plans are approximate. Plan locations should not be interpreted as exact for bidding or construction purposes.

105-P02 UTILITIES: No utility relocations or adjustments are planned. All utilities on the project need to be protected and remain in existing location.

202-P01 CLEARING & GRUBBING / REMOVAL OF TREES: Cut down trees that are 3 inches or larger in diameter measured at a point 4.5 feet above the ground after October 31st and before April 1st. Cut trees may be laid on the ground and removed at a later date. Trees to be cut down during this time period are shown in Section 40.

203-010 SHRINKAGE: 25 percent additional volume is included for shrinkage in earth embankment.

203-385 AVERAGE HAUL: No average haul has been computed for this project.

203-P01 GUARDRAIL EMBANKMENT: The cost of labor, equipment, and materials to perform the following work will be included in the price bid for "GUARDRAIL EMBANKMENT"

1. Construct inslopes for Guardrail Embankment according to Standard Drawing D-764-22 or D-764-48 and Section 203.04 G of the Standard Specifications utilizing Compaction Control, Type B. The total embankment material needed to construct the guardrail embankments as shown in the plans is shown on the summary table located in Section 10 Sheet 1.
2. Borrow material for the project will be obtained from borrow sites located by the Contractor and approved by the Engineer. Include all royalties, utility and fencing adjustments, environmental and cultural clearances, site restoration, and any other costs associated with obtaining, transporting, and placing borrow material in the unit price bid for "GUARDRAIL EMBANKMENT". The total borrow material needed to construct the guardrail embankments as shown in the plans is shown on the summary table located in Section 10 Sheet 1.
3. Include all costs associated with stripping, stockpiling, stabilizing, transporting, and placing topsoil material in the unit price bid for "GUARDRAIL EMBANKMENT". The total topsoil quantity to construct the guardrail embankments as shown in the plans is shown on the summary table located in Section 10 Sheet 1.
4. Include all grading costs associated with constructing approaches in the unit price bid for "GUARDRAIL EMBANKMENT".
5. Include all costs associated with placing seed and straw mulch in all disturbed areas in the unit price bid for "GUARDRAIL EMBANKMENT".

210-P01 FOUNDATION FILL: Delete Section 210.04 B.3 and insert the following:

3. Foundation Fill.
Place foundation fill in layers not exceeding 6 inches to the required elevation. Thoroughly compact each layer with mechanical tamping equipment. Use water as required to achieve satisfactory compaction and stability.

210-P02 PIPE EXCAVATION: The amount of excavation under the centerline pipe may vary due to the depth of poor foundation soil and will be determined by the Engineer. The actual excavation, regardless of depth, will not be measured for payment but will be included in the unit price bid for "FOUNDATION FILL". Excavate according to the limits for width and length as shown on Section 20 Sheet 2. Use Foundation Fill material to backfill the excavation areas. Payment for Foundation Fill will be according to the limits for width and length as shown on Section 20 Sheet 2 and depth measured in the field.

216-P01 WATER: Include all costs associated with the application of water for compaction of subgrade and foundation fill, and for use as a dust palliative, as required, in the cost for other bid items.


251-P01 SEEDING WEST OF HWY 85: Seeding Class III shall consist of the following #37-28A seed mixture Scenario #13 for Sites 1,2,3 & 7:

Species	Preferred Cultivar, Ecotype, or Germplasm	Common Name	Drilled PLS lb/acre
Cool Season Grasses:			
<i>Elymus canadensis</i>	Mandan	Canada wildrye	2.8
<i>Nassella viridula</i>	Lodorm	Green needlegrass	2.4
<i>Pascopyrum smithii</i>	Rodan	Western wheatgrass	4.9
Warm Season Grasses:			
<i>Bouteloua gracilis</i>	Bad River	Blue grama	0.3
<i>Calamovilfa longifolia</i>	Goshen	Prairie sandreed	0.8
<i>Schizachyrium scoparium</i>	Badlands	Little bluestem	0.8
Alternate Warm Season (for one of the above species)			
<i>Bouteloua curtipendula</i>	Pierre	Sideoats grama	1.2
Forbs			
<i>Dalea purpurea</i> OR <i>Dalea candida</i>	Local	Purple prairieclover	0.25
<i>Helianthus pauciflorus</i> OR <i>Solidago rigida</i>	Antelope	White prairieclover	0.3
<i>Echinacea angustifolia</i> OR <i>Ratibida columnifera</i>	Bismarck	Stiff sunflower	0.7
<i>Echinacea angustifolia</i> OR <i>Ratibida columnifera</i>	Local	Stiff goldenrod	0.1
<i>Echinacea angustifolia</i> OR <i>Ratibida columnifera</i>	Bismarck	Purple coneflower	0.5
<i>Ratibida columnifera</i>	Local	Praire coneflower	0.1
Companion			
		Oats	10
Totals		Forbs Alternate Forbs	23.4 (22.5)

Cultivars listed in the second column are preferred, but local seed collections grown for harvest are acceptable if performance and origin are certified or documented. All seed sources should be derived from local collections and grown in a general area extending 300 miles north and 200 miles south of the area to be reclaimed, within similar elevation and precipitation zones as western North Dakota, i.e., from Jamestown on the east to Billings, MT on the west.

For broadcast seeding, multiply pounds of each species seeded by 1.5. The seed bed should be thoroughly worked and firm.

The seed mix may need to be adjusted due to site characteristics and/or lack of available seed for some species. In the latter case, adjust the species seeding rates by the formulas below table to obtain approximately 50 seed per square foot and/or 12-16 lbs. of PLS per acre for drilled seed and 18-24 lbs. per acre for broadcast seeding.



HEC-0004(202)		
Multiple Locations		
	Plan Notes	
	Billings County, ND	
DRWN. BY AK	CHKD. BY SPK	PROJECT NO. 2103-01811

PLAN NOTES

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	HEC-0004(202)	6	2

Seeding depth should be 1/4 inch or less for drilled seed.

Note: The following steps/documents are required as per Conditions of Approval #28 B, Certification & Reporting:

1. Report of Seeding (#37-28B)
2. Certification of Seed Mixture from Seed Company, and seed tags from bags or copy of seed tags for all planted material on forest service property must be submitted to the Medora Ranger District. (The Engineer will submit these upon receiving them from the Contractor.)

Call the Medora Ranger District (701) 227-7800 if there are any questions.

251-P02 SEEDING EAST OF HWY 85: Seeding Class III shall consist of the following mixture for Sites 4, 5, & 6:

Species	Lbs. of PLS/Acre
Alfalfa	9
Western Wheatgrass	4
Fairway Crested Wheatgrass	5
Slender Wheatgrass	2
Oats	10
Total	30

261-P01 FIBER ROLLS: Fiber rolls have been provided for temporary and permanent erosion control. The perimeter temporary erosion control has been provided for placement prior to disturbing the topsoil or as indicated by the Engineer.

Preserve the temporary erosion control throughout the duration of the project. If the erosion is damaged due to negligence, repair at the Contractor's expense.

Place permanent fiber rolls after seeding Class III. Locations are shown in Section 77.

An additional 400 LF of Fiber Rolls 12IN have been provided for locations to be determined by the Engineer. Include all costs for labor, equipment, and materials necessary to complete this work and all costs to relocate fiber rolls as needed for construction related activities in the unit price bid for "FIBER ROLLS 12IN".

302-P01 COUNTY INSTALLED SURFACING: County forces will haul, lay, & compact the 6 inches of aggregate or scoria surfacing, as noted on the Typical Sections. They will also reshape the existing surfacing as needed. Coordinate grading operation with Billings County so that the surfacing can be placed within 48 hours after the finished grading is complete at each site. The County is available to haul, lay, and compact the surfacing from Monday through Thursday only.

The Contractor is responsible for all roadway maintenance from the project start through final acceptance. The only exception is if the County does not begin delivery of the surfacing within the 48 hours notice period, not including Friday through Sunday. The contact is Pat Redmond at (701) 690-6827.

Allow the County to complete surfacing installation prior to beginning guardrail installation.

704-P01 TRAFFIC CONTROL DEVICES LIST: The traffic control devices list has been developed using traffic control signing layouts (shown in Section 100 of the plans) and Standard Drawings listed below:

- Standard D-704-19, Type E: For road closure to all but local traffic. Detour is not provided.
- Standard D-704-22, Type K: For trucks hauling material.

704-P02 TRAFFIC CONTROL GENERAL: Leave roadway open to local traffic during construction.

714-P01 FLARED END SECTIONS: Level and compact the material under the flared end sections to grade prior to setting all flared end sections to ensure no voids exist beneath.

714-P02 DEFLECTION TESTING: Delete Section 714.04 A.8 in its entirely and insert the following:

8. Deflection Testing.

The Engineer will visually inspect all metal pipe used on the project for deflection a minimum of 30 days after the pipe is installed. If the Engineer sees any deflection, the Engineer will require the Contractor to pass a nine point mandrel or approved object through the pipe to check for deflection. Use a mandrel with a diameter not less than 95 percent of the inside diameter of the pipe. If the mandrel cannot be passed through the pipe, replace the pipe.

Perform the deflection test under the observation of the Engineer.

714-P03 COMPACTION CONTROL FOR AGGREGATE: Delete Section 714.04 A.10 in its entirely and insert the following:

10. Compaction Control for Aggregate.


Place foundation fill in layers not exceeding 6 inches to the required elevation. Thoroughly compact each layer with mechanical tamping equipment. Use water as required to achieve satisfactory compaction and stability.

714-P04 COMPACTION CONTROL FOR NON-AGGREGATE MATERIAL: Delete Section 714.04 A.11 in its entirely and insert the following:

11. Compaction Control for Non-Aggregate Material.

Compact non-aggregate material to the compaction requirements in Section 203.04 G.3, "Compaction Control, Type B." Use a maximum lift thickness of 6 inches.

Compact material for approach pipes according to the manufacturer's recommendations.



HEC-0004(202)	
Multiple Locations	
	Plan Notes
Billings County, ND	
DRWN. BY AK	CHKD. BY SPK
PROJECT NO. 2103-01811	

ENVIRONMENTAL NOTES

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	HEC-0004(202)	6	3

ENVIRONMENTAL NOTES (EN): Billings County, the North Dakota Department of Transportation, and the Federal Highway Administration have made environmental commitments to secure approval of this project. The following environmental notes are requirements to comply with these commitments:

EN-1 AQUATIC NUISANCE SPECIES (ANS): Equipment that was last used outside of North Dakota or within a Class I infested waterbody (identified on the North Dakota Game and Fish Department (NDGFD) website) requires an inspection by NDGFD. Notify the NDGFD at least 10 business days prior to pumps, watercraft, or any equipment entering a public water to allow the NDGFD sufficient time to inspect any and all such equipment for ANS. Contact the NDGFD ANS Coordinator, Ben Holen by e-mail - bholen@nd.gov for equipment inspections. Supply one of the following to the engineer as proof of compliance prior to work taking place in the water: (1) the NDGFD inspection report, (2) documented NDGFD correspondence (email or signed letter).

EN-2 THREATENED AND ENDANGERED SPECIES: The project is located near/within suitable habitat for the species listed in the following table:

SPECIES	HABITAT	PRESENCE
Whooping Crane	Cropland/Wetland Associations	Spring: March 15 - May 15* Fall: September 10 – November 15
Northern Long-Eared Bat	Forested/Wooded Areas/Bridges/Box Culverts/Caves/Mines	Active Season: April 15 - October 31* Inactive Season: Nov 1 – April 14*

*Time frames can differ slightly, depending on the year

If any of the above threatened and endangered species are identified within 1 mile of the project, the Contractor will notify the Engineer immediately and cease construction activities in the vicinity until an avoidance area is established. The Engineer will establish an avoidance area that is at least a 0.5 mile and immediately coordinate with the USFWS (701-355-8513), FHWA (701-221-9464), and NDDOT Environmental and Transportation Services (701-328-2592). The Contractor will not resume work within the avoidance area until the Engineer has confirmed with the agencies that work may proceed (either the species have left the area, or approved avoidance/minimization measures have been implemented).

Conduct tree removal activities outside of the active season for the northern long-eared bat (November 1 – April 14).

Ensure Tree removal is limited to that specified in the project plans. Install bright colored flagging/fencing prior to any tree clearing to ensure contractors stay within clearing limits.

EN-3 TEMPORARY WETLAND IMPACT: Temporary impact areas within wetlands and or other waters are incorporated into the plans for this project. Remove temporary fill placed and sedimentation in wetlands or other waters. Restore these wetlands to preconstruction contours.

EN-4 WETLAND MITIGATION: Wetland mitigation is required for unavoidable permanent wetland impacts. The wetland mitigation plan is incorporated into the plans for this project. After completion of the mitigation area, the Engineer will complete the Onsite Mitigation Certification Form SFN 61042. Any sedimentation occurring within the mitigation area will be removed.

PERMITS REQUIRED:


United States Army Corp of Engineers – Section 404 Permit
Status: Has been obtained for the project.

North Dakota Department of Environmental Quality – NDPDES Construction Stormwater Permit
Status: To be obtained by the Contractor prior to construction. Owner is to be listed as Billings County on the permit.

EN-5 NOXIOUS WEED CONTROL ON FOREST SERVICE LANDS: To prevent the potential spread of noxious weeds, the Contractor is required to furnish weed-free equipment. The Contractor's equipment shall be cleaned to remove all dirt and plant parts and material that may carry noxious weed seeds into the construction area on FS Lands. All subsequent move-ins shall be treated the same as the initial move-in. Prior to move-in the Contractor shall make equipment available to Forest Service inspection at an agreed location.

EN-6 FIRE CONTROL ON FOREST SERVICE LANDS:

- a) Contractor's Responsibility for Contractor-Caused Fires – The Contractor, whether or not directed by the Forest Service, shall immediately extinguish, without expense to the Government, all fires on or in the vicinity of the project which are caused by Contractor's employees, whether set directly or indirectly as a result of Contractor operations. The Contractor may be held liable for all damages and costs of additional labor, subsistence, equipment, supplies, and transportation resulting from fires set or caused by the Contractor's employees or resulting from contract operations.
- b) Fire Plan – At all times during fire season period, as specified by State law, the Contractor shall comply with each of the following provisions to the extent applicable to his operation under the contract.
 - i. Fire Tools – The Contractor will provide for each employee in the contract area at least one approved hand tool of a type appropriate in the contract area, such as shovel, pulaski, or ax.
 - ii. Fire Extinguishers – Each unit of powered equipment used in connection with this contract, including automobiles, trucks, tractors, etc., shall be equipped with a fire extinguisher as follows: One - fire extinguisher, dry chemical type of not less than 2-1/2-pound capacity with 4 BC or higher rating.
 - iii. Smoking – Smoking shall not be permitted within the contract area except on surfaced or dirt roads, at landings, within closed vehicles, in camps, or at other posted places, and shall never be allowed while working or traveling on foot.
 - iv. Storage of Petroleum and Other Highly Flammable Products – Gasoline, oil, grease, or other highly flammable material will be stored either in a separate building used exclusively for such storage, or at a site where all combustible debris and vegetation is cleared away within a radius of 25 feet. Fire extinguishers and/or sand barrels may be required at such locations specified by the Forest Service when unusually hazardous conditions exist.
 - v. Welding – Welding or use of cutting torches will be permitted only in areas that have been cleared or are free of all material capable of carrying fire. Flammable debris and vegetation must be removed from within a minimum of 10 feet radius of all welding and cutting torch operations. A shovel and a 5-gallon standard backpack water container (filled), with hand pump attached, shall be immediately available for use in the event of a fire start.



HEC-0004(202)		
Multiple Locations		
	Environmental Notes	
	Billings County, ND	
DRWN. BY AK	CHKD. BY SPK	PROJECT NO. 2103-01811

ESTIMATE OF QUANTITIES

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	HEC-0004(202)	8	1

Spec	Code	Description	Unit	Total Quantities
103	0100	CONTRACT BOND	LSUM	1
201	0330	CLEARING & GRUBBING	LSUM	1
202	0174	REMOVAL OF PIPE ALL TYPES AND SIZES	LF	28
202	0312	REMOVE EXISTING FENCE	LF	1,183
203	0218	GUARDRAIL EMBANKMENT	EA	28
210	0210	FOUNDATION FILL	CY	6
261	0112	FIBER ROLLS 12IN	LF	2,780
261	0113	REMOVE FIBER ROLLS 12IN	LF	1,390
624	3002	DOUBLE BOX BEAM RAIL RETROFIT - E-RAIL	LF	284.9
702	0100	MOBILIZATION	LSUM	1
704	1000	TRAFFIC CONTROL SIGNS	UNIT	701
704	1052	TYPE III BARRICADE	EA	26
714	5015	PIPE CORR STEEL .064IN 18IN	LF	62
714	5201	PIPE CORR STEEL .079IN 24IN POLYMERIC COATED	LF	4
714	5810	END SECT CORR STEEL .064IN 18IN	EA	2
714	9660	REMOVE & RELAY END SECTION-ALL TYPE & SIZES	EA	1
752	0200	FENCE BARBED WIRE 4 STRAND	LF	1,172
752	2100	VEHICLE GATE	EA	2
752	2995	CORNER ASSEMBLY-WOOD POST	EA	5
752	3995	DOUBLE BRACE ASSEMBLY-WOOD POST	EA	13
764	0131	W-BEAM GUARDRAIL	LF	1,359
764	0145	W-BEAM GUARDRAIL END TERMINAL	EA	27
764	2081	REMOVE END TREATMENT & TRANSITION	EA	4



BASIS OF ESTIMATE

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND		HEC-0004(202)	10	1

Foundation Fill – (Volume +25%)

Pipe Culverts: Depth & Limits as shown in Section 20 Sheet 2

Water


Included with other items if needed

Guardrail Embankment Quantity Summary (For Informational Purposes)								
Location	Embankment (CY)	Excavation (CY)	Borrow (CY)	Topsoil (CY)	Temporary Cover Crop (ACRE)	Seeding Class III East of Hwy 85 (ACRE)	Seeding Class III Scenario 13 (ACRE)	Straw Mulch (ACRE)
Site 1	373	69	304	165	0.26	-	0.26	0.52
Site 2	486	0	486	187	0.30	-	0.30	0.60
Site 3	428	4	424	163	0.24	-	0.24	0.48
Site 4	356	0	356	210	0.26	0.26	-	0.52
Site 5	256	0	256	184	0.24	0.24	-	0.48
Site 6	659	142	525	245	0.40	0.40	-	0.80
Site 7	570	0	570	248	0.34	-	0.34	0.68
Total	3,128	215	2,921	1,402	2.04	0.90	1.14	4.08

Notes:

1. Quantity shown for embankment has been increased by 25% to account for shrinkage.
2. Topsoil depth is estimated at 4 inches.
3. One application of temporary seeding and straw mulch is included for use if needed.
4. Seeding and mulching areas shown are based on the calculated area between the edge of roadway and limits of construction.

Additional seeding and mulching for disturbed areas used to facilitate construction or accommodate the Contractor's method and means will be the responsibility of the Contractor with no additional cost to the project.



HEC-0004(202)

Multiple Locations



Basis of Estimate

Billings County, ND

DRWN. BY AK	CHKD. BY SPK	PROJECT NO. 2103-01811
----------------	-----------------	---------------------------

STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND	HEC-0004(202)	20	1

Curve 10818_3 (Site 1)

P.C. Station = 3+00.00
 P.I. Station = 7+83.44
 P.T. Station = 11+27.16
 Delta = 74° 22' 06" (RT)
 Degree = 8° 59' 27"
 Tangent = 483.44
 Length = 827.16
 Radius = 637.27
 External = 162.62
 Back = S 80° 17' 40.59" E
 Ahead = S 05° 55' 34.68" E
 Chord Bearing = S 43° 06' 37.64" E
 Proposed Full Super = 5.2%

Station	Left Slope	Right Slope
3+50.33	PC + 50.33	5.20 -5.20
10+76.83	PT - 50.33	5.20 -5.20
11+08.39	PT - 18.77	3.57 -3.57
	PT	
11+77.49	PT + 50.33	0.00 -3.57
12+46.59	PT + 119.43	-3.57 -3.57

Curve 11048_3 (Site 7)



P.C. Station = 6003+50.00
 P.I. Station = 6006+42.49
 P.T. Station = 6009+11.82
 Delta = 39° 19' 40" (LT)
 Degree = 7° 00' 00"
 Tangent = 292.49
 Length = 561.82
 Radius = 818.51
 External = 50.69
 Back = N 57° 56' 49.33" E
 Ahead = N 18° 37' 09.33" E
 Chord Bearing = N 38° 16' 59.33" E
 Proposed Full Super = 5.8%

Station	Left Slope	Right Slope
6004+14.45	PC + 64.45	-5.80 5.80
6008+47.37	PT - 64.45	-5.80 5.80
6008+96.94	PT - 14.88	-3.57 3.57
	PT	
6009+76.27	PT + 64.45	-3.57 0.00
6010+55.60	PT + 143.78	-3.57 -3.57

Curve 10818_6 (Site 1)

P.C. Station = 14+91.40
 P.I. Station = 18+30.82
 P.T. Station = 21+09.18
 Delta = 58° 59' 38" (LT)
 Degree = 9° 32' 57"
 Tangent = 339.42
 Length = 617.78
 Radius = 600.00
 External = 89.35
 Back = S 05° 55' 34.68" E
 Ahead = S 64° 55' 12.68" E
 Chord Bearing = S 35° 25' 23.68" E
 Proposed Full Super = 5.2%

Station	Left Slope	Right Slope
13+71.97	PC - 119.43	-3.57 -3.57
14+41.07	PC - 50.33	-3.57 0.00
	PC	
15+10.17	PC + 18.77	-3.57 3.57
15+41.73	PC + 50.33	-5.20 5.20
20+58.85	PT - 50.33	-5.20 5.20



HEC-0004(202)

Multiple Locations

Superelevation Tables


Billings County, ND



DRAWN BY
AK
CHKD BY
SPK
PROJECT NO.
2103-01811

Note: Calculation based on AASHTO Method Five. A design speed of 35 MPH for Site 1, a design speed of 45 MPH for Site 7, and maximum superelevation of 6% were used.

	STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND		HEC-0004(202)	20	2



One-half Pipe Extension

Pay Items



- 1) Pipe*
- 2) Foundation Fill
- 3) Removal of Pipe (If Required)

*Included in Pipe Pay Item

- 1) Pipe
- 2) Trench Excavation
- 3) Pipe Embankment

Bedding CY Per Foot (for centerline CSP)	
Size	CSP
24"	0.70

*2' has been provided for use if needed as determined by the Engineer in the field.



HEC-0004(202)


Multiple Locations

	Pipe Extension Bedding & Backfill Details	
	Billings County, ND	DRWN. BY AK


CHKD. BY
SPK

PROJECT NO.
2103-01811


	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	HEC-0004(202)	20	3




VEHICLE GATE



DOUBLE BRACE ASSEMBLY




LINE POST DETAIL




BREAK-AWAY FENCE FOR WIDE DEPRESSIONS SUBJECT TO FLOODING

POST SIZES								
	TREATED WOOD		TREATED RAILROAD TIE		STEEL			
USE OF POST	Post dia.	Post length	Post dimensions	Post length	Post dia.	Post length	Post wt. Lbs/Ft	Anchor wt. Lbs.
Line Post	4"	6'-6"				6'-6"	1.33	0.67
Corner Post			7"x9"	8'				
Brace Post			7"x9"	8'				
Gate Post			7"x9"	8'				
Horizontal Brace					2 ⁷ / ₈ "	6'-6"	As approved by Engineer	




FASTENING TO POSTS




HEC 0004(202)

M. W. L. L. M. 1




STATE	PROJECT NO.	SECTION NO.	SHEET NO.
		ND	HEC-0004(202)

150' Existing R/W or as Shown on Plans







EXISTING TYPICAL SECTION



PROPOSED TYPICAL SECTION

Notes:
*4:1 Max Slope thru End Terminal then transition to existing to match at Bridge Abutment
**See Section 20 Sheet 1 for Superelevations
Cross sections have been provided for locations with a ditch section



HEC-0004(202)

Multiple Locations





Existing & Proposed
Typical Sections
Billings County, ND

DRWN. BY AK CHKD. BY SPK PROJECT NO.
2103-01811

© KLJ 2025

	STATE	PROJECT NO.	SECTION NO.	HEET NO.
	ND	HEC-0004(202)	40	1





202 0312 REMOVE EXISTING FENCE

Sta 3023+80 to 3025+53 R
Sta 3025+05 to 3025+52 L
Sta 3026+20 to 3026+27 R
Sta 3026+28 to 3026+42 L

180	LF
70	LF
94	LF
57	LF
Total =	401 LF

LEGEND

- X — Remove Existing Fence
- ● — Remove Existing Guardrail
-  Tree Removal

Structure # 04-127-210


Structure # 04-127-210


Removals

KLJ



Removals

CHKD. BY	PROJECT NO.
SPK	2103-01811





STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND	HEC-0004(202)	40	5



764 2081 REMOVE END TREATMENT & TRANSITION

Sta 6009+82 to 6010+19 Rt	1 EA
Sta 6009+86 to 6010+23 Lt	1 EA
Sta 6010+94 to 6011+31 Rt	1 EA
Sta 6010+98 to 6011+35 Lt	1 EA
Total =	4 EA

LEGEND

- X— Remove Existing Fence
- Remove Existing Guardrail
- ☒ Tree Removal

HEC-0004(202)

Structure # 04-110-48,0

Removals

Site 7
 Billings County, ND



DRAWN BY AK
 CHECKED BY SPK
 PROJECT NO. 2103-01811

	STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND		HEC-0004(202)	75	1


Wetland Number	Location	Wetland Type	Wetland Feature	USACE Jurisdictional Wetlands	Wetland Impact				Wetland Mitigation						
					Wetland Impacts Acre(s)			USFWS Easement Impacts Acre(s)		Mitigation Proposed			Onsite Mitigation Method		
					Temp.	Perm. (Fill/Drain)	Perm. (Cut)	Temp.	Perm.	EO 11990	USACE	USFWS	Mitigation Location; Ratio	Ditch Shift Acre(s)	Onsite Acre(s)
1a	Sec 34, T-144-N, R-98-W	Riverine	Natural	Y	0.045	0.012				Y	N		Ditch Shift 1: 1:1	0.012	
2a	Sec 32, T-142-N, R-101-W	Riverine	Natural	Y											
2b	Sec 32, T-142-N, R-101-W	Riverine	Natural	Y											
3a	Sec 3, T-141-N, R-101-W	Riverine	Natural	Y											
3b	Sec 3, T-141-N, R-101-W	Riverine	Natural	Y											
4a	Sec 2, T-141-N, R-101-W	Riverine	Natural	Y											
4b	Sec 2, T-141-N, R-101-W	Riverine	Natural	Y											
5a	Sec 32, T-142-N, R-98-W	Riverine	Natural	Y											
5b	Sec 32, T-142-N, R-98-W	Riverine	Natural	Y											
6a	Sec 9, T-141-N, R-98-W	Ditch	Created	Y											
6b	Sec 15, T-141-N, R-98-W	Riverine	Natural	Y											
6c	Sec 15, T-141-N, R-98-W	Riverine	Natural	Y											
7a	Sec 32, T-137-N, R-101-W	Riverine	Natural	Y											
7b	Sec 32, T-137-N, R-101-W	Riverine	Natural	Y											
					Totals	0.045	0.012	-	-	-			0.012	-	

Number	Location	Type	Feature	USACE Jurisdictional ¹	Impacts to Other Waters				Other Water Mitigation					
					Acres			Linear Feet			Mitigation Proposed			
					Temp.	Perm. (Fill/Drain)	Perm. (Cut)	Temp.	Perm. (Fill/Drain)	Perm. (Cut)	EO 11990	USACE	USFWS	
OW 1b	Sec 33, T-144-N, R-98-W	River	Natural	Y										
OW 2c	Sec 32, T-142-N, R-101-W	Creek	Natural	Y										
OW 3c	Sec 3, T-141-N, R-101-W	Creek	Natural	Y										
OW 4c	Sec 2, T-141-N, R-101-W	Creek	Natural	Y										
OW 5c	Sec 32, T-142-N, R-98-W	Creek	Natural	Y										
OW 6d	Sec 9, T-141-N, R-98-W	River	Natural	Y										
OW 7c	Sec 32, T-137-N, R-101-W	Creek	Natural	Y										
					Totals	-	-	-	-	-				

¹ A wetland Jurisdictional Determination was issued by the USACE on 05/24/2023; NWO-1980-02417-BIS for Wetland 1a and OW 1b.
A wetland Jurisdictional Determination was issued by the USACE on 05/09/2023; NWO-2023-00548-BIS for Wetlands 2a and 2b, and OW 2c.
A wetland Jurisdictional Determination was issued by the USACE on 05/09/2023; NWO-2023-00549-BIS for Wetlands 3a and 3b, and OW 3c.
A wetland Jurisdictional Determination was issued by the USACE on 05/09/2023; NWO-2023-00551-BIS for Wetlands 4a and 4b, and OW 4c.
A wetland Jurisdictional Determination was issued by the USACE on 05/09/2023; NWO-2023-00552-BIS for Wetlands 5a and 5b, and OW 5c.
A wetland Jurisdictional Determination was issued by the USACE on 06/09/2023; NWO-2015-02357-BIS for Wetlands 6a, 6b, 6c and OW 6d.
A wetland Jurisdictional Determination was issued by the USACE on 05/10/2023; NWO-1997-61421-BIS for Wetlands 7a and 7b, and OW 7c.

Mitigation Summary Table						
	Location	Ditch Shift Acre(s)	Onsite Acre(s)	11990 Bank Acre(s)	USACE/11990 Bank Acre(s)	USFWS Bank Acre(s)
USACE Only				X	X	X
EO 11990 Only	Onsite	0.012		X	X	X
USACE/11990				X	X	X
USFWS				X	X	X
	Total	0.012	-	-	-	-

Impact Summary Table			
Permanent Impact Summary		Temporary Impacts and additional information	
Wetland Type	Total Acre(s)	Water Type	Total Acre(s)
Natural/JD (Fill/Drain)	0.012	Temporary Wetland JD	0.045
Natural/Non-JD (Fill/Drain)	0.000	Non-JD Wetland Temporary	0.000
Artificial/JD (Fill/Drain)	0.000		
Artificial/Non-JD (Fill/Drain)	0.000	Permanent OW	0.000
Total	0.012	Temporary OW	0.000
JD Natural (Cut)	-	Permanent OW-d	-
JD Artificial (Cut)	-	Temporary OW-d	-
Non-JD Natural (Cut)	-		
Non-JD Artificial (Cut)	-		
Total	-		




HEC-0004(202)

Multiple Locations



Wetlands, Mitigation and Environmental Wetland Impact Table Billings County, ND

DRAWN BY AK CHECKED BY DB PROJECT NO. 2103-01811



	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
			ND	HEC-0004(202)

SE1/4, Sec 32
T-142-N, R-101-W
National Forest System Lands

Curve 10818-3
PI = 7+83.44
Delta = 74° 22' 05.91" (RT)
Da = 8° 59' 26.94"
R = 637.27
T = 483.44
L = 827.16

OW 2c
(Do not disturb)

Delineated Wetland 2a
(Do not disturb)

Delineated Wetland 2b
(Do not disturb)

E

E

E

E

BM 11

0.10 Acres

PC 14+61.07

110'

16

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1


1

1

1


STATE	PROJECT NO.	SECTION NO.	HEET NO.
	ND	HEC-0004(202)	76

NE1/4, Sec 4
T-141-N, R-101-W
Darryl Lance & Stephanie M Thomas



261 0112 FIBER ROLLS 12IN
Sta 1003+38 to 1003+66 Rt 30 LF
Sta 1004+57 to 1004+93 Lt 40 LF
Sta 1004+79 to 1004+83 Rt 20 LF
Sta 1006+03 to 1006+10 Rt 20 LF
Sta 1006+03 to 1006+06 Lt 20 LF
Total = 130 LF

261 0113 REMOVE FIBER ROLLS 12IN
Sta 1003+38 to 1003+66 Rt 30 LF
Sta 1004+57 to 1004+93 Lt 40 LF
Sta 1004+79 to 1004+83 Rt 20 LF
Sta 1006+03 to 1006+10 Rt 20 LF
Sta 1006+03 to 1006+06 Lt 20 LF
Total = 130 LF



HEC-0004(202)

Structure # 04-10919-0


LEGEND	
	Fiber Rolls 12IN
	Temporary Cover Crop & Straw Mulch

Temporary Sediment and
Erosion Control
Site 2
Billings County, ND




DRAWN BY AK CHECKED BY SPK PROJECT NO. 2103-01811

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
		ND	HEC-0004(202)



261	0112	FIBER ROLLS 12IN		
		Sta 2014+84 to 2014+87 Rt	20	LF
		Sta 2014+95 to 2014+97 Lt	20	LF
		Sta 2015+56 to 2015+59 Rt	20	LF
		Sta 2015+67 to 2015+71 Lt	20	LF
		Total =	80	LF

261	0113	REMOVE FIBER ROLLS 12IN		
		Sta 2014+84 to 2014+87 Rt	20	LF
		Sta 2014+95 to 2014+97 Lt	20	LF
		Sta 2015+56 to 2015+59 Rt	20	LF
		Sta 2015+67 to 2015+71 Lt	20	LF
		Total =	80	LF




HEC-0004(202)


St. Louis 63110-1000

LEGEND

Temporary Sediment and
Erosion Control
Site 3
Billings County, ND


RWN. BY	CHKD. BY	PROJECT NO.
AK	SPK	2103-01811





STATE	PROJECT NO.	SECTION	SHEET
		NO.	NO.
ND	HEC-0004(202)	76	6


SE1/4, Sec 33
T-144-N, R-98-W
William Romanyshyn



SW1/4, Sec 34
T-144-N, R-98-W
William Romanyshyn

261	0112	FIBER ROLLS 12IN	
		Sta 5010+76 to 5010+88 Rt	30 LF
		Sta 5010+96 to 5010+97 Lt	40 LF
		Sta 5011+55 to 5011+57 Rt	20 LF
		Sta 5011+63 to 5011+68 Lt	20 LF
		Total =	110 LF

261	0113	REMOVE FIBER ROLLS 12IN	
		Sta 5010+76 to 5010+88 Rt	30 LF
		Sta 5010+96 to 5010+97 Lt	40 LF
		Sta 5011+55 to 5011+57 Rt	20 LF
		Sta 5011+63 to 5011+68 Lt	20 LF
		Total =	110 LF




HFC-0004(202)

Structure # 04-127-06-0

LEGEND	
	Fiber Rolls 12IN
	Temporary Cover Crop & Straw Mulch


Temporary Sediment and
Erosion Control
Site 6
Billings County, ND

KLJ



261	0112	FIBER ROLLS 12IN	
		Sta 6009+05 to 6009+45 Rt	40 LF
		Sta 6010+31 to 6010+32 Rt	20 LF
		Sta 6010+31 to 6010+32 Lt	20 LF
		Sta 6010+85 to 6010+86 Lt	20 LF
		Sta 6010+86 Rt	20 LF
		Total =	120 LF

261	0113	REMOVE FIBER ROLLS 12IN	
		Sta 6009+05 to 6009+45 Rt	40 LF
		Sta 6010+31 to 6010+32 Rt	20 LF
		Sta 6010+31 to 6010+32 Lt	20 LF
		Sta 6010+85 to 6010+86 Lt	20 LF
		Sta 6010+86 Rt	20 LF
		Total =	120 LF



HEC-0004(202)

Structure # 04-110-48-0

LEGEND	
	Fiber Rolls 12IN
	Temporary Cover Crop & Straw Mulch

Temporary Sediment and
Erosion Control
Site 7
Billings County, ND

KLJ

	STATE	PROJECT NO.	SECTION NO.	HEET NO.
	ND	HEC-0004(202)	77	1

SE1/4, Sec 32
T-142-N, R-101-W
National Forest System Lands

Curve 10818-3
PI = 7+83.44
Delta = 74° 22' 05.91" (RT)
Da = 8° 59' 26.94"
R = 637.27
T = 483.44
L = 827.16

OW 2c

(Do not disturb)

Delineated Wetland 2a

(Do not disturb)

Delineated Wetland 2b

(Do not disturb)

E

E

E

E

E

E

BM 11

0.10 Acres

FC 14+61.07

110'

16

0.05 Acres

Fiber Rolls 12IN - 80 LF

150'

11

12

13

14

15

Franks Creek Road

150'

11

12

13

14

15

16


125'

11+27.16

PT

STATE	PROJECT NO.	SECTION NO.	HEET NO.
	ND	HEC-0004(202)	77

NE1/4, Sec 4
T-141-N, R-101-W
Darryl Lance & Stephanie M Thomas



261 0112 FIBER ROLLS 12IN

Sta 1003+44 to 1003+80 Rt	40 LF
Sta 1004+29 to 1004+81 Lt	70 LF
Sta 1004+64 to 1004+83 Rt	20 LF
Sta 1006+03 to 1006+10 Rt	20 LF
Sta 1006+03 to 1006+06 Lt	20 LF
Total =	170 LF


HEC-0004(202)

Structure # 04-109-19-0


LEGEND	
	Fiber Rolls 12IN
	Seeding Class II & Straw Mulch

Permanent Sediment and
Erosion Control
Site 2
Billings County, ND


DRAWN BY AK CHECKED BY SPK PROJECT NO. 2103-01811



STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND	HEC-0004(202)	77	3



261 0112 FIBER ROLLS 12IN
 Sta 2014+69 to 2014+87 Rt 30 LF
 Sta 2014+84 to 2014+95 Lt 20 LF
 Sta 2015+59 to 2015+64 Rt 20 LF
 Sta 2015+67 to 2015+77 Lt 20 LF
 Sta 2016+96 to 2017+03 Lt 20 LF
 Total = 110 LF



HEC-0004(202)


Structure # 04-110-19-0

LEGEND	
	Fiber Rolls 12IN
	Seeding Class II & Straw Mulch



Permanent Sediment and
Erosion Control
Site 3
Billings County, ND

DRWN. BY AK CHKD. BY SPK PROJECT NO.
2103-01811



261 0112 FIBER ROLLS 12IN

Sta 3024+02 to 3025+00 Rt
Sta 3025+40 to 3025+55 Lt
Sta 3025+40 to 3025+55 Rt
Sta 3026+25 to 3026+44 Lt
Sta 3026+25 to 3026+41 Rt

100	LF
20	LF
20	LF
70	LF
20	LF
Total =	230 LF

LEGEND

— Fiber Rolls 12IN


— Seeding Class II & Straw Mulch

HEC-0004(202)

Structure # 04-127-21 0

Permanent Sediment and
Erosion Control
Site 4
Billings County, ND

Y	CHK'D. BY	PROJECT NO.
AK	SPK	2103-01811




261 0112 FIBER ROLLS 12IN

Sta 4036+41 Rt	20	LF
Sta 4037+45 to 4037+63 Lt	20	LF
Sta 4037+64 to 4037+81 Rt	20	LF
Sta 4038+24 to 4038+42 Lt	20	LF
Sta 4038+42 to 4038+59 Rt	20	LF
Total =	100	LF

$$\text{Total} = \frac{20 \text{ EI}}{100 \text{ LF}}$$

HFC-0004(202)

Structure # 04-126-17 0



LEGEND

Fiber Rolls 12IN
Seeding Class II &
Straw Mulch

Permanent Sediment and
Erosion Control
Site 5
Billings County, ND

KLJ

10/10/2025


0:10:18 AM

AndrewKre

K:\Projects\County\ND\Billings\2103_01811_HEC_0004(202)RCN23750\CAD\Design\Plans\Sections\0277PE_005.dwg

STATE	PROJECT NO.	SECTION NO.	SHEET NO.
		77	6
ND	HEC-0004(202)		

SE1/4, Sec 33
T-144-N, R-98-W
William Romanyshyn




SW1/4, Sec 34
T-144-N, R-98-W
William Romanyshyn

261	0112	FIBER ROLLS 12IN	
		Sta 5009+62 to 5010+96 Lt	140 LF
		Sta 5010+73 to 5010+88 Rt	20 LF
		Sta 5010+86 to 5010+96 Lt	40 LF
		Sta 5011+55 to 5011+69 Rt	20 LF
		Sta 5011+63 to 5011+77 Lt	20 LF
		Sta 5013+22 to 5013+27 Lt	20 LF
		Total =	260 LF

HEC-0004(202)

St. Louis 66-127-06-9




LEGEND

Fiber Rolls 12IN


Permanent Sediment and
Erosion Control
Site 6
Billings County, ND

BY	CHK'D. BY	PROJECT NO.
AK	SPK	2103-01811

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
			ND	HEC-0004(202)



261 0112 FIBER ROLLS 12IN
 Sta 6008+79 to 6009+71 Rt 100 LF
 Sta 6010+17 to 6010+31 Rt 20 LF
 Sta 6010+19 to 6010+31 Lt 20 LF
 Sta 6010+86 to 6010+99 Lt 20 LF
 Sta 6010+86 to 6011+02 Rt 20 LF
 Total = 180 LF



HEC-0004(202)


Structure # 04-110-48,0

LEGEND	
	Fiber Rolls 12IN
	Seeding Class II & Straw Mulch

Permanent Sediment and
 Erosion Control
 Site 7
 Billings County, ND



DRAWN BY AK
 CHECKED BY SPK
 PROJECT NO. 2103-01811



SW1/4SE1/4, Sec 29
T-142-N, R-98-W
Andrew J Klym


PROJECT NO.	SECTION NO.	SHEET NO.
HEC-0004(202)	80	2

752	0200	FENCE BARBED WIRE 4 STRAND	
		Sta 4037+31 to 4037+62 Lt	59 LF
		Sta 4037+79 to 4037+88 Rt	51 LF
		Sta 4038+26 to 4038+36 Lt	51 LF
		Sta 4038+44 to 4038+83 Rt	64 LF
		Total =	225 LF

752	3995	DOUBLE BRACE ASSEMBLY-WOOD POST
	Sta 4037+60 - 27' Lt	1 EA
	Sta 4037+79 - 28' Rt	1 EA
	Sta 4038+27 - 28' Lt	1 EA
	Sta 4038+46 - 27' Rt	1 EA
	Total =	4 EA

Note


Install temporary fencing until permanent fencing is in place. The cost of temporary fence is incidental to other items.



LEGEND		HEC-0004(202)	
	Fence Barbed Wire 4 Strand	Structure # 04-126-17.0	
	Corner Assembly Wood Post	Fencing Layout	
	Double Brace Assembly Wood Post	Site 5 Billings County, ND	
	Vehicle Gate Assembly	UNWRN. BY AK	CHKD. BY SPK
		PROJECT NO. 2103-01811	

Note

Install temporary fencing until permanent fencing is in place. The cost of temporary fence is incidental to other items.



LEGEND	
	Fence Barbed Wire 4 Strand
	Corner Assembly
	Wood Post
	Double Brace Assembly Wood Post
	Vehicle Gate Assembly

HFC-0004(202)


Structure # 04-127-06-0

Fencing Layout


Site 6
Billings County, ND


The logo for KLJ, featuring a stylized 'K' and 'L' intertwined with a 'J'.

ALIGNMENT SURVEY COORDINATE DATA - MULTIPLE LOCATIONS							STATE	PROJECT NO.	SECTION NO.	SHEET NO.				
								ND	HEC-0004(202)	81	1			
HORIZONTAL ALIGNMENT							HORIZONTAL ALIGNMENT							
POINT	STATION	NORTHING	EASTING	LATITUDE	LONGITUDE	DESCRIPTION	POINT	STATION	NORTHING	EASTING	LATITUDE *	LONGITUDE	DESCRIPTION	
Site 1 - Franks Creek Road (Chain 10818)							Site 4 - 26th St SW (Chain 26STS)							
BEGIN	0+00.00	526,192.84	1,217,907.12	47°04'12.146" N	103°30'46.465" W		BEGIN	7000+00.00	511,035.04	1,321,266.56	47°02'19.041" N	103°05'46.805" W		
PC	3+00.00	526,142.26	1,218,202.83	47°04'11.759" N	103°30'42.168" W		PC	7000+51.86	511,033.40	1,321,318.40	47°02'19.042" N	103°05'46.056" W		
PI	7+83.44	526,060.76	1,218,679.34	47°04'11.136" N	103°30'35.244" W		PI	7001+95.42	511,028.85	1,321,461.88	47°02'19.044" N	103°05'43.983" W		
PT	11+27.16	525,579.91	1,218,729.26	47°04'06.412" N	103°30'34.257" W		PT	7003+38.02	510,995.92	1,321,601.60	47°02'18.764" N	103°05'41.951" W		
PC	14+91.40	525,217.62	1,218,766.87	47°04'02.853" N	103°30'33.514" W		END	7004+07.60	510,979.96	1,321,669.34	47°02'18.629" N	103°05'40.966" W		
PI	18+30.82	524,880.01	1,218,801.91	47°03'59.536" N	103°30'32.821" W									
PT	21+09.18	524,736.13	1,219,109.33	47°03'58.233" N	103°30'28.304" W		Site 5 - 23rd St SW (Chain 12617)							
END	24+09.18	524,608.97	1,219,381.05	47°03'57.081" N	103°30'24.311" W		BEGIN	4000+00.00	527,128.19	1,311,227.88	47°04'54.502" N	103°08'19.471" W	Sec Cor	
							END	4052+86.19	526,939.11	1,316,510.69	47°04'54.381" N	103°07'03.085" W	Sec Cor	
Site 2 - Franks Creek Road (Chain 10919)							Site 6 - 123rd Ave SW (Chain 12706)							
BEGIN	1000+00.00	523,440.97	1,226,369.26	47°03'48.188" N	103°28'42.794" W		BEGIN	5000+00.00	584,799.88	1,323,723.73	47°14'27.539" N	103°05'46.541" W	Sec Cor	
PC	1007+18.75	523,959.45	1,226,867.04	47°03'53.488" N	103°28'35.892" W		END	5026+36.73	587,435.22	1,323,809.04	47°14'53.564" N	103°05'46.567" W	Qtr Cor	
PI	1009+33.52	524,114.37	1,227,015.78	47°03'55.072" N	103°28'33.830" W									
PT	1011+45.06	524,218.38	1,227,203.69	47°03'56.168" N	103°28'31.174" W		Site 7 - East River Road (Chain 11048)							
END	1014+30.43	524,356.58	1,227,453.35	47°03'57.625" N	103°28'27.646" W		BEGIN	6000+00.00	365,547.00	1,227,212.30	46°37'51.024" N	103°27'04.951" W		
							PC	6003+50.00	365,732.75	1,227,508.94	46°37'52.966" N	103°27'00.803" W		
Site 3 - Franks Creek Road (Chain 11019)							PI	6006+42.49	365,887.97	1,227,756.84	46°37'54.589" N	103°26'57.337" W		
BEGIN	2000+00.00	523,539.56	1,230,605.05	47°03'50.741" N	103°27'41.704" W		PT	6009+11.82	366,165.15	1,227,850.23	46°37'57.358" N	103°26'56.149" W		
PC	2003+00.00	523,504.20	1,230,902.96	47°03'50.503" N	103°27'37.384" W		END	6016+07.16	366,824.10	1,228,072.24	46°38'03.940" N	103°26'53.324" W		
PI	2008+00.99	523,445.16	1,231,400.46	47°03'50.105" N	103°27'30.171" W									
PT	2011+99.25	522,975.35	1,231,574.47	47°03'45.536" N	103°27'27.403" W		Site 8 - 123rd Ave SW (Chain 12721)							
PC	2017+95.20	522,416.50	1,231,781.46	47°03'40.101" N	103°27'24.112" W		BEGIN	3000+00.00	508,330.90	1,321,181.22	47°01'52.336" N	103°05'46.746" W	Qtr Cor	
PI	2022+53.91	521,986.35	1,231,940.78	47°03'35.917" N	103°27'21.578" W		END	3026+34.49	510,964.08	1,321,264.31	47°02'18.340" N	103°05'46.803" W	Sec Cor	
PT	2026+11.30	521,950.83	1,232,398.11	47°03'35.736" N	103°27'14.958" W									
END	2027+24.23	521,942.08	1,232,510.70	47°03'35.692" N	103°27'13.328" W		Site 9 - 123rd Ave SW (Chain 12721)							
							BEGIN	3079+07.48	516,234.43	1,321,431.28	47°03'10.388" N	103°05'46.909" W	Sec Cor	
Site 4 - 123rd Ave SW (Chain 12721)														
BEGIN	3000+00.00	508,330.90	1,321,181.22	47°01'52.336" N	103°05'46.746" W	Qtr Cor								
PI	3026+34.49	510,964.08	1,321,264.31	47°02'18.340" N	103°05'46.803" W	Sec Cor								
END	3079+07.48	516,234.43	1,321,431.28	47°03'10.388" N	103°05'46.909" W	Sec Cor								
NOTES: Survey is based upon North Dakota State Plane System, NAD83(2011), South Zone, US Survey Feet Coordinates are grid coordinates. Combined scale factor to go from Grid Distance to Ground Distance = 1.0001915367 Vertical Control Datum: North American Vertical Datum 1988 (NAVD 88), Geoid 18							<input type="checkbox"/> Assumed Coordinates	HEC-0004(202)						
							<input checked="" type="checkbox"/> All coordinates on this sheet are GRID coordinates. They are derived from the "North Dakota State Plane Coordinate System of 1983", NAD83(2011), South Zone. Units are in U.S. Survey Feet.	Multiple Locations						
								Survey Coordinate and Curve Data						
								Billings County, ND						
								DRAWN BY AK CRKD BY JAC PROJECT NO. 2103-01811						



ALIGNMENT SURVEY COORDINATE DATA - MULTIPLE LOCATIONS								STATE	PROJECT NO.	SECTION NO.	HEET NO.		
		ND	HEC-0004(202)	81	2								
SURVEY CONTROL POINTS						SURVEY CONTROL POINTS							
POINT	STATION	NORTHING	EASTING	LATITUDE	LONGITUDE	DESCRIPTION	POINT	STATION	NORTHING	EASTING	LATITUDE *	LONGITUDE	DESCRIPTION
Site 1 - Franks Creek Road													
GPS2	524,575.44	1,220,067.23	2293.5	47°03'57.010" N	103°30'14.388" W	1" KLJ Alum Cap							
GPS6	529,811.39	1,214,514.84	2435.3	47°04'46.550" N	103°31'37.451" W	1" KLJ Alum Cap							
BM11	525,248.85	1,218,842.68	2257.2	47°04'03.189" N	103°30'32.437" W	#4 Rebar							
BM12	525,548.44	1,218,671.54	2248.9	47°04'06.080" N	103°30'35.073" W	#4 Rebar							
Site 2 - Franks Creek Road													
BM7	523,954.76	1,226,741.65	2293.5	47°03'53.395" N	103°28'37.699" W	#4 Rebar							
BM8	523,698.27	1,226,698.85	2285.4	47°03'50.849" N	103°28'38.177" W	#4 Rebar							
Site 3 - Franks Creek Road													
BM9	522,725.60	1,231,578.38	2314.1	47°03'43.074" N	103°27'27.211" W	#4 Rebar							
BM10	522,619.60	1,231,758.57	2318.3	47°03'42.095" N	103°27'24.553" W	#4 Rebar							
Site 4 - 123rd Ave SW													
BM1	511,104.56	1,321,365.75	2536.4	47°02'19.759" N	103°05'45.407" W	1" KLJ Alum Cap							
BM2	510,723.50	1,321,183.92	2542.8	47°02'15.941" N	103°05'47.849" W	#5 Rebar							
Site 5 - 23rd St SW													
CP3	527,186.78	1,307,079.45	2670.3	47°04'53.700" N	103°09'19.411" W	1" KLJ Alum Cap							
BM3	526,926.94	1,314,848.41	2577.9	47°04'53.714" N	103°07'27.086" W	1" KLJ Alum Cap							
BM4	527,057.00	1,315,221.33	2574.4	47°04'55.120" N	103°07'21.762" W	1" KLJ Alum Cap							
Site 6 - 123rd Ave SW													
CP1	584,225.50	1,327,072.67	2508.3	47°14'22.962" N	103°04'57.757" W	1" KLJ Alum Cap							
RP4	590,016.84	1,326,528.42	2454.2	47°15'19.916" N	103°05'08.402" W	#4 Rebar							
BM5	585,826.50	1,323,829.85	2429.9	47°14'37.701" N	103°05'45.495" W	#4 Rebar							
BM6	586,052.87	1,323,673.96	2429.3	47°14'39.883" N	103°05'47.862" W	#4 Rebar							
Site 7 - East River Road													
BM13	366,445.08	1,228,063.05	2422.9	46°38'00.198" N	103°26'53.252" W	#4 Rebar							
BM14	366,212.96	1,227,779.64	2407.6	46°37'57.803" N	103°26'57.185" W	1" KLJ Alum Cap							
NOTES: Survey is based upon North Dakota State Plane System, NAD83(2011), South Zone, US Survey Feet Coordinates are grid coordinates. Combined scale factor to go from Grid Distance to Ground Distance = 1.0001915367 Vertical Control Datum: North American Vertical Datum 1988 (NAVD 88), Geoid 18							<input type="checkbox"/> Assumed Coordinates	HEC-0004(202)					
							<input checked="" type="checkbox"/> All coordinates on this sheet are GRID coordinates. They are derived from the "North Dakota State Plane Coordinate System of 1983", NAD83(2011), South Zone. Units are in U.S. Survey Feet.	Multiple Locations					
								Survey Coordinate and Curve Data Billings County, ND					
								DRWN. BY	CHKD. BY	PROJECT NO.			
								AK	JAC	2103-01811			







Traffic Control Devices List

Work Zone Traffic Control

Billings County, ND

STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND	HEC-0004(202)	100	2

CONSTRUCTION SIGN LAYOUT



HEC-0004(202)

Multiple Locations




Work Zone
Traffic Control
Sites 1, 2, & 3
Billings County, ND

DRWN. BY AK	CHKD. BY SPK	PROJECT NO. 2103-01811
----------------	-----------------	---------------------------


The sign layout as shown is for general information purposes only. The Contractor will be required to conform to MUTCD and the Standard Drawings when installing the traffic control signing.

	STATE	PROJECT NO.	SECTION NO.	HEET NO.
	ND	HEC-0004(202)	100	3

CONSTRUCTION SIGN LAYOUT



The sign layout as shown is for general information purposes only. The Contractor will be required to conform to MUTCD and the Standard Drawings when installing the traffic control signing.



HEC-0004(202)

Multiple Locations




Work Zone
Traffic Control
Sites 4 & 5
Billings County, ND

DRWN. BY AK	CHKD. BY SPK	PROJECT NO. 2103-01811
----------------	-----------------	---------------------------


© KLJ 2025

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	HEC-0004(202)	100	4

CONSTRUCTION SIGN LAYOUT



The sign layout as shown is for general information purposes only. The Contractor will be required to conform to MUTCD and the Standard Drawings when installing the traffic control signing.



HFC-0004(202)

Multiple Locations





Work Zone
Traffic Control
Site 6
Billings County, ND

DRWN, BY AK	CHKD, BY SPK	PROJECT NO. 2103-01811
----------------	-----------------	---------------------------

STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND	HEC-0004(202)	100	5

CONSTRUCTION SIGN LAYOUT



HEC-0004(202)


Multiple Locations





Work Zone
Traffic Control
Site 7
Billings County, ND


DRWN. BY AK	CHKD. BY SPK	PROJECT NO. 2103-01811
----------------	-----------------	---------------------------

The sign layout as shown is for general information purposes only. The Contractor will be required to conform to MUTCD and the Standard Drawings when installing the traffic control signing.









GUARDRAIL STAKING DIAGRAM

Guardrail Embankment (F)

Reshaping Roadway (By County Forces)

NOTES:

- (A1) Install a MASH Sequential Kinking end terminal at this location. See Standard Drawing D-764-51.
- (A2) Install a FLEAT end terminal at this location. See Standard Drawing D-764-38.
- (B) Thrie-Beam Transition. See Sheet 130-1. Include all material and work involved to install the Thrie-Beam Transition in the unit price bid for "W-BEAM GUARDRAIL".
- (C) End of concrete endpost to center of timber post.
- (D) Remove, salvage, and stockpile all existing object markers at the bridge ends for County pickup. Extend each existing concrete endpost as shown on Sheet 130-1. Connect rail to concrete endpost by drilling holes through it. The thickness of the concrete endpost is approximately 13-inches. Provide hex bolts of sufficient length to extend through the full thickness of the concrete endpost, rail, connector plate, washers, and nut. Include all costs in the unit price bid for "W-BEAM GUARDRAIL".
- (E) Curved Rail Section R = 125.42'.
- (F) See Standard Drawing D-764-48. Include all material and work involved to widen for guardrail installation in the unit price bid for "GUARDRAIL EMBANKMENT". Refer to Standard Drawing D-764-40 for additional details.

All offsets to back face of W-Beam.



HEC-0004(202)


Structure # 04-110-19.0



MGS W-Beam
Guardrail Layout
Site 3
Billings County, ND

DRWN. BY AK	CHKD. BY SMM	PROJECT NO. 2103-01811
----------------	-----------------	---------------------------

QUANTITIES		
GUARDRAIL EMBANKMENT	4 EA	
PIPE CORR STEEL .079IN 24IN POLYMERIC COATED	4 LF	
REMOVE & RELAY END SECTION-ALL TYPE & SIZES	1 EA	
W-BEAM GUARDRAIL	182.6 LF	
W-BEAM GUARDRAIL END TERMINAL	4 EA	



GUARDRAIL STAKING DIAGRAM

NOTES: _____

WBI ENERGY PL _____

(A1) Install a Sequential Kinking end terminal at this location. See Standard Drawing D-764-5. _____

(A2) Install a FLOAT end terminal at this location. See Standard Drawing D-764-6. _____

(B) See Standard Drawing D-764-10. Connection is to existing concrete endpost. Install connector plate as shown on Sheet 130-1 behind the endpost. Include all material and work involved to install the Thrie Beam Transition in the unit price bid for "W-BEAM GUARDRAIL".

(C) End of concrete endpost to center of timber post.

(D) Remove, salvage, and stockpile all existing object markers at the bridge ends for County pickup. Extend each existing concrete endpost as shown on Sheet 130-1. Connect rail to concrete endpost by drilling holes through it. The thickness of the concrete endpost is approximately 13-inches. Provide hex bolts of sufficient length to extend through the full thickness of the concrete endpost, rail, connector plate, washers, and nut. Include all costs in the unit price bid for "W-BEAM GUARDRAIL".

(E) Curved Rail Section R = 125.42'.

(F) See Standard Drawing D-764-22. Include all material and work involved to widen for guardrail installation and modify approaches in the unit price bid for "GUARDRAIL EMBANKMENT".

(G) Radius = 8'

(H) Install Special W-Beam Guardrail Anchor at this location. See Standard Drawing D-764-14. Include all costs in the unit price bid for "W-BEAM GUARDRAIL".

(I) Radius = 32'

Refer to Standard Drawings D-764-1 and D-764-13 for additional details.

All offsets to back face of W-Beam.





HEC-0004(202)

Structure # 04-127-21.0

W-Beam
Guardrail Layout
Site 4
Hills County, ND

QUANTITIES	
GUARDRAIL EMBANKMENT	4 EA
W-BEAM GUARDRAIL	270.3 LF
W-BEAM GUARDRAIL END TERMINAL	3 EA






HEC-0004(202)

Structure # 04-127-060



W-Beam
Guardrail Layout
Site 6
Billings County, ND

QUANTITIES	
GUARDRAIL EMBANKMENT	4 EA
PIPE CORR STEEL .064IN 18IN	62 LF
END SECT CORR STEEL .064IN 18IN	2 EA
W-BEAM GUARDRAIL	182.6 LF
W-BEAM GUARDRAIL END TERMINAL	4 EA



NOTES:

- (A1) Install a Sequential Kinking end terminal at this location. See Standard Drawing D-764-5.
- (A2) Install a FLEAT end terminal at this location. See Standard Drawing D-764-6.
- (B) Post space for guardrail is 6'-3" unless dimensioned otherwise.
- (C) Remove, salvage, and stockpile all existing object markers at the bridge ends for County pickup. Connect to Existing Bridge Railing. Include all costs in the unit price bid for "W-BEAM GUARDRAIL".
- (D) Curved Rail Section R = 125.42'.
- (E) See Standard Drawing D-764-22. Include all material and work involved to widen for guardrail installation in the unit price bid for "GUARDRAIL EMBANKMENT".
- (F) Replace existing timber post with new timber post. Include all material and work involved in the unit price bid for "W-BEAM GUARDRAIL".






HEC-0004(202)

Structure # 04 110 48 0

W-Beam
Guardrail Layout
Site 7
Illings County, ND

QUANTITIES	
GUARDRAIL EMBANKMENT	4 EA
W-BEAM GUARDRAIL	175.0 LF
W-BEAM GUARDRAIL END TERMINAL	4 EA




DOUBLE BOX BEAM BID ITEMS (04-126-17.0)

SPEC	CODE	ITEM DESCRIPTION	UNIT	QUANTITY
624	3002	DOUBLE BOX BEAM RAIL RETROFIT - E-RAIL	LF	135.0

DOUBLE BOX BEAM BID ITEMS (04-127-06.0)

SPEC	CODE	ITEM DESCRIPTION	UNIT	QUANTITY
624	3002	DOUBLE BOX BEAM RAIL RETROFIT - E-RAIL	LF	149.9



HEC-0004(202)


Structure # 04-126-17.0 & Structure # 04-127-06.0

	Double Box Beam E-Rail Layout	
	Billings County, ND	
DRWN. BY SMM	CHKD. BY CDB	PROJECT NO. 2103-01811


23 U.S.C. § 407 Documents
NDDOT Reserves All Objections

The filled circles indicate drilled and tapped holes for $\frac{7}{8}$ "^ø bolts M 164 (A 325). See Detail "B".


STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND	HEC-0004(202)	170	2




(Concrete Rail Connection)
BAR 5 X 1/2 X 10 3/4" DETAIL




(Concrete Rail Connection)
BAR 5 X 1/2 X 1'-4" DETAIL




(Rail Connection)
BAR 5 X 1/2 X 1'-0" DETAIL




(Concrete Post Connection)
BAR 5 X 1/2 X 1'-5 1/2" DETAIL




1/4" & 5/16" Thickness
Quantities Determined in Field
SHIM PLATE DETAIL




The open circle indicates a drilled hole through the 1/2" plate for a 7/8"ø bolt M 164 (A 325).



GUARDRAIL CONNECTION PLATE DETAILS



CONNECTION ANGLE DETAILS



(Concrete Post Connection)
BAR 3 X 1/2 X 1'-5 1/2" DETAIL

Fabricate rail elements from square structural tubing in accordance with ASTM Specification A 500 Grade B.

Supply steel plates and angles conforming to AASHTO Specification M 270 Grade 36, unless otherwise noted.

Fabricate railing to the horizontal and vertical alignment of the structure.

Include costs for furnishing and installing the guardrail connection plates in "DOUBLE BOX BEAM RAIL RETROFIT - E-RAIL".

Hot-dip galvanize structural steel after fabrication according to AASHTO M 111.

Fabricate rails so that each rail segment between splices is attached to a minimum of two posts.


Supply threaded rods meeting M 270 Grade 36 Steel and galvanize according to M 232. Tighten the threaded rods to provide a minimum tensile force of 2,500 lbs. and a maximum tensile force of 2,700 lbs.

Embed the anchor bolts into the concrete with a chemical adhesive system that can develop a tensile strength of at least 17,500 lbs.

Supply all anchor and splice bolts meeting AASHTO M 164 (A 325) and be galvanized according to M 232.


The contractor must field verify all dimensions and incorporate them into the shop drawings. Submit the double box beam rail retrofit work drawings to the Engineer for approval before fabrication.

Position washers to completely cover slotted holes.




(1/4" R AASHTO M 270 Grade 36)

R WASHER "C"




RAIL SPLICE DETAIL



Rail cap shall be a Bar 4 3/4 x 3/16 x 4 3/4". Cope corners 1" to provide Zinc drains.
Install angle with washers and self-locking nuts or nuts and jam unit.

RAIL CAP DETAILS



DETAIL "B"



HEC-0004(202)

Structure # 04-126-17-0 & Structure # 04-127-06-0

Double Box Beam
E-Rail Retrofit Details


Billings County, ND

DRWN. BY SMM CHKD. BY WDT PROJECT NO. 2103-01811





	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
	ND	HEC-0004(202)	170	3

23 U.S.C. § 407 Documents
NDDOT Reserves All Objections



DOUBLE BOX BEAM E-RAIL RETROFIT PART ELEVATION



HEC-0004(202)

Structure # 04-126-17-0 & Structure # 04-127-06-0


Double Box Beam -Rail Retrofit Details

Billings County, ND

The logo for KJL, featuring a stylized 'K' and 'J' intertwined with a central 'L'.


Double Box Beam Rail Retrofit Details


DRWN. BY SMM	CHK'D. BY CDB	PROJECT NO. 2103-01811
-----------------	------------------	---------------------------



Site 1


	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	HEC-0004(202)	200	2	






Site 3


	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	HEC-0004(202)	200	4	



Site 3


	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	HEC-0004(202)	200	5	








Site 6

	STATE	PROJECT NO.	SECTION NO.	HEET NO.
ND	HEC-0004(202)	200	7	





Site 6

	STATE	PROJECT NO.	SECTION NO.	SHEET NO.
ND	HEC-0004(202)	200	9	

