## **RESEARCH REPORT DOCUMENTATION PAGE**

1. Report No.	2. Report Date	3. Contract No.		4. Project No.
5. Title and Subtitle	February 2020	N/A	6. Report Type	5U-2-987 (U29)U33 7. Project No.
Evaluation of ScourStop® Flow Transition Mats For Scour Protection			Click on link to open report	8. Project No. 9. Project No. 10. Project No.
11. Author(s)/Principle Investigator(s)				
12. Performing Organization Name and Addre	ess	13. Sponsoring Agency Name and Ad	dress	
IDDOT M+R       Image: Morth Dakota DOT         IDDOT OTHER*       Image: Materials and Research Division         IDSU       Image: State Stat		North Dakota DOT Materials and Research Division 300 Airport Road Bismarck ND 58504-6005		
14. Supplementary Notes				
15. Abstract Purpose and Need Storm water flow from culverts and pavement in urban and rural settings can accelerate soil scour and erosion in turn impeding proper drainage which then may require maintenance to restore. Rip-rap and TRM "turf reinforcement mat" is currently used as a permanent scour and erosion protection, but rip-rap reventment may erode away and disintegrate over time requiring periodic maintenance. Rip-rap also may pose a safety hazard to children in residential settings and can collect debris and weeds producing an aesthetically unappealing structure. Flow Transition Mats are designed to replace rip-rap reventment as a permanent maintenance free scour and erosion protection system at culverts, pipes, and pavement drainage areas. Mats allow vegetation to become established and protect flow paths from erosion. Objective The objective of this experimental project is to evaluate the performance of ScourStop® Flow Transition Mats as a permanent method for energy dissipation to prevent scour downstream from culverts, pipes, or pavement. Scope NDDOT plans to incorporate ScourStop® Flow Transition Mats as part of project SU-2-987(029)033. This project is located near Jamestown Business Loop East respectively. Summary The four installations of ScourStop® were successfully installed according to the plans and manufacturer's recommendation and are performing as designed with some sod distress. The top soil adjacent to the installations was eroded away during the flood of 2011 prior to installation. This resulted in a low success rate of the permanent seeding around the ScourStop® installations. The picture in photo 18 captures the state of the permanent seeding in August of 2012. The sod appears to be growing with the exception of the two installations. The sol condition has not impacted the performance of these two installations ability to protect against scour.				
16. Key Words Flow Transition Mat ScourStop Culvert Erosion	17. Distribution Statement No restrictions. This North Da Mat	document is available kota Department of erials and Research 300 Airport Roa Bismarck ND 58504	e <mark>by clicking this link:</mark> Transportation Division: d -6005	18. No. of Pages 23 19. File type Pdf