

1. Report No. UND 06-03	2. Report Date December 2008	3. Contract No. N/A	4. Project No. NH-6-081(053)192
5. Title and Subtitle Evaluation of Coarse-Graded Superpave HMA Pavements in North Dakota Using Asphalt Pavement Analyzer		6. Report Type Click on link to open report Work Plan <input type="checkbox"/> Construction <input type="checkbox"/> Evaluation <input type="checkbox"/> Final <input checked="" type="checkbox"/>	7. Project No. 8. Project No. 9. Project No. 10. Project No.
11. Author(s)/Principle Investigator(s) Dr. Nabil Suleiman, Principal Investigator			
12. Performing Organization Name and Address NDDOT M+R <input type="checkbox"/> North Dakota DOT NDDOT OTHER* <input type="checkbox"/> Materials and Research Division NDSU <input type="checkbox"/> 300 Airport Road UND <input checked="" type="checkbox"/> Bismarck ND 58504-6005 UGPTI <input type="checkbox"/> OTHER* <input type="checkbox"/> *see supplementary notes		13. Sponsoring Agency Name and Address North Dakota DOT Materials and Research Division 300 Airport Road Bismarck ND 58504-6005	
14. Supplementary Notes			
15. Abstract Objective To evaluate the rutting resistance performance of coarse-graded Superpave HMA pavement cores using the asphalt pavement analyzer. To carry out permeability tests on coarse-graded field specimen cores obtained from different locations on US Highway 81 north of Grafton, ND. To identify the in-place air void percentage of coarse-graded Superpave HMA pavement from Highway 81 north of Grafton, ND. Scope The scope of the work consists of receiving coarse-graded Superpave field cores from three different locations on US Highway 81 north of Grafton, ND and testing their rut resistance performance and permeability. Rut resistance performance will be tested under dry and wet conditions using the APA. Summary For this study, the rutting resistance of the coarse-graded mix was evaluated on field cores and tested using the asphalt pavement analyzer. Asphalt permeability and the air voids utilizing field cores were also determined. Statistical analysis indicated that the variations within the wet and dry APA results were significant but the variations for APA results within sections, air voids results, or permeability results were insignificant. The APA results show that 50 percent of the dry tested core specimens across the project sections of the coarse graded mix have exhibited satisfactory rutting resistance. All but one of the 18 wet tested specimens has failed the APA rut depth specification.			
16. Key Words Asphalt Superpave Rutting Aggregate	17. Distribution Statement No restrictions. This document is available to the public from: North Dakota Department of Transportation Materials and Research Division: 300 Airport Road Bismarck ND 58504-6005 Office: (701) 328-6900 Fax: (701) 328-0310		18. No. of Pages 26 19. File type/Size PDF / 200 KB