SINGLE USE CONCRETE CYLINDER MOLD VERIFICATION PROCEDURE #45

May 2, 2002

Equipment Checked: SINGLE USED CONCRETE CYLINDER MOLDS (AASHTO T 23 & AASHTO M205)

Purpose:

This method provides instructions for checking elongation, strength, absorption, and water leakage of paper molds. For plastic molds, check for water leakage and strength.

Inspection Equipment Required:

- 1. Caliper readable to 0.001:
- 2. Balance readable to 0.1 gram
- 3. Glass plate to cover 6" diameter cylinder
- 4. Tapping rod

Tolerance:

The molds shall meet the tolerances listed in AASHTO M 205

Procedure:

- 1. Fill mold with dry crushed coarse aggregate passing the ¾" sieve and retained on the No.4. Fill mold in three layers, rodding each layer 25 times. After rodding final layer, empty the mold of the aggregate. Wipe inside of mold with dry cloth and check for physical damage.
- 2. Weigh mold to the nearest 0.1 gram and measure the height to the nearest 0.001".
- 3. Place mold on firm flat surface and fill with water at room temperature to a depth of 90 to 95% of the mold height.
- 4. Place mold on the dial stand, cover mold with the glass plate and using the caliper, record the mold height to the nearest 0.001".
- 5. Allow mold to stand for three hours and take a second reading with the caliper. Examine and record any visible leakage. Empty water from mold, dry lightly with towel, and record the final weight to the nearest 0.1 gram.
- 6. Calculate elongation as the difference between the final height and the initial height. Calculate absorption as the difference between the final weight and the initial weight.

EQUIPMENT CALIBRATION RECORD

Calibration Procedure No. 45 Concrete Cylinder Molds – Single Use (AASHTO T 23 & AASHTO M 205)

	Date:				Calibrated by:		
	Previous Calibration Date:				Next Due:		
	ID No.:						
	Frequency: Each Shipment						
	Calibration Equipment				Serial Number		
	Height		<u> 1</u>		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
	Glass p	late 7x7" ¼"	thick				
	Balance	e readable to	o 0.1 g				
	Comments:						
	Condition of Molds after Rodding: Good				Bad		
Weight	t of Mold	#2 	#3	#4	#5 	#6 	Final
	_						Initial
Height ———	of Molds -				<u> </u>		Final
	_						Initial
Diame	ter						
Length	-						
Δny nh	- ovsical da	mage or leaki	ing?				

Any physical damage or leaking?

5/3/2002