

1. Report No. ND 03-02	2. Report Date December 2009	3. Contract No. N/A	4. Project No. AC-IM-2-094(070)275
5. Title and Subtitle  Concrete Bridge Deck Sealants		6. Report Type <b>Click on link to open report</b>  Work Plan <input type="checkbox"/> Construction <input type="checkbox"/> Evaluation <input type="checkbox"/> <u>Final</u> <input checked="" type="checkbox"/>	7. Project No. 8. Project No. 9. Project No. 10. Project No.
11. Author(s)/Principle Investigator(s) Andrew Mastel and Brian Fuchs			
12. Performing Organization Name and Address  NDDOT M+R <input checked="" type="checkbox"/> North Dakota DOT NDDOT OTHER* <input type="checkbox"/> Materials and Research Division NDSU <input type="checkbox"/> 300 Airport Road UND <input type="checkbox"/> Bismarck ND 58504-6005 UGPTI <input type="checkbox"/> OTHER* <input type="checkbox"/> *see supplementary notes		13. Sponsoring Agency Name and Address  North Dakota DOT Materials and Research Division 300 Airport Road Bismarck ND 58504-6005	
14. Supplementary Notes			
15. Abstract  <b>Purpose and Need</b> When moisture and the chloride ions penetrate deep enough, the reinforcing steel starts to corrode. This corrosion causes extreme pressure in the concrete due to the volume change in the steel. This volume change starts to slowly break the concrete apart. With the intrusion of water into the concrete, small voids are filled with water and become susceptible to freeze thaw cycles causing internal expansion within the concrete resulting in deterioration. When a bridge deck is 20% delaminated, a bridge deck overlay is usually the rehabilitation option chosen, provided the structure is not deficient or in need of replacement. However, for the bridge decks that have delamination of less than 20%, the NDDOT does not currently have another rehabilitation or maintenance option available for use.  <b>Objective</b> For bridge decks with very little delamination, another alternative needs to be available to protect the concrete so the bridge can remain in service for a longer time before the public is inconvenienced by rehabilitation of the bridge deck. One method is to apply a concrete surface and crack sealer to the existing concrete bridge deck. If the delamination is from corroding reinforcing steel, the sealer may create a barrier that will stop the intrusion of water and deicing chemicals; thereby slowing the further corrosion of the steel. Further deterioration caused by the expansion of freezing water in small voids may be stopped if the intrusion of water can be halted. This study proposes to compare the performance of several different products used to seal the concrete surface and cracks.  <b>Scope</b> A literature search was performed and several products were chosen. The three products selected are: Radcon Formula #7, Degusa Degadeck Crack Sealer, and Tamms Dural 335. Each product will be applied according to the manufacturer's recommendations. There is a total of four bridge decks in this research project. The total deck surface area for all decks combined is 2,414 SY. Each product will be applied to approximately 25% of the total surface area of the decks with 25% of the total surface area left for control sections.  <b>Summary</b> The Tamms and Degusa product have areas where excess material has been applied to the deck surfaces. This is most noticeable in the deeper tined concrete. Cracks are visibly sealed with these sealers. The Radcon product is unnoticeable as to the amount of sealer applied when dry. The depth of tining remains unchanged when Radcon is applied. It is unclear if the cracks in the Radcon section are sealed as the sealer is intended to penetrate the surface and form a gel in the cracks. The chloride sampling and chain dragging results are summarized in Tables 6 and 7. From the results of these tests it is difficult to draw conclusions to whether or not the products are meeting the manufacturer's performance characteristics.			
16. Key Words Bridge Sealants Sealers Maintenance Bridge Maintenance	17. Distribution Statement No restrictions. This document is available electronically by <a href="#">clicking this link</a> :  North Dakota Department of Transportation Materials and Research Division: 300 Airport Road Bismarck ND 58504-6005 Office: (701) 328-6900 Fax: (701) 328-0310		18. No. of Pages 95  19. File type/Size PDF/ 19 MB