







TRUCK INSPECTION ROADSIDE SITE  
PULLEY WINCH SIGN COVER FOR WARNING SIGNS



Notes:

Use 0.100 inch minimum thickness sign backing material.

Punch holes round for 3/8" bolts.

Build Pulling Winch with a self locking mechanism. Provide winch and cable attachment in compliance with SAE Standard J1853 and mount using three 3/8" diameter bolts, washers and lock washers.

Use laminated, high carbon steel gears. Copper braze drive gears and arc weld gears Rigid weld reel for added strength. Assure reel is free wheeling when ratchet is disengaged. Match gear ratio for easy cranking. Use zinc plated finish. Use heavy duty steel with molded grips for handle and embossed reinforced steel base. Provide permanently lubricated bearings for drive shafts. Include cable clamp. Provide large hub for pulling winch for use with cable operation.

Use 4" wide x 2" deep x 1/8" thick stainless steel hinges with 4-3/16"Dia [#10-24] x 5/8" long slotted countersunk flat head stainless steel stove bolts/machine screws with stainless steel locking nuts to attach to extruded panels. Place centerline of hinge pin with offset letters so sign will hang down vertically.

Use 3/8" thick steel plate conforming to AASHTO M270 Grade 36 and galvanized in conformance with ASTM A153 for pulling winch and pulley attachment hardware. Provide pulleys of approximately 3" diameter plus a 5/16" diameter cable ride. Use spacers between the hub and the attachment brackets so pulleys ride in the center of brackets without moving back and forth. Fabricate bolts, nuts and washers of steel meeting ASTM A307 and galvanized in conformance with ASTM A153.

Use double galvanized 7 strand steel wire cable not less than 3/16" diameter meeting ASTM A475.

NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
11-12-13	
REVISIONS	
DATE	CHANGE
8-30-18	Updated notes to active voice.
9-05-19	New Design Engineer PE Stamp.
8-08-24	Electronic Stamp/Signature.



08/08/24